



## PRODUCT DATA SHEET

Power Lube® Industrial High Performance Lubricant  
w/PTFE, 11 Wt Oz  
Part Number: 03045



Product Description	POWER LUBE is a high performance, multi-purpose lubricant that utilizes PTFE and extreme pressure additives to provide unparalleled lubricating performance. It has twice the load carrying capacity of most general purpose lubricants.
Applications	Bearings, gears, linkages, motors, chains, cables, rollers, guide bars, pulleys, cams, valves, ball joints, hinges, slides, cutting tools, taps, dies, pistons, handling equipment, conveyors, hoists, lifts, doors and fans.
Unit Package Description	16 Ounce Aerosol
Brand	CRC
Generic Description 1	High Performance Lubricant with PTFE
Net Fill	11 Wt Oz
UPC Code	078254030456
Unit Dimensions	7.75H x 2.63W x 2.63D in
Units Per Case	12
Case Dimensions	8.1H x 8.3W x 11.1D in
Cases Per Pallet	133
Case Weight	10 lbs
I 2 of 5 Code	30078254030457
Appearance	Light Amber Liquid w/white precipitate
Base Type	Petroleum Solvent
Flash point (F)	<20°F
Flash point (C)	<-7°C
Flammability Class - CPSC	Extremely Flammable
Spec Gravity Concentrate	0.863
Plastic Safe	No
Film Type	Wet
Film Thickness	Not Determined

Last revised: 3/2/2016  
Page 1 of 2



Customer Care: 800-556-5074  
Technical Assistance: 800-521-3168  
www.crcindustries.com

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.



## PRODUCT DATA SHEET



Evaporation Rate	Fast
Dielectric Strength	Not Determined
Working Temp (F)	Max 300°F
Working Temp (C)	Max 148.9°C
Propellant	Hydrocarbon
NSF Category Code	H2
NSF Number	017403
Aerosol Flammability Level	III
DOT Proper Shipping Name	Aerosols, Flammable, Limited Quantity
VOC % (Federal)	23.9
VOC g/L (Federal)	206.3
VOC Lbs./Gal. (Federal)	1.7
VOC Category	Multi-Purpose Lubricant
Removal (How To)	Remove with petroleum solvents or mineral spirits.

Last revised: 3/2/2016  
Page 2 of 2



Customer Care: 800-556-5074  
Technical Assistance: 800-521-3168  
www.crcindustries.com

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.