

PRODUCT DATA SHEET

White Lithium Grease, 10 Wt Oz Part Number: 03080

Product Description

Applications

Brand

Net Fill

UPC Code

Superior lubrication and durability in any weather or temperature. Perfect for use as a break-in lubricant for bearings or as a general purpose lubricant and corrosion inhibitor for tools, machinery and equipment.

Hinges, latches, overhead door tracks, open gears, chains, cables, slide conveyors, guide rails, cams, pistons, machinery, tools, & equipment. A break-in lubrication for bearings.

Unit Package Description 16 Ounce Aerosol CRC **Generic Description 1** White Lithium Aerosol Grease 10 Wt Oz 078254030807 7.75H x 2.63W x 2.63D in Unit Dimensions Units Per Case 12 **Case Dimensions** 8.1H x 8.3W x 11.1D in Cases Per Pallet 133 11 lbs 30078254030808 Off-White Viscous Grease Lithium Stearate <0°F <-18°C **Extremely Flammable** 0.6257 Yes Grease Fast 2 Working Temp (F) 0 to 300°F

> Last revised: 3/28/2016 Page 1 of 2



Customer Care: 800-556-5074 Technical Assistance: 800-521-3168 www.crcindustries.com



of CRC Industries, Inc.

and adheres to the strictest guidelines for quality in all facets of research, development and production. $CRC^{\circledast}, K\&W^{\circledast}, Sta-Lube^{\circledast}, Marykate^{\circledast} and products denoted with <math display="inline">^{\circledast}$ and $^{\intercal}$ are trademarks

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair



logh, High Viscosity Film Excellent Heat and Water Resistance Phicula de Alta Viscosidad y Resistencia Excelente Resistencia al Calor y al Agua

HINGER LIGHO:



1 01

Case Weight I 2 of 5 Code Appearance Base Type

> Flash point (F) Flash point (C) Flammability Class - CPSC Spec Gravity Concentrate Plastic Safe Film Type

NLGI Grade

Evaporation Rate



PRODUCT DATA SHEET

Working Temp (C)	-17.8 to 148.9°C
Propellant	Hydrocarbon
NSF Category Code	H2
NSF Number	017410
Aerosol Flammability Level	III
DOT Proper Shipping Name	Aerosols, Flammable, Limited Quantity
VOC % (Federal)	85
VOC g/L (Federal)	531.8
VOC Lbs./Gal. (Federal)	4.43
VOC Category	Not Regulated
Removal (How To)	Remove with Petroleum Distillates.



leigh, High Viscosity Film Englient Heat and Water Resistance Péloula de Alta Viscosidad y Resistencia Expetente Resistencia al Calor y al Agua

OANGER: EXTR LIGHO:



and adheres to the strictest guidelines for quality in all facets of research, development and production.



Customer Care: 800-556-5074 Technical Assistance: 800-521-3168 www.crcindustries.com



 $CRC^{\circledast}, K\&W^{\circledast}, Sta-Lube^{\circledast}, Marykate^{\circledast} and products denoted with <math display="inline">^{\circledast}$ and m are trademarks of CRC Industries, Inc.

Last revised: 3/28/2016 Page 2 of 2