



## PRODUCT DATA SHEET

Dielectric Grease, 10 Wt Oz  
Part Number: 03082



Product Description	Non-curing silicone compound used for electrical sealing, lubricating, protecting and insulating. Waterproofs electrical connections and components. Improves electrical performance in adverse weather conditions.
Applications	Electrical panels, outdoor lighting, scoreboards, traffic lights, high voltage poles, transformers, disconnects, switching mechanisms, electrical contacts, spark plugs, battery terminals, fasteners, o-rings, rubber and plastic parts.
Unit Package Description	16 Ounce Aerosol
Brand	CRC
Generic Description 1	Non Curing Silicone Lubricating Compound with Perma-Lock™
Net Fill	10 Wt Oz
UPC Code	078254030821
Unit Dimensions	7.75H x 2.63W x 2.63D in
Units Per Case	12
Case Dimensions	8.1H x 8.3W x 11.1D in
Cases Per Pallet	133
Case Weight	11 lbs
I 2 of 5 Code	30078254030822
Appearance	Translucent to Opaque Gel Paste
Base Type	Silicone
Flash point (F)	<20°F
Flash point (C)	<-7°C
Flammability Class - CPSC	Extremely Flammable
Spec Gravity Concentrate	0.646
Plastic Safe	Safe on Most Plastics
Film Type	Non-Curing Silicone Paste
Evaporation Rate	Fast

Last revised: 3/28/2016  
Page 1 of 2



Customer Care: 800-556-5074  
Technical Assistance: 800-521-3168  
www.crcindustries.com

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.



## PRODUCT DATA SHEET



Dielectric Strength	500 Volts/Mil
NLGI Grade	2
Working Temp (F)	-70 to 400°F
Working Temp (C)	-56.7 to 204.4°C
Propellant	Hydrocarbon
NSF Category Code	H1
NSF Number	130627
Aerosol Flammability Level	III
DOT Proper Shipping Name	Aerosols, Flammable, Limited Quantity
VOC % (Federal)	90.1
VOC g/L (Federal)	582
VOC Lbs./Gal. (Federal)	4.85
VOC Category	Not Regulated
Removal (How To)	Remove with Petroleum Distillates.

Last revised: 3/28/2016  
Page 2 of 2



Customer Care: 800-556-5074  
Technical Assistance: 800-521-3168  
www.crcindustries.com

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.