





**Product Description** 

A high purity, NLGI Grade 1.5 multi-purpose white lithium grease. Provides superior lubrication & durability in any weather and most temperatures. Bright white in color.

Ideal for when appearance is important.

**Applications** 

Assembly lubes, bearings, break-in lubrication for bearings, cables, chains, chassis points, conveyor bearings, door tracks, garage door channels & openers, hinges, latches, machinery, open gears, overhead door tracks, roller bearings, sleeve bearings.

Unit Package Description

14 Ounce Can

**Brand** 

Sta-Lube

Generic Description 1

Super White Multi-Purpose Grease

Net Fill

14 Wt Oz

**UPC** Code

072213315103

**Unit Dimensions** 

3.44H x 4.13W x 4.13D in

Units Per Case Case Dimensions

12

3.5H x 12.5W x 17D in

Cases Per Pallet

96

Case Weight

13 lbs

I 2 of 5 Code

30072213315104

**Appearance** 

White Semi-Solid to Solid Grease

Base Type

Lithium-12

Flash point (F)

475°F

Flash point (C)

246°C

Flammability Class - CPSC

None

Spec Gravity Concentrate

0.9 at 60°F

**NLGI** Grade

1.5

Timken OK Load [Lbs.]

25 Lbs

Plastic Safe

Not Determined

**Evaporation Rate** 

<0.01 (Butyl Acetate=1)

Last revised: 7/15/2015

Page 1 of 2



Customer Care: 800-556-5074 Technical Assistance: 800-521-3168 www.crcindustries.com



CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.

> CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.



## **PRODUCT DATA SHEET**



Working Temp (F) 0 to 300°F

Working Temp (C) -17.8 to 148.9°C

Drop Point 350°F

Leakage 5

Oil Separation 5

Oxidation Stability 10

Pour Point (F) 0°F

Pour Point (C) -17.78°C

I SO Viscosity Grade 165 Water Washout 10%

Worked Penetration 285 to 295

Propellant None

NSF Category Code H2

NSF Number 147593

DOT Proper Shipping Name Not Regulated

VOC % (Federal) <0.1

VOC g/L (Federal) <0.9

VOC Lbs./Gal. (Federal) <0.01

VOC Category Not Regulated

Removal (How To) Remove with a degreaser or brake cleaner product.

Last revised: 7/15/2015

Page 2 of 2

