



PRODUCT DATA SHEET

Super White™ Multi-Purpose Lithium Grease, 35 Lbs
Part Number: SL3155



Product Description	A high purity, NLGI Grade 1.5 multi-purpose white lithium grease. Provides superior lubrication & durability in any weather and most temperatures. Bright white in color. Ideal for when appearance is important.
Applications	Assembly lubes, bearings, break-in lubrication for bearings, cables, chains, chassis points, conveyor bearings, door tracks, garage door channels & openers, hinges, latches, machinery, open gears, overhead door tracks, roller bearings, sleeve bearings.
Unit Package Description	35 Pound Pail
Brand	Sta-Lube
Generic Description 1	Super White Multi-Purpose Grease
Net Fill	35 Lb
UPC Code	072213315509
Unit Dimensions	14.5H x 12W x 12D in
Units Per Case	1
Case Dimensions	14.5H x 12W x 12D in
Cases Per Pallet	36
Case Weight	40 lbs
Appearance	White Semi-Solid to Solid Grease
Base Type	Lithium-12
Flash point (F)	475°F
Flash point (C)	246°C
Flammability Class - CPSC	None
Spec Gravity Concentrate	0.9 at 60°F
NLGI Grade	1.5
Timken OK Load [Lbs.]	25 Lbs
Plastic Safe	Not Determined
Evaporation Rate	<0.01 (Butyl Acetate=1)
Working Temp (F)	0 to 300°F

Last revised: 7/15/2015
Page 1 of 2



Customer Care: 800-556-5074
Technical Assistance: 800-521-3168
www.crcindustries.com

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.



PRODUCT DATA SHEET



Working Temp (C)	-17.8 to 148.9°C
Drop Point	350°F
Leakage	5
Oil Separation	5
Oxidation Stability	10
Pour Point (F)	0°F
Pour Point (C)	-17.78°C
ISO Viscosity Grade	165
Water Washout	10%
Worked Penetration	285 to 295
Propellant	None
NSF Category Code	H2
NSF Number	147593
DOT Proper Shipping Name	Not Regulated
VOC % (Federal)	<0.1
VOC g/L (Federal)	<0.9
VOC Lbs./Gal. (Federal)	<0.01
VOC Category	Not Regulated
Removal (How To)	Remove with a degreaser or brake cleaner product.

Last revised: 7/15/2015
Page 2 of 2



Customer Care: 800-556-5074
Technical Assistance: 800-521-3168
www.crcindustries.com

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.