

PRODUCT DATA SHEET

Extreme Duty Food Grade Grease, 14 Wt Oz Part Number: SL35615

Product Description	An NSF H1 registered, NLGI #2 high performance lubricating grease used where incidental contact with food is a possibility. It also excels in applications where resistance to water washout and broad operating temperatures are absolutely necessary.
Applications	Food processing & handling equipment, breweries, canneries, carton/packaging equipment, dairies, & meat processing plants
Unit Package Description	14 Ounce Cartridge
Brand	Sta-Lube
Generic Description 1	Extreme Duty Food Grade Grease
Net Fill	14 Wt Oz
UPC Code	072213356151
Unit Dimensions	9.25H x 2.2W x 2.2D in
Units Per Case	10
Case Dimensions	9.5H x 4.5W x 11.38D in
Cases Per Pallet	150
Case Weight	9 lbs
I 2 of 5 Code	30072213356152
Appearance	Tan, Smooth Grease
Base Type	Calcium Sulfonate
Flash point (F)	428°F
Flash point (C)	220°C
Flammability Class - CPSC	Combustible
Spec Gravity Concentrate	0.95 to 1.05
NLGI Grade	2
Timken OK Load [Lbs.]	65 Lbs
Plastic Safe	Yes
Evaporation Rate	Very Slow
Working Temp (F)	-20 to 400°F

Last revised: 7/15/2015 Page 1 of 2



CRC

Extreme Duty Food Grade

Grease

NSF H1 Contains Anti-Wear and Extreme Pressure Additives Great for use on all Types of Food Plant Machinery

> Customer Care: 800-556-5074 Technical Assistance: 800-521-3168 www.crcindustries.com



and adheres to the strictest guidelines for quality in all facets of research, development and production. $CRC^{\circledast}, K\&W^{\circledast}, Sta-Lube^{\circledast}, Marykate^{\circledast} and products denoted with <math display="inline">^{\circledast}$ and m are trademarks

of CRC Industries, Inc.



PRODUCT DATA SHEET



Working Temp (C)	204.44°C
4 Ball EP	620
4 Ball Wear	0.45 Max
Drop Point	572°F
Leakage	0.4
Low Temp Torque	<5,000
Oil Separation	0.2
Oxidation Stability	1
Pour Point (F)	10.4°F
Pour Point (C)	-12°C
Water Washout	2.75
Worked Penetration	265 to 295
Propellant	None
NSF Category Code	Н1
NSF Number	144236
DOT Proper Shipping Name	Not Regulated
VOC % (Federal)	0
VOC g/L (Federal)	0
VOC Lbs./Gal. (Federal)	0
VOC Category	Not Regulated
Removal (How To)	Remove with a degreaser.

Customer Care: 800-556-5074 Technical Assistance: 800-521-3168 www.crcindustries.com



CRC[®], K&W[®], Sta-Lube[®], Marykate[®] and products denoted with [®] and [™] are trademarks of CRC Industries, Inc.

and adheres to the strictest guidelines for quality in all facets of research, development and production.

Last revised: 7/15/2015 Page 2 of 2