

PRODUCT DATA SHEET

Nickel Anti-Seize Lubricating Compound, 8 Wt Oz Part Number: SL35911



Sta-Lube Nickel Anti-Seize is a nickel based formula that is free of copper, lead, sulfides and chlorides. This

premium quality lubricant has extremely high temperature

and excellent chemical resistance. Conductive.

Applications

Catalyst beds, reaction chambers, special alloy fittings. May be used on fittings, bushings, flanges, headers, nuts, screws, studs, threaded surfaces, pipes, plugs, and manifolds to prevent seizing and galling of surfaces.

Unit Package Description

8 Ounce Brush-Top Bottle

Sta-Lube

Generic Description 1

General Purpose Anti Seize Lubricant

Net Fill

0°F (1316°C)

Net Wt: 8 oz (227 g)

8 Wt Oz

UPC Code

072213359114

Unit Dimensions

4.25H x 2.5W x 2.5D in

Units Per Case

12

Case Dimensions

5H x 6.63W x 10D in

Cases Per Pallet 108

8 lbs Case Weight

I 2 of 5 Code 30072213359115

Appearance Silver Semi-Solid Paste

Base Type

Nickel

Flash point (F)

430°F

Flash point (C)

221°C

None

Flammability Class - CPSC Spec Gravity Concentrate

1.24

Plastic Safe

Yes

Film Type

Wet

1.5

Evaporation Rate

<0.01 (Butyl Acetate=1)

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified

Dielectric Strength

Not Determined

NLGI Grade

Last revised: 1/6/2016

Page 1 of 2







PRODUCT DATA SHEET



Working Temp (F) -95 to 2400°F Working Temp (C) -70.6 to 1315.6°C

Propellant None

Military Specification Meets requirements of Mil-PRF-907E Number

DOT Proper Shipping Name Not Regulated

VOC % (Federal) 0
VOC g/L (Federal) 0
VOC Lbs./Gal. (Federal) 0

VOC Category Anti-Seize Lubricant (Non-Aerosol)

Removal (How To) Remove with general purpose degreaser.

Last revised: 1/6/2016



