

北京 010-68008 911 江苏省无锡 0510-81157933 广东省深圳 0755-83656701

[www.shuntu.net](http://www.shuntu.net) 在线查询 [www.Omrons.com.cn](http://www.Omrons.com.cn)

进口压电开关 piezoelectric switches 压电陶瓷开关 选型资料 PDF 说明书

以色列进口带灯开关 Israel ROSSLARE 压电开关 PX-13

防水按钮开关 IP68 按键开关 Piezo electric switches

Piezo-electric switches 由 AL6061 铝合金制作，有 7 种颜色。

IP68 防水按钮开关 PX-13N0 直径 22MM 金属按钮开关 ROSSLARE 进口按钮开关  
由 AL6061 铝合金制作，有 7 种颜色。

北京 Autonics 独家代理 广东省 深圳 江苏省 无锡 查询热线 4006-022-002 中国北京  
Autonics 总代理商 由 AL6061 铝合金制作，有 7 种颜色。

PX-13R, REL-PX13R0+011, PX-13R0, PX-13RO, 红色

PX-13L, REL-PX13L0+011, PX-13L0, PX-13LO, 蓝色

PX-13M, REL-PX13M0+011, PX-13M0, PX-13MO, 绿色

PX-13N, REL-PX13N0+011, PX-13N0, PX-13NO, 天然色, 金属色

PX-13B, REL-PX13B0+011, PX-13B0, PX-13BO, 黑色

PX-13G, REL-PX13G0+011, PX-13G0, PX-13GO, 金色

PX-13W, REL-PX13W0+011, PX-13W0, PX-13WO, 白色, 银色

无火花, 无磁, 防腐, 可用于室内, 室外。

采用先进的压电技术, 无机械动作。

按下按钮时, 指示灯在红色和绿色间变化

寿命达 2 千万次。

保护等级: IP-68 进口按钮开关, 高档按钮开关, 进口金属按钮开关

. 安装使用简单

. 宽电压范围 5V 到 12V DC

. 压电技术使得保护等级达到 IP68

. 无需外接电源, 可用于干接触输入

. 美观: 7 种颜色 - 黑色, 自然色(Nat) 金属色, 金色 (金黄色), 绿色, 红色, 蓝色, 银色 (银白色)

. 接触电阻 <100 ohm . 导线 2 x 24 AWG 280mm (11.02 in) wires

. 2 线接口,

. 按键寿命达一百万次以上 . 脉冲时间 >50ms

#### ENVIRONMENTAL SPECIFICATIONS

. 工作温度 -40° C 到 70° C (-40° F 到 158° F)

. 储存温度 -60° C 到 80° C (-76° F 到 176° F)

. 工作湿度 0% 至 99% 湿 - 满足 IP68 (防水) 要求

. 可以室内使用, 也适用于室外使用

#### PHYSICAL SPECIFICATIONS

. 尺寸 高: 19.5 mm (0.767 in) 直径: 29.5 mm (1.16 in)

. 标准螺纹 22 mm (0.86 in) M22 . 重量 22 g (0.0484 lbs) 产品质保: 5 年

罗仕拿安全产品, 三类主要产品: 门禁控制, 侵入探测 (入侵检测) 和安保巡更,

# PX-13

## Rugged Piezoelectric Switches



**ROSSLARE'S PX-13 ARE GENERAL PURPOSE HIGH PERFORMANCE 22MM PANEL-MOUNTED NORMALLY OPEN (N.O) PIEZOELECTRIC SWITCHES SUITED FOR LONG-LIFE AND RUGGED USE APPLICATIONS.**

**MADE FROM AL6061 ALUMINUM ALLOY MATERIAL WITH TYPE II ANODIZATION, THE UNITS ARE AVAILABLE IN 7 COLORS. THE PX-13 REQUIRES NO EXTERNAL POWER SOURCE TO OPERATE; IT IS ANTI-VANDAL, WATER AND WEATHER RESISTANT AND CAN BE OPERATED WITH FINGERS, GLOVES AND THROUGH ELASTOMERIC OVERLAYS.**

### GENERAL DESCRIPTION

Rosslare's PX-13 is heavy duty, non-sparking, nonmagnetic, corrosion resistant, illuminated, anti-vandal, and is designed for both indoor and outdoor use.

The switch features solid state Piezoelectric Switch Technology generating a dry contact N.O. pulse simply by the touch of a finger, with no physical movement or moving parts.

The PX-13 features virtually unlimited lifespan of over 20 Million uses, which is the ideal benefit of piezoelectric technology, and tested to work in harsh conditions of -40°C to +70°C.

PX-13 meets IP-68 ingress protection and is resilient to submerging in water, dirt and dust applications, making it suitable for both indoor and outdoor conditions.

### MAIN FEATURES

- Easy to install and use
- Supports a wide range of switch voltages from 5V to 12V DC
- Piezoelectric technology can sense actuation within a solid metal enclosure,

makes the devices rugged Waterproof, Meets IP-68

- Fully potted design prevents penetration of dirt, dust and water
- Require no operating power, capable of actuating a dry contact input
- Available in a range of seven attractive anodized Aluminum colors – Black , Natural (Mat) , Gold, Green, Red, Blue, and Silver

### PROFESSIONAL GRADE FEATURES

- SMT designed electronics for higher quality, superior performance, and reduced cost
- Compatible with Rosslare's Access Controllers as a REX or a system input (Alarm or Event)
- No polarity considerations for the Switch
- Meets RoHS Requirements for non-corrosive materials

# SPECIFICATIONS

## ELECTRICAL SPECIFICATIONS

|                      |   |
|----------------------|---|
| ■ Voltage            | 5VDC to 12VDC (Max)                                     |
| ■ Input Current      | < 1A  |
| ■ Contact Resistance | <100 ohm  |
| ■ Wire Leads         | 2 x 24 AWG 280mm (11.02 in) wires                       |
| ■ 2-Wire Interface   | No polarity wires for +Vin or Ground of switched device |
| ■ Button life        | Over one million cycles                                 |
| ■ Impulse Time       | >50ms (on Actuation)                                    |

## ENVIRONMENTAL SPECIFICATIONS

|                         |   |
|-------------------------|---|
| ■ Operating Temperature | -40°C to 70°C (-40°F to 158°F)          |
| ■ Storage Temperature   | -60°C to 80°C (-76°F to 176°F)          |
| ■ Operating Humidity    | 0% to 99% Wet - Meets IP68 (Waterproof) |
| ■ Operating Environment | Indoor and Outdoor                      |

## PHYSICAL SPECIFICATIONS

|                   |  |
|-------------------|--|
| ■ Dimensions      | Height: 19.5 mm (0.767 in) Diameter: 29.5 mm (1.16 in) |
| ■ Standard Thread | 22 mm (0.86 in)  |
| ■ Weight          | 22 g (0.0484 lbs)                                      |

## SYSTEM COMPONENTS

The Piezoelectric switches are compatible with Rosslare's controllers (AC-225, AC-425, AC-115, etc.), security systems and many third party systems.

## PRODUCT WARRANTY

5-year Limited Product Warranty

## ABOUT ROSSLARE SECURITY

Rosslare Security Products, a division of Rosslare Enterprises Ltd. manufactures high-quality security products since 1980. The company's three main lines: Access Control, Intrusion Detection and Guard Patrol, together with a growing product range have transformed Rosslare Security into a major worldwide force in security. Rosslare holds itself to the highest standards of customer service and manufacturing (ISO 9001:2008, ISO 14001:2004, ISO 13485:2003). The company complies with the EU Directive 2002/95/EC on Restriction of Hazardous Substances (RoHS).