

Packaging — Complete, filled transport packages — Compression and stacking tests using a compression tester

The European Standard EN ISO 12048:2000 has the status of a
British Standard

ICS 55.180.40

National foreword

This British Standard is the official English language version of EN ISO 12048:2000. It is identical with ISO 12048:1994. It supersedes BS ISO 12048:1994 which is withdrawn.

The UK participation in its preparation was entrusted by Technical Committee PKW/1, Packaging generalities, to Subcommittee PKW/1/4, Test methods, which has the responsibility to:

- aid enquirers to understand the text;
- present to the responsible international/European committee any enquiries on the interpretation, or proposals for change, and keep the UK interests informed;
- monitor related international and European developments and promulgate them in the UK.

A list of organizations represented on this subcommittee can be obtained on request to its secretary.

Cross-references

Attention is drawn to the fact that CEN and CENELEC Standards normally include an annex which lists normative references to international publications with their corresponding European publications. The British Standards which implement these international or European publications may be found in the BSI Standards Catalogue under the section entitled “International Standards Correspondence Index”, or by using the “Find” facility of the BSI Standards Electronic Catalogue.

A British Standard does not purport to include all the necessary provisions of a contract. Users of British Standards are responsible for their correct application.

Compliance with a British Standard does not of itself confer immunity from legal obligations.

Summary of pages

This document comprises a front cover, an inside front cover, the EN ISO title page, the EN ISO foreword page, the ISO title page, page ii, pages 1 to 5, the annex ZA page, an inside back cover and a back cover.

The BSI copyright notice displayed in this document indicates when the document was last issued.

This British Standard, having been prepared under the direction of the Consumer Products and Services Sector Committee, was published under the authority of the Standards Committee and comes into effect on 15 February 2001

© BSI 02-2001

ISBN 0 580 36832 7

Amendments issued since publication

Amd. No.	Date	Comments

English version

**Packaging - Complete, filled transport packages - Compression
and stacking tests using a compression tester (ISO 12048:1994)**

Emballages - Emballages d'expédition complets et pleins -
Essais de compression et de gerbage à l'aide d'une
machine d'essai de compression (ISO 12048:1994)

Verpackung - Versandfertige Packstücke - Kompressions-
und Stapelprüfung unter Verwendung einer
Kompressionsprüfmaschine (ISO 12048:1994)

This European Standard was approved by CEN on 16 November 2000.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

Foreword

The text of the International Standard from Technical Committee ISO/TC 122 "Packaging" of the International Organization for Standardization (ISO) has been taken over as an European Standard by Technical Committee CEN/TC 261 "Packaging", the secretariat of which is held by AFNOR.

This European Standard supersedes EN 22872:1992 and EN 22874:1992.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by June 2001, and conflicting national standards shall be withdrawn at the latest by June 2001.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and the United Kingdom.

Endorsement notice

The text of the International Standard ISO 12048:1994 has been approved by CEN as a European Standard without any modification.

NOTE: Normative references to International Standards are listed in annex ZA (normative).

INTERNATIONAL STANDARD

ISO
12048

First edition
1994-10-15

Packaging — Complete, filled transport packages — Compression and stacking tests using a compression tester

*Emballages — Emballages d'expédition complets et pleins — Essais de
compression et de gerbage à l'aide d'une machine d'essai de compression*



Reference number
ISO 12048:1994(E)

Packaging — Complete, filled transport packages — Compression and stacking tests using a compression tester

1 Scope

This International Standard specifies a method for testing the resistance to compression of complete, filled transport packages and a method for carrying out a stacking test on complete, filled transport packages using the same apparatus.

The test may be used to assess the performance of a package in terms of its strength or the protection it offers to its contents when it is subjected to compressive forces. A test may be performed either as a single test to investigate the effects (deformation, collapse or failure) of compression or stacking, or as part of a sequence of tests designed to measure the ability of a package to withstand a distribution system that includes a compression or stacking hazard.

This test may also be used as a stacking test to investigate performance under particular conditions of loading, as, for example, when the bottom package in a stack rests on an open-decked pallet.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 2206:1987, *Packaging — Complete, filled transport packages — Identification of parts when testing*.

ISO 2233:—¹⁾, *Packaging — Complete, filled transport packages — Conditioning for testing*.

3 Principle

The test package is placed between the platens of a compression tester and either:

- in the case of a compression test, a load is applied until failure occurs or predetermined values for load or displacement are reached; or
- in the case of a stacking test, a predetermined load is applied for a predetermined time or until failure occurs.

4 Apparatus

4.1 Compression tester, motor-driven, platen-type, capable of applying load through uniform movement of one or both platens at a relative speed of 10 mm/min \pm 3 mm/min.

NOTES

1 The comparison between results obtained from apparatus operated at other speeds (for example 12,5 mm/min \pm 2,5 mm/min) and results obtained at 10 mm/min \pm 3 mm/min is not recommended.

2 For certain packagings, such as metal drums or wooden crates, lower speeds may be required to prevent load peaks in excess of the predetermined value.

4.1.1 Platens

Each platen shall be

- flat:
 - with a tolerance of 1 part in 1 000 for surface areas $<1 \text{ m}^2$;
 - for surface areas $>1 \text{ m}^2$, such that when placed horizontally the difference in height between the lowest and highest points of the platen does not exceed 1 mm;
- dimensioned so as to extend over the whole area of that side of the test package or interposed devices with which it is in contact;

¹⁾ To be published. (Revision of ISO 2233:1986)

- rigid, so as not to deform by more than 1 mm at any point when the tester applies a load of 75 % of its maximum rating, either to a centrally placed 100 mm × 100 mm × 100 mm block having sufficient strength to accept the load without failure, or to four similar blocks placed at the four corners, in the case of swivel-mounted platens.

One platen shall remain horizontal, within a tolerance of two parts per 1 000, at all times during the test. The other platen shall be either rigidly mounted so as to remain horizontal within two parts per 1 000 at all times during the test, or be held by a universal joint at its centre and so be free to tilt in any direction.

The working surfaces of the platens may be locally recessed for fixing bolts etc.

4.1.2 Means of applying a predetermined load for a predetermined time, with a fluctuation not exceeding ± 4 % of the predetermined load and with no more relative movement of the platens than is necessary to maintain this load during any vertical displacement of the upper platen.

4.2 Recording device or other means of indicating applied load and platen displacement, with a percentage of error not exceeding 2 % of the load and an accuracy for recording platen displacement of ± 1 mm.

4.3 Means of measuring package dimensions with an accuracy of ± 1 mm.

5 Package preparation

The test package shall normally be filled with its intended contents. However, simulated or dummy contents may be used, on condition that the dimensions and physical properties of such contents shall be as close as possible to those of the intended contents.

Ensure that the test package is closed normally, as if ready for distribution. If simulated or dummy contents are used, ensure that the normal method of closure is still employed.

6 Conditioning

The package shall be conditioned in accordance with one of the sets of conditions given in ISO 2233.

7 Procedure

Wherever possible the test shall be carried out in the same atmospheric conditions as used for conditioning, where this is critical to the materials or application of the package. In other circumstances, the test shall be carried out in atmospheric conditions

which are as near as practicable to those used for conditioning.

When possible, carry out the test on five replicate packages.

7.1 Compression test

7.1.1 Weigh the package and its contents separately, fill the package and measure the external dimensions of the filled package.

7.1.2 Place the test package centrally on the lower platen of the test machine (4.1), in the predetermined attitude.

When the compression load is not to be applied over the whole surface of the package which is being tested, appropriate devices should be suitably interposed between the package and platen of the compression tester in order to simulate the conditions met in distribution systems when applying these compression loads.

7.1.3 Apply the load by relative movement of the platens at the appropriate speed, in such a way that peaks in excess of the predetermined load do not occur, until the predetermined value is reached or until collapse occurs, whichever is first. If collapse occurs first, record the value of the load reached.

In measuring deformation, the initial reading (the datum point), unless otherwise specified, shall be taken at an initial load which is a function of the expected average compression load according to table 1.

Table 1 — Datum points

Average compression load N	Datum point N
101 – 200	10
201 – 1 000	25
1 001 – 2 000	100
2 001 – 10 000	250
10 001 – 20 000	1 000
20 001 – 100 000	2 500
etc.	etc.

7.1.4 If required, maintain the predetermined load for a predetermined time or until collapse occurs, whichever is first. If collapse occurs first, record the value of the time elapsed.

7.1.5 Remove the load by movement of the platens, examine the package and, if collapse has occurred, measure its dimensions and examine the contents for damage.

7.1.6 Where it is desired to measure the ability of a complete, filled transport package to resist external

compressive loads applied to opposite edges or corners of the package, follow the procedure in 7.1.1 to 7.1.5, using a tester in which the platens are not free to tilt.

7.2 Stacking test

NOTE 3 A stacking test on a complete, filled transport package, using one of three methods of applying a static load, is given in ISO 2234.

7.2.1 Proceed as in 7.1.1 to 7.1.3 and maintain the predetermined load for a predetermined time or until collapse occurs, whichever is first. If collapse occurs first, record the value of the time elapsed.

NOTE 4 Where it is desired to measure the ability of a complete, filled transport package to resist external compressive loads applied during stacking, a tester with one fixed platen is preferred.

7.2.2 Remove the load by movement of the platens, examine the package and, if collapse has occurred, measure its dimensions and examine the contents for damage.

NOTES

5 At any time during the test it may be necessary to measure dimensions (see annex A).

6 Appropriate profiles representative of particular loading conditions may be inserted between platens and package as required.

8 Test report

The test report shall include the following information:

- a) reference to this International Standard;
- b) whether a compression or stacking test was carried out;
- c) number of replicate packages tested;
- d) full description of the package, including dimensions, structural and material specifications

of the package and its fittings, cushioning, blocking, closure or reinforcing arrangements;

- e) description of the contents — if simulated or dummy contents were used, full details shall be given;
- f) gross mass of the package and mass of contents, in kilograms;
- g) relative humidity, temperature and time of conditioning; temperature and relative humidity of test area at time of test; whether these values comply with the requirements of ISO 2233;
- h) the attitude in which the package was tested, using the method of identification given in ISO 2206;
- i) type of test apparatus used, including whether the compression tester was mechanically or hydraulically operated and whether or not both platens were rigidly mounted;
- j) location of measurement points on packages and stage of test at which measurements were made;
- k) design and dimensions of any profiles used;
- l) test conditions, i.e.: the rate of application of the load (see 4.1), the load applied, in newtons, and duration of application of load to the package;
- m) a record of the average results, including load applied until collapse if less than the predetermined load, the time elapsed until collapse if less than the predetermined time, any observed changes in package dimensions and, if required, load/platen displacement recording, with any observations which may assist in correct interpretation;
- n) any deviation from the test methods described in this International Standard;
- o) date of test;
- p) signature of tester.

Annex A **(informative)**

Example of a method of measuring package deformation load

A.1 Place the weighed, filled transport package centrally between the platens and apply, at the standard rate of 10 mm/min \pm 3 mm/min, an initial load of approximately 10 % of the value of the predetermined load to be applied.

A.2 Take a preliminary series of dimensional measurements of the package from the surfaces which apply the load to the package to several points along the vertical edges of the package and, optionally, along the sides.

A.3 Apply the predetermined load for a predetermined time.

A.4 Repeat the dimensional measurements, in the same positions as in A.2, at predetermined stages during application of the load.

NOTE 7 The average deformations may be measured more simply by using a chart recorder.

Annex B (informative)

Bibliography

- [1] ISO 2234:1985, *Packaging — Complete, filled transport packages — Stacking tests using static load.*

Annex ZA
(normative)**Normative references to international publications with their
corresponding European publications**

This European Standard incorporates, by dated or undated reference, provisions from other publications. These normative references are cited at the appropriate places in the text, and the publications are listed hereafter. For dated references, subsequent amendments to or revisions of any of these publications apply to this European Standard only when incorporated in it by amendment or revision. For undated references the latest edition of the publication referred to applies (including amendments).

NOTE Where an International Publication has been modified by common modifications, indicated by (mod.), the relevant EN/HD applies.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN</u>	<u>Year</u>
ISO 2206	1987	Packaging - Complete, filled transport packages - Identification of parts when testing	EN 22206	1992

BSI — British Standards Institution

BSI is the independent national body responsible for preparing British Standards. It presents the UK view on standards in Europe and at the international level. It is incorporated by Royal Charter.

Revisions

British Standards are updated by amendment or revision. Users of British Standards should make sure that they possess the latest amendments or editions.

It is the constant aim of BSI to improve the quality of our products and services. We would be grateful if anyone finding an inaccuracy or ambiguity while using this British Standard would inform the Secretary of the technical committee responsible, the identity of which can be found on the inside front cover. Tel: 020 8996 9000. Fax: 020 8996 7400.

BSI offers members an individual updating service called PLUS which ensures that subscribers automatically receive the latest editions of standards.

Buying standards

Orders for all BSI, international and foreign standards publications should be addressed to Customer Services. Tel: 020 8996 9001. Fax: 020 8996 7001. Standards are also available from the BSI website at <http://www.bsi-global.com>.

In response to orders for international standards, it is BSI policy to supply the BSI implementation of those that have been published as British Standards, unless otherwise requested.

Information on standards

BSI provides a wide range of information on national, European and international standards through its Library and its Technical Help to Exporters Service. Various BSI electronic information services are also available which give details on all its products and services. Contact the Information Centre. Tel: 020 8996 7111. Fax: 020 8996 7048.

Subscribing members of BSI are kept up to date with standards developments and receive substantial discounts on the purchase price of standards. For details of these and other benefits contact Membership Administration. Tel: 020 8996 7002. Fax: 020 8996 7001. Further information about BSI is available on the BSI website at <http://www.bsi-global.com>.

Copyright

Copyright subsists in all BSI publications. BSI also holds the copyright, in the UK, of the publications of the international standardization bodies. Except as permitted under the Copyright, Designs and Patents Act 1988 no extract may be reproduced, stored in a retrieval system or transmitted in any form or by any means – electronic, photocopying, recording or otherwise – without prior written permission from BSI.

This does not preclude the free use, in the course of implementing the standard, of necessary details such as symbols, and size, type or grade designations. If these details are to be used for any other purpose than implementation then the prior written permission of BSI must be obtained.

If permission is granted, the terms may include royalty payments or a licensing agreement. Details and advice can be obtained from the Copyright Manager. Tel: 020 8996 7070.