

Standard Test Method for Print Resistance of Lacquers¹

This standard is issued under the fixed designation D 2091; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

This standard has been approved for use by agencies of the Department of Defense.

1. Scope

1.1 This test method covers the resistance of dried lacquer films to imprinting.

1.2 The values stated in SI units are to be regarded as the standard. The values given in parentheses are for information only.

1.3 This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.

2. Referenced Documents

2.1 ASTM Standards:

D 823 Practices for Producing Films of Uniform Thickness of Paint, Varnish, and Related Products on Test Panels²

D 1005 Test Method for Measurement of Dry-Film Thickness of Organic Coatings Using Micrometers²

- D 1186 Test Methods for Nondestructive Measurement of Dry Film Thickness of Nonmagnetic Coatings Applied to a Ferrous Base²
- D 1400 Test Method for Nondestructive Measurement of Dry Film Thickness of Nonconductive Coatings Applied to a Nonferrous Metal Base²
- D 5235 Test Method for Microscopical Measurement of Dry Film Thickness of Coatings on Wood Products³

2.2 U.S. Federal Specifications:

CCC-C-419(f) Cloth, Duck, Cotton, Unbleached, Plied⁴ CCC-C-440(e) Cloth, Cheesecloth, Bleached and Unbleached⁴

3. Summary of Test Method

3.1 A weight presses a piece of fabric against the test surface. The surface is then examined and changes in appearance of the test surface are reported.

4. Significance and Use

4.1 An unsatisfactory appearance can result from pressure deformation of a film inherently too soft or containing residual solvent. This test method is primarily used to evaluate the resistance of a lacquer finish to printing under the conditions of packaging, shipping, and warehousing.

5. Apparatus and Materials

5.1 *Test Panels*—A plane surface consisting of wood, metal, paper supported on plate glass, plastic, or other surface with an area at least 100 % greater than the base of the weight. The planeness, smoothness, and composition should be agreed upon by the purchaser and the seller.

5.2 *Imprinting Fabric*, 8-oz Army duck, Type III, conforming to Fed. Spec. CCC-C-419(f) or cheesecloth, Type I, conforming to Federal Specification CCC-C-440(e).

Note 1—With the cheese cloth only, use a pad of nonwoven felt cloth at least 1.3 mm (0.05 in.) thick, weighing 0.24 kg/m²(7 oz/yd²) and larger than the plane end of the weight.

5.3 Weights, consisting of metal cylinders cut from standard stock 51 mm (2 in.) in diameter, with plane ends perpendicular to the axis, and of a length to give a pressure of 3.5 or 7.0 kPa ($\frac{1}{2}$ or 1 lb/in.²).

5.4 Automatic Application Equipment, (Optional), as described in Practices D 823.

5.5 *Film Thickness Measuring Apparatus*, as described in Test Methods D 1005, D 1186, D 1400, and D 5235.

6. Preparation of Test Specimen

6.1 *Single Coats*—Prepare a specimen for test by applying the test lacquer to a panel with a film applicator or other specified method, as described in Practices D 823, to give a

Copyright © ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States.

¹ This test method is under the jurisdiction of ASTM Committee D01 on Paint and Related Coatings, Materials, and Applications and is the direct responsibility of Subcommittee D 01.52 on Factory Coated Wood Products.

Current edition approved Oct. 1, 2003. Published October 2003. Originally approved in 1962. Last previous edition approved in 1996 as D 2091 – 96.

² Annual Book of ASTM Standards, Vol 06.01.

³ Annual Book of ASTM Standards, Vol 06.02.

⁴ Available from Standardization Documents Order Desk, DODSSP, Bldg. 4, Section D, 700 Robbins Ave., Philadelphia, PA 19111-5098

🖗 D 2091 – 96 (2003)





FIG. 1 Print Resistance

specified film thickness to be stated in the result. In the absence of a specified dry film thickness, $25 \pm 3 \mu m (1 \pm 0.1 mil)$ is recommended.

6.2 *Multiple Coats*—Use the finish system as agreed upon between the purchaser and the seller. In the absence of a specified dry film thickness, 75 \pm 8 µm (3 \pm 0.3 mils) are recommended.

6.3 *Conditioning*—Allow to dry as agreed upon between the purchaser and the seller, but run the test within 48 h after coating. In the absence of a specified drying schedule, a period of 24 h at $23 \pm 2^{\circ}$ C (73.5 $\pm 3.5^{\circ}$ F) and a relative humidity of 50 ± 5 % is recommended.

7. Procedure

7.1 Place over a uniform area of the specimen either a smooth piece of duck cloth or a piece of cheesecloth with a felt pad cushion. Place one or more weights, each on top of the other, on the duck or cheesecloth and pad and maintain the weight in compliance with one of the following test conditions:

7.1.1 At 23 \pm 2°C (73.5 \pm 3.5°F) and 50 \pm 5 % relative humidity for an 18-h period,

7.1.2 At 50°C (120°F) for a 4-h period, or

7.1.3 At 60°C (140°F) for a 4-h period.

7.2 After the specified time, remove the weight, pad, and fabric. Remove lint and dust from the panel with a clean air stream. Examine the specimen immediately under bright, diffused illumination for impression of the fabric into the lacquered surface and compare to photographic standards (Fig. 1).

8. Report

- 8.1 Report the following information:
- 8.1.1 Surface involved,
- 8.1.2 Drying schedule,
- 8.1.3 Film thickness,
- 8.1.4 Weight used,
- 8.1.5 Test temperature used, time, and

8.1.6 Conditions of test other than those primarily specified in this test method.

9. Precision

9.1 Results varying by more than 1° of print should be suspect, either with the same or different operators.

10. Keywords

10.1 lacquer; print resistance

ASTM International takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.

∰ D 2091 – 96 (2003)

This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org).