



Standard Test Method for the Determination of the Component Retention of a Mechanical Pump Dispenser¹

This standard is issued under the fixed designation D 4335; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This test method covers the evaluation of the force required to remove the hood and the actuator from a mechanical dispensing pump.

1.2 *This standard may involve hazardous materials, operations, and equipment. This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to consult and establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

2. Referenced Documents

2.1 ASTM Standards:

D 618 Practice for Conditioning Plastics and Electrical Insulating Materials for Testing²

3. Significance and Use

3.1 This test method may be used to establish performance specifications.

3.2 This test method may be used to establish quality control assessment.

4. Apparatus

4.1 *Test Stand*—The test apparatus shall be capable of applying a smoothly increasing load to the test specimen until the component is separated from the pump assembly.

NOTE 1—The condition of 4.1 is fulfilled by most motor driven tensile strength testers including constant rate of elongation testers.

NOTE 2—The test standard should be equipped with a maximum-force indicator.

4.2 *Fixtures*, to hold the mechanical pump dispenser.

4.2.1 The fixtures must allow no slippage between the test specimen and the fixture, so that distortion is avoided.

4.2.2 The fixtures for the test apparatus may be custom-made for this test.

¹ This test method is under the jurisdiction of ASTM Committee D10 on Packaging and is the direct responsibility of Subcommittee D10.33 on Mechanical Dispensers.

Current edition approved Oct. 10, 1999. Published December 1999. Originally published as D 4335 – 84. Discontinued 1991. Reinstated 1999.

² *Annual Book of ASTM Standards*, Vol 08.01.

5. Sampling

5.1 Select an appropriate number of dry, unused pump dispensers at random for precision and accuracy desired. Use of 10 test specimens is recommended, but a minimum of three is acceptable.

6. Test Specimen

6.1 Test specimens shall be clean, dry, and previously unused mechanical pump dispensers assembled in the same manner as in production.

7. Conditioning

7.1 If possible, condition the test specimens at $23 \pm 3^{\circ}\text{C}$ ($73 \pm 5.4^{\circ}\text{F}$) for not less than 4 h. If the test specimens are not conditioned at the recommended temperature, this should be noted in the test report (see 9.1).

8. Procedure

8.1 Attach fixtures to the test stand in accordance with the manufacturer's instructions or in a manner consistent with the pump's geometry.

8.2 Adjust the test stand so that there is no force acting on the specimen.

NOTE 3—At this time, there should be a zero reading on the force gage.

8.3 Manual Method:

8.3.1 Place the pump assembly into the fixture.

8.3.2 Grasp the component to be separated in the hand.

8.3.3 Pull the component as slowly as possible, avoiding quick, jerking actions.

8.3.4 Continue to pull the component until it separates from the assembly.

8.3.5 Observe and record the maximum force, N (lb), required to separate the component from the assembly.

8.4 Machine Method:

8.4.1 Place the pump assembly into the fixture.

8.4.2 Secure the other component to the movable crosshead.

8.4.3 Operate the test stand at a rate of 250 mm/min (10 in./min).

8.4.4 Stop the machine when the component has separated from the assembly.

8.4.5 Observe and record the maximum force, N (lb),

required to separate the component from the assembly.

9. Report

9.1 The report shall include the following:

9.1.1 Complete identification of the component tested, including materials of construction, size, and manufacturer's code and date of manufacture, if known,

9.1.2 Number of specimens tested,

9.1.3 Number of test specimens that were separated from the assembly,

9.1.4 Mean, minimum, maximum, and standard deviation of forces required to separate the components from the assembly,

9.1.5 Special storage conditions, if applicable,

9.1.6 Description of the test apparatus, and

9.1.7 Method used, whether manual or machine (see 8.3 and 8.4).

10. Precision and Bias

10.1 *Precision*—The precision of Test Method D 4335 is highly dependent on the interference requirements of the

particular pump components tested. One laboratory has investigated one particular pump actuator removed from one particular pump piston with 82 replicate tests, yielding an average of 6.24 lbf with a range of 9.0 to 4.6 lbf and a standard deviation of 0.95 lbf. Other pump component assemblies will have other averages of retention and will have more or less variability between replicate tests. Users of this test method are encouraged to reference historical files of previous tests of similar pump component assemblies for an estimate of within-laboratory repeatability. Due to this varying component interference requirement dependency, further investigation of repeatability and reproducibility is not practicable.

10.2 *Bias*—Test Method D 4335 has no bias because an accepted reference or referee value is not available.

11. Keywords

11.1 component; mechanical pump dispenser; retention

The American Society for Testing and Materials takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.

This standard is copyrighted by ASTM, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org).