

## AUG Series

20 Watts

Total Power: 20 Watts  
Input Voltage: 36V - 75V  
# of Outputs: Single



## Special Features

- Ultra Low Profile - 4.8mm
- Efficiency - 88% @ 5V
- -40°C to +75°C Operating temperature(Ambient)
- Open Frame SMT
- Low output ripple and noise
- Regulation to zero load
- CISPR22, Class A for Conduct and Radiated EMI
- Parallel Application
- Pb-free reflow compatible and ROHS compliant

## Electrical Specifications

Input	
Input range	36 - 60 VDC 60 - 75VDC (with derating)
Efficiency	88% @ 5Vo
Output	
Line / Load Regulation	+5%, -3%
Noise / Ripple	100mV p-p
OVP	115% of $V_{O_{nom}}$ (latch-up)
OCP	4.2A for 5V 6.2A for 3.3V 7.2A for 2.5V 8.2A for 1.5V and 1.8V
LVP	95% of $V_{O_{nom}}$ (latch-up)
Isolation	1500VDC
Control	
Enable	ON: RC pin connected to -Vin or open OFF: RC pin connected to +Vin

## Environmental Specifications

Ambient Operating temperature	-40°C to +75°C (forced air 1.2m/s)
Storage temperature	-45°C to +90°C

## Safety


UL 60950  
CE CE Mark



### Ordering Information

Input Voltage	Output Voltage	Efficiency	Model Number
48V	1.5V @ 8A	83% (Typ)	AUG08M48
48V	1.8V @ 8A	84% (Typ)	AUG08Y48
48V	2.5V @ 7A	86% (Typ)	AUG07G48
48V	3.3V @ 6A	88% (Typ)	AUG06F48
48V	5.0V @ 4A	88% (Typ)	AUG04A48

### Pin Assignment



### Pin Assignments

Pin No	Symbol	Function	Pin No	Symbol	Function
1, 10, 11, 20	NC	Mechanical supplemental contact pins	12	ALM	Alarm output
2	+Vout	+Output	13	RC	Remote on/off control
3	+Vout	+Output	14	PO	Parallel operation
4	+Vout	+Output	15	NC	-
5	-Vout	-Output	16	+Vin	+Input
6	-Vout	-Output	17	+Vin	+Input
			18	-Vin	-Input
			19	-Vin	-Input

Note: Astec reserves the right to make changes to the information contained herein without notice and assumes no liability of its use and application.

### Astec Power

5810 Van Allen Way  
Carlsbad, CA 92008  
USA  
Telephone: +1 760 930 4600  
Facsimile: +1 760 930 0698  
Technical Support: +1 888 41 ASTEC  
or +1 407 241 2752

Waterfront Business Park  
Merry Hill, Dudley  
West Midlands, DY5 1LX  
United Kingdom  
Telephone: +44 (0) 1384 842 211  
Facsimile: +44 (0) 1384 843 355

Units 2111-2116, Level 21  
Tower 1, Metroplaza  
223, Hing Fong Road  
Kwai Fong, New Territories  
Hong Kong  
Telephone: +852 2437 9662  
Facsimile: +852 2402 4426

For global contact, visit:  
[www.astecpower.com](http://www.astecpower.com)  
[technicalsupport@astec.com](mailto:technicalsupport@astec.com)

While every precaution has been taken to ensure accuracy and completeness in this literature, Astec Power assumes no responsibility, and disclaims all liability for damages resulting from use of this information or for any errors or omissions.

Printed in USA

**Emerson Network Power.**  
The global leader in enabling  
business-critical continuity.

- AC Power
- Connectivity
- DC Power
- Embedded Power**
- Inbound Power
- Integrated Cabinet Solutions
- Outside Plant
- Precision Cooling
- Site Monitoring and Services

**EmersonNetworkPower.com**

Emerson Network Power and the Emerson Network Power logo are trademarks and service marks of Emerson Electric Co.  
©2005 Emerson Electric Co.