



EFAP-S552

550W Output Power
 Supports Tylersburg Platform
 Single +12V Output Rail
 EPS2U Application for Rack Mount System
 Dimension: 100(W) x 70(H) x 239.5(D) mm



INQUIRY

DownLoad

- 📄 [DRAWING](#)
- 📄 [CE](#) 📄 [FCC](#) 📄 [UL](#) 📄 [TUV](#) 📄 [CCC](#) 📄 [CB](#) 📄 [BSMI](#)

Features :

Universal Power Input
 Active Power Factor Correction
 Single +12V Output Rail
 Remote DC Sense on +5V and +3.3V
 Short Circuit Protection
 Over Current Protection
 Over Voltage Protection
 MTBF >100,000 Hours

General Specifications :

Input Range : 100 to 240 VAC, +/-10%
 Power Factor: >0.95 minimum at full load
 Efficiency: 80% minimum, at full load (115/230Vac), 80PLUS® Certified
 Hold up Time: 18mS minimum, at full load
 PSON (Remote ON/OFF): TTL compatible signal
 Power Good: 100 to 500 ms, TTL compatible signal
 Operating Temperature: 0 to 50 °C
 Operating Humidity: 20 to 90 %

Regulation, Ripple & Noise:

Output	+3.3V	+5V	+12V1	+12V2	+12V3	+12V4-	-5V	-12V	+5Vsb
Load Regulation	± 5%	± 5%	± 5%					± 10%	± 5%
Cross Regulation	± 5%	± 5%	± 5%					± 10%	± 5%
Line Regulation	± 1%	± 1%	± 1%					± 1%	± 1%
Ripple & Noise	50mV	50mV	120mV					120mV	50mV

Input and Output Ratings:

Input			Output										
Voltage	Frequency	Current	Watt	Load	+3.3V	+5V	+12V1	+12V2	+12V3	+12V4	-5V	-12V	+5Vsb
100-240Vac	47-63Hz	8~3.5A	600W	Max. Load	24A	24A	43A					0.5A	2A
				Min. Load	0.5A	0.5A	1A					0.1A	0A

NOTE:

1. The +5 & +3.3 Volt combine total output shall not exceed 130W
2. The +5, +3.3 and +12 Volt combine total output shall not exceed 534W
3. Noise bandwidth is from DC to 20 MHz.

Agency Requirements :

Harmonic: Meet EN6 1000-3-2 standards
EMI/RFI: CE, FCC class B and CISPR class B
Safety: UL, cUL, CB, TUV, CCC