



1 产品概述 Product Summarize

用于直流操作的保护和自动装置中。作为机械保持和手动复归的动作指示器。动作显示为机械掉牌。其中DX-8G型为横向安装。

电磁式原理。壳体结构采用JK-5(凸出式后接线), JKE-5Q(凸出式前接线), JK-6/4(嵌入式后接线)标准组件, 订货须指明。

It's used in DC operated protection and automatic devices, working as action indicator for mechanical remaining and manual resetting. Action display is mechanical drop-plate. Among them, DX-2G is horizontal installation type. By electromagnetic principle. Adopted standard component such as JK-5, protruding back connected, JKE-5Q, protruding front connected, JK-6/4, inserted back connected on case structure. Please indicate it as placing an order.

2 主要技术参数 Main Technological Parameter

电压额定值 Un(V)	Voltage rated value Un (V)	220,110,48,24,12
电流型额定值 In(A)	Current rated value In(A)	0.01,0.015,0.025,0.05,0.075,0.1,0.15,0.25,0.5,0.75,1,2,4
动作值 Action value	电压型 Voltage type	$\leq 70\%U_n$
	电流型 Current type	$\leq 90\%I_n$
动作时间 Action time		电压型 $U=U_n$, 电流型 $I=120\%, I_n \leq 30ms$ Voltage type $U=U_n$, Current type $I=120\%, I_n \leq 30ms$
功率消耗(W) Power wastage (W)	电压型 Voltage type	≤ 3
	电流型 Current type	≤ 0.3
触点形式 Contact form		三副动合触点 3 pairs of movable connection contact
触点断开容量 Contact breaking capacity		直流有感 50W 交流电路 250VA DC sensitive 50W, AC circuit, 250VA

3 安装开孔尺寸、接线图 Mounging plate opening size, Wiring drawing

