



## 1 产品概述 Product Summarize

用于直流操作的保护线路中,作为动作指示器。其特点为工作可靠、信号明显。

电磁式动作原理,拍合式结构,掉牌信号,手动复归。其中DX-11型有4动合触点,DX-11A型有2副独立的电气上无联系的动合触点,继电器安在垂直屏板上,可以前面接线或后面接线,订货时指明。

It can be applied to the protective circuit operated by D C as operation indicator, with functions of reliable working and significant signal.

It adopts electromagnetic type working principle, clapper type structure, lose brand signal, and hand resetting. DX-11 type has 4 front contacts; and DX-11A type has 1 pair of independent front contacts (has no relations with each other in electrics). The relay is mounted on vertical plate, and can be wired in front or back, which can be specified when orders.

## 2 主要技术参数 Main Technological Parameter

额定值 Rated value	电压型(V) Voltage type (V)	220,110,48,24,12
	电流型(A) Current type (A)	0.01,0.015,0.025,0.05,0.075,0.1,0.15,0.5,0.75,1
长期值 Long term value	电压型(V) Voltage type (V)	242,121,53,26.5,13.5
	电流型(A) Current type (A)	0.03,0.045,0.075,0.15,0.225,0.3,0.45,0.75,1.5,2.25,3
动作值 Operating value	电压型(V) Voltage type (V)	≤ 70% 额定值 rated value
	电流型(A) Current type (A)	≤ 90% 额定值 rated value
返回值 Return value		≥ 2% 额定值 rated value
Power consumption (W) 功率消耗(W)	电压型 Voltage type	0.3
	电流型 Current type (A)	2
触点形式 Contact type		2 动合 front apertures
触点断开容量 Contact breaking capacity		DC50W,AC100VA

## 3 安装开孔尺寸、接线图 Mounging plate opening size,Wiring drawing

