



1 产品概述 Product Summarize

用于电力系统二次回路的继电保护线路中，作为直流回路动作指示信号用。

电磁型拍合式原理。一次可两次掉牌信号指示，并能保持，可手动或电动复归。

This series are applied for relay protective circuit of secondary loop in power system as operation indicating signal of DC circuit.

It adopts electromagnetic type working principle, and sends out and keeps two times lose brand signal indicating once. It can be hand or electric resetting.

2 主要技术参数 Main Technological Parameter

型号 Type	DX-15/S	DX-15/D	DX-15/2S	DX-15/2D
额定电流 $I_{nDC}(A)$ Rated current $I_{nDC}(A)$	0.01,0.015,0.025,0.05,0.075,0.1,0.15,0.25,0.5,0.75,1,2			
额定电压 $U_{nDC}(V)$ Rated voltage $U_{nDC}(V)$	220,110,48,24,12			
复归电压 DC(V) Resetting voltage DC(V)	220,110,48,24,12			
复归方式 Resetting mode	手动 Hand	电动或手动 Electric or hand	手动 Hand	电动或手动 Electric or hand
显示方式 Display mode	掉牌 Lose brand			
触点形式 Contact type	2副断电复归动合触点 2副断电保持动合触点 2 pairs of power-off resetting front contacts, 2 pairs of power-off holding front contacts		2副断电复归动合触点 4副断电保持动合触点 2 pairs of power-off resetting front contacts, 4 pairs of power-off holding front contacts	
触点断开容量 Contact breaking capacity	DC50W,AC250VA			

3 安装开孔尺寸、接线图 Mounging plate opening size,Wiring drawing

