



1 产品概述 Product Summarize

本继电器是一种带有舌簧式密封触点、永久磁铁自保持、电复归和灯光指示的继电器，用于直流操作的保护回路中，作为远方复归的动作指示器。

This is a relay with reed-type sealed contact, permanent magnet self-protection, electric resetting and lamplight pointing. This series are applying for protective circuit of DC operation as operation indicator of remote resetting.

2 主要技术参数 Main Technological Parameter

工作绕组额定值 Working winding rated value	启动电流 I_n (A) Starting current I_n (A)	0.010,0.015,0.025,0.05,0.075,0.1,0.15,0.25,0.5,1,2
	启动电压 U_n (V) Starting voltage U_n (V)	220,110,48,24
复归绕组额定值 U_n (V) Resetting winding rated value U_n (V)		220,110,48,24
动作值 Operation value	电流启动 Current starting	$\leq I_n$
	电压启动 Voltage starting	$\leq 70\%U_n$
复归值 Resetting value		$\leq 70\%U_n$
动作与返回时间(ms) Operating and return time (ms)		≤ 5
触点容量(W) Contact capacity (W)		DC 220V 0.2A, $t=5ms$, 10 电阻电路 30 DC 220V 0.2A, $t=5ms$, 10 resistance circuit 30

3 安装开孔尺寸、接线图 Mouning plate opening size,Wiring drawing

