



1 产品概述 Product Summarize

本继电器采用舌簧触点，用于直流操作保护或自动化装置中，作动作指示用。

触点密封，动作快，灵敏度高，灯光显示电气复归，保持自动复归触点各两副。

This series adopt reed-type sealed contact. This relay is applying for DC operative protection or automatic equipment as operation indicating.

It has the characteristics of sealed contact, rapid operation, high sensitivity, lamplight pointing electric resetting, and two pairs of holding automatic resetting contacts each.

2 主要技术参数 Main Technological Parameter

额定值 Rated value	工作电源(A) Working current (A)	0.010,0.015,0.025,0.05,0.075,0.1,0.15,0.25,0.5,1,2
	工作电压(V) Working voltage (V)	220,110,48,24
	复归电压(V) Resetting voltage (V)	220,110,48,24
动作时间(ms) Operating time (ms)		≤ 5
触点形式 Contact type		2 副动合保持触点,2 副断电复归动合触点 2 pairs of front holding contacts, 2 pairs of power-off resetting front contacts
动作值 Operating value		电压启动 ≤ 70%Un, 电流启动 ≤ In, 复归电压 ≤ 70%Un Voltage starting ≤ 70%Un, current starting ≤ In, resetting voltage ≤ 70%Un
触点断开容量 Contact breaking capacity		保持触点直流 10W 交流 30VA, 自动复归触点 ≤ 2W Holding contact DC 10W, AC 30VA, automatic resetting contact ≤ 2W

3 安装开孔尺寸、接线图 Mouning plate opening size,Wiring drawing

