



1 产品概述 Product Summarize

用于自动控制装置中，以扩大被控制的电路和提高接触能力。DZ-51型用于直流电路，DZ-52型用于交流电路，拍合式结构，利用弹簧返回，采用后接线插键方式。

This series are applying for automatic controlling equipments to enlarge the controlled circuits and improve contact capacity. DZ-51 type is used in DC circuit, and DZ-52 type is used in AC circuit with flapped structure which returns by spring and adopts back wiring bond-intercalated mode.

2 主要技术参数 Main Technological Parameter

型号 Type	DZ-51	DZ-52
额定电压(V) Rated voltage	DC 6,12,24,48,110,220	AC 12,24,36,60,110,127,220,380
触点形式 Contact type	2 动合,2 动断;4 动合,4 动断;2 动合,2 动断;2 转换 2 move to match, 2 move to break; 4 move to match, 4 move to break; 2 move to match, 2 move to break; 2 switching	
触点断开容量 Contact breaking capacity	U ≤ 250V, I ≤ 1A 直流有感电路(t=5ms)50W; U ≤ 250V I ≤ 2.5A 交流电路中 500VA U≤250V, I≤1A, DC inductive circuit (t=5ms) 50W; U≤250V, I≤2.5A, AC circuit 500VA	
动作电压 Operation voltage	≤ 75% 额定电压值 ≤75% rated voltage value	≤ 85% 额定电压值 ≤85% rated voltage value
返回电压 Return voltage	≥ 5% 额定电压 rated voltage	
动作时间(S) Operating time	≥ 0.03	

3 安装开孔尺寸、接线图 Mounging plate opening size,Wiring drawing

