



1 产品概述 Product Summarize

用于自动控制装置中，以扩大被控制的电路和提高接触能力。DZ-61型用于直流电路，DZ-62型用于交流电路电磁式动作原理，拍合式结构，利用弹簧返回，采用后接线插键方式。

This series are applying for automatic controlling equipments to enlarge controlled circuits and improve contact capacity. DZ-61 type is used in DC circuit, and DZ-62 type is used in AC circuit with flapped structure which returns by spring and adopts back wiring bond-intercalated mode.

2 主要技术参数 Main Technological Parameter

型号 Type	DZ-61	DZ-62
额定电压(V) Rated voltage	DC 6,12,24,48,110,220	AC,12,24,36,60,110,127,220,380
动作电压 Operation voltage	≤ 75% 额定电压值 ≤75% rated voltage value	≤ 85% 额定电压值 ≤85% rated voltage value
返回电压 Return voltage	≥ 5%额定电压 rated voltage	
动作时间(S) Operating time	≤ 0.03	
触点规格代号 Contact specification & code	20,02,40,04,22,002	
触点长期允许电流 Contact long term permit current	5A	
触点断开容量 Contact breaking capacity	DC 50W,AC 500VA	

3 安装开孔尺寸、接线图 Mouning plate opening size,Wiring drawing

