



1 产品概述 Product Summarize

本继电器具有保持绕组，用于直流操作的继电保护回路中，以增加主保护继电器的触点数量和容量。

This relay has holding windings, is applying for relay protective loop operated by DC to increase contact number and capacity of main protective relay.

2 主要技术参数 Main Technological Parameter

型号 Type		DZB-11E/312	DZB-12E/600	DZB-13E/312	DZB-14E/312	DZB-15E/312
直流 额定值 DC rated value	电压(V) Voltage	220,110,48,24	220,110,48,24	220,110,48,24		
	电流(A) Current				0.25,0.5,1,2,4,8	0.25,0.5,1,2,4,8
直流 保持值 DC holding value	电压(V) Voltage				220,110,48,24	220,110,48,24
	电流(A) Current	0.25,0.5,1,2,4,8	0.25,0.5,1,2,4,8	0.25,0.5,1,2,4,8		0.25,0.5,1,2,4,8
保持绕 组数量 No. of holding windings	电压 Voltage				1	1
	电流 Current	3	3	1		1
触点形式 Contact type		3动合,1动断, 2转换 3 move to mat h, 1 move to br eak, 2 switchin g	6动合 6 move to match	3动合,1动断, 2转换 3 move to mat ch, 1 move to break, 2 switc hing	3动合,1动断, 2转换 3 move to mat ch, 1 move to break, 2 switc hing	3动合,1动断, 2转换 3 move to mat ch, 1 move to break, 2 switc hing

3 安装开孔尺寸、接线图 Mounging plate opening size,Wiring drawing

