



### 1 产品概述 Product Summarize

用于继电保护与自动控制电路中,用作切换电路、增加触点的数量与容量,或用于出口跳闸电路。

拍合式电磁继电器。

This series are applying for relay protection and automatic controlling circuit to switch circuit and increase contact number and contact capacity. This series can also be applying in output tripping circuit.

This series are flapped type electromagnetic relays.

### 2 主要技术参数 Main Technological Parameter

额定工作电压 DC(V) Rated working voltage	220,110,48,24
额定工作电流 DC(A) Rated working current	0.25,0.5,1,2,4
额定保持电流 DC(A) Rated holding current	0.25,0.5,1,2,4
额定保持电压 DC(V) Rated holding voltage	220,110,48,24
动作值 Operating value	电压型 50%~70% 额定电压,电流型 ≤ 80% 额定电流 Voltage type 50%~70% rated voltage, current type ≤80% rated current
保持值 Holding value	电流保持 ≤ 80% 额定保持电流,电压保持 ≤ 70% 额定保持电压 Holding current ≤80% rated holding current, holding current ≤70% rated holding voltage
返回时间(ms) Return time (ms)	DZK-900/8 ≤ 5, DZK-900/4 ≤ 2
功耗(W) Power consumption (W)	电压线圈 ≤ 8, 电流线圈 ≤ 2.5 Voltage coil ≤ 8, current coil ≤ 2.5
触点容量 Contact capacity	DZK-900/8 为 50W 250VA, DZK-900/4 为 30W 150VA DZK-900/8 is 50W 250VA, DZK-900/4 is 30W 150VA

### 3 安装开孔尺寸、接线图 Mounging plate opening size, Wiring drawing

