



1 产品概述 Product Summarize

继电器用于磁力控制器或闭路板上,作为交、直流电动机运载和短路保护之用。不适于在下列条件下工作。

在腐蚀性气体及充满导电尘埃或水蒸所的地方。

有剧烈震动或强力颠簸及与垂直倾斜度超过 5° 的地方。

This series are mainly applying for magnetic blow out controller or closed circuit plate as DC, AC motor carrier loading and short circuit protection. This series are unsuitable to work under the following conditions:

The place with active gases and full of conductive dust or vapor;

The place with strenuous vibration or bumpiness and the vertical bank angle is >50.

2 主要技术参数 Main Technological Parameter

线圈代号	Coil code	额定电流	Rated current	调整范围	A Adjustment range	标定刻度	A Labeled calibration
1		600		720 ~ 2300		750、1500、2250	
2		300		360 ~ 1160		375、750、1100	
4		150		192 ~ 585		200、400、550	
6		100		120 ~ 455		150,300,450	
8		80		96 ~ 312		100,200,300	
11		60		72 ~ 233		75,150,225	
16		40		48 ~ 150		50,100,150	
32		20		24 ~ 78		25,50,75	
45		15		18 ~ 62		20,40,30	
64		10		12 ~ 39		13,25,38	

3 安装开孔尺寸、接线图 Mounging plate opening size,Wiring drawing

