



1 产品概述 Product Summarize

本继电器用在自动控制线路及电梯控制中作为扩大范围和提高接触能力之用。

电磁式动作原理。固定式安装在垂直屏板上，板后接线。

This series are applying for automatic controlling circuit and elevator controlling to enlarge range and improve contact capacity.

This series adopt electromagnetic working principle. The relay is installed on the vertical plate fixedly and adopts back wiring.

2 主要技术参数 Main Technological Parameter

型号规格 Type	JY-16A/61	JY-16A/63	JY-16A/62	JY-16A/64
特点 Characteristic	带外壳 With shell	不带外壳 Without shell	带外壳 With shell	不带外壳 Without shell
额定电压(V) Rated voltage (V)	直流 12,24,48,110,220		交流 6,12,24,36,48,60,110,127,220,380	
动作电压(V) Operating voltage (V)	≤ 70% 额定电压 rated voltage		≤ 85% 额定电压 rated voltage	
返回电压(V) Return voltage (V)	≥ 5% 额定电压 rated voltage			
动作时间(s) Operating time (S)	≤ 0.03			
触点规格代号 Contact specification code	20,02,40,04,22,002,202,022			
触点长期允许电流 Contact long term allowable current	5A			
触点断开容量 Contact breaking capacity	直流 50W,交流 250VA DC 50W, AC 250VA			

3 安装开孔尺寸、接线图 Mounging plate opening size,Wiring drawing

