



1 产品概述 Product Summarize

用于各种自动控制线路中,作为时间元件,可以同时控制5个按时间彼此关的元件。

电动机式原理,继电器的机构由同步电动机带动,依靠电动机和继电器中速装置的作用产生延时,继电器安装在垂直的面板上,可以前面接线或后面线订货时指明。This series are applying for all kinds of automatic controlling circuit as timing elements, which control 5 components by time-sequence.

This series adopt motor type principle. The structure of the relay is driven by synchronous motor, and then create delaying by the speed device in motor and relay. The relay can be mounted on vertical plate, and can be front wiring or back wiring.

2 主要技术参数 Main Technological Parameter

额定电压(V) Rated voltage (V)	220,127,12(50Hz)
延时整定范围(min) Delaying setting range (min)	1~20 准确度 ± 5s accuracy
触点形式 Contact type	5副延时动合,每副触点可独立延时整定,1副瞬时动合 5 pairs of delaying move to match, each contact can independently delaying setting, 1 pair of instantaneous move to match
触点断开容量(W) Return time (s), power consumption ≤1S	瞬时动合触点 20 延时动合触点 100 Instantaneous front contact 20 delaying front contact 100
返回时间(s),功耗 ≤ 1S Contact breaking capacity (W)	≤ 1

3 安装开孔尺寸、接线图 Mounging plate opening size,Wiring drawing

