






Leiterplatten-Layout Vorschlag für SMT
PCB-Layout Proposal for SMT





Anforderungsstufe 1
Performance Level 1

Kontaktbereich vergoldet
Mating Area gold plating

Anschlussbereich verzinkt 4-6 μm
Terminal Area 4-6 μm tin plating

Koplanarität der Anschlüsse $\leq 0.1\text{ mm}$
Coplanarity Area of Termination $\leq 0.1\text{ mm}$

Verpackt in Gurtverpackung - Tape on Reel Packaging
Verpackungseinheit: 560 Stück - Packaging unit: 560 pcs



BA7-03 - Standard Bauhöhe

type7-03 - standard assembly height

Copyright by ERNI GmbH
Proprietary notice pursuant to ISO 16016 to be observed

Information:			Tolerances		 All Dimensions in mm		Scale		3:1	
All rights reserved. Only for Information. To ensure that this is the latest version of this drawing, please contact one of the ERNI companies before using.			Subject to modification without prior notice. Drawing will not be updated.			Designation				
						Federl. SMC-Q 12-SMD-BA7-03 <i>Female SMC-Q 12-SMD-type7-03</i>				
			e		01.06.2011				www.ERNI.com	
Index		Date				Class			SMCQ	

Copyright by ERNI GmbH
Proprietary notice pursuant to ISO 16016 to be observed