







Bestückungsplan / contact layout



Leiterplatten- Lochbild / PCB drillhole pattern





Stecklänge / mating length



E = early mate, late break / voreilend

S = standard

L = late mate, early break / nacheilend



Lötanschluss 0,6x0,6mm / solder terminal 0,6x0,6mm

Isolierwerkstoff / housing material : PBT GF 30

Bauart 4 / type 4

Anforderungsstufe 1 = 500 Steckzyklen / performance class 1 = 500 mating cycles

Fehlende Maße und Angaben nach IEC 60 603-2 / DIN EN 60 603-2

Missing information and dimensions per IEC 60 603-2 / DIN EN 60 603-2

Bedruckung siehe Zeichnung 294905

marking see drawing 294905

Information:		Tolerances		Scale	2:1
All rights reserved. Only for Information. To ensure that this is the latest version of this drawing, please contact one of the ERNI companies before using.		Subject to modification without prior notice. Drawing will not be updated.		Designation	
-		21.09.2009		Messerleiste B/2 32 Löt	
Index		Date		Male Connector B/2 32 solder	
				384261	
				I	
				A3	
				Class	
				STVB/2	

Copyright by ERNI GmbH
Proprietary notice pursuant to ISO 16016 to be observed.

ERNI www.ERNI.com