



200W, EUC-200ST Series

- Power the world with highest efficiency -



- **Input Voltages/Power Factor:** 90 ~ 305 Vac / 0.99 (typical)
- **Output Wattage:** 200W, **Constant Current**
- Fully encapsulated with waterproof **IP67** level compliant,
- **Reliability Protections:** OVP, OTP, SCP
- **High Efficiency:** up to 92%
- **Safety Regulation:** Comply with UL8750 & EN61347
- **MTBF: 300,000 hrs @ 25°C, full load, 110 Vac input**
- **Lifetime: 70,000 Hrs @ 110 Vac Input, 80% load, 25°C ambient Temp.**
- **Warranty: 5-year**



Model No. (1)	Output Voltage Range (V)	Output Current (A)	OVP (Vmax.)	OTP (°C)	Efficiency (%) (5)	Comment
EUC-200S045ST	267 - 445	0.45	668	110	92	
EUC-200S070ST	171 - 285	0.70	428	110	92	
EUC-200S105ST	114 - 190	1.05	285	110	92	
EUC-200S140ST	85 - 142	1.40	213	110	92	
EUC-200S175ST	68 - 114	1.75	171	110	91	
EUC-200S210ST	57 - 95	2.10	143	110	91	
EUC-200S245ST	48 - 81	2.45	122	110	91	
EUC-200S280ST	42 - 71	2.80	107	110	91	
EUC-200S315ST	38 - 63	3.15	95	110	91	
EUC-200S350ST	34 - 57	3.50	86	110	91	
EUC-200S420ST	28 - 47	4.2	71	110	91	
EUC-200S490ST	24 - 40	4.9	60	110	91	
EUC-200S560ST	21 - 35	5.6	53	110	91	
EUC-200S630ST	19 - 32	6.3	48	110	91	
EUC-200S833ST	14 - 24	8.33	36	110	90	

Note (1) A suffix - XXXX may be added to denote variations or modifications to the base unit (2) Output Rated Class 2 at USR & CNR (3) Non-Class 2 output at USR & CNR (4) Class 2 output (USR) & Non-Class 2 output (CNR) (5) All rating measured at Full Load and 220 Vac Input

Parameter	Conditions/ Description	Min.	Normal	Max.	units
Input Voltage Range	Universal Input	90	100 - 277	305	Vac
Input Frequency Range		47		63	Hz
Input Current	100 Vac / 220 Vac input, full load output			2.4 / 1.2	A
Power Factor	At 100 Vac / 220 Vac Input	0.99 / 0.96			
Inrush Current	At 240 Vac Input, 25°C cold start			65	A

Parameter	Conditions/ Description	Min.	Normal	Max.	units
Line Regulation				±1	%
Load Regulation				±3	%
Ripple and Noise	20MHz Bandwidth, refer Note-1			3	%pk-pk (Vo)
Voltage Overshoot / Under shoot	% of Vout when power turn on or off			10	%
Turn-On Delay	Measured at 110 Vac / 220 Vac Input and Full Load			2.0 / 2.0	S

Parameter	Conditions/ Description	Min.	Normal	Max.	units
Efficiency	Refer to individual models, measured at Full load, 110/ 220 Vac @ 25°C	87.0 / 88.0	89.0 / 90.0		%
MTBF	Per MIL-HDBK-217F @ 25°C ambient temperature, full load, 110 Vac input		300,000		Hours
Operating/ Storage Temperature		-35 / -40		70 / 80	°C
Dimension (L x W x H)		266.4 x 79.5 x 46.0 / 10.5 x 3.1 x 1.8			mm / inch
Weight		1,500			g

Parameter	Standard	Category	Comment
SAFETY	USA & Canada: UL 8750 Compliance to UL 1310 Class 2, UL 1012, UL 935		
	CAN/ CSA-22.2 No. 0. CSA-C22.2 No. 250.0	cUL	
	Europe: EN 61347-1, EN61347-2-13	CE	
EMI	Conducted emission Test & Radiated emission Test with 6 dB margin	EN55015	
	Harmonic Distortion, Current Emission	EN61000-3-2	
EMS	Voltage Flicker and Fluctuation	EN61000-3-3	
	Electrostatic Discharge (ESD)	EN61000-4-2	
	Radiated RFI	EN61000-4-3	
	Fast Transients / Burst - EFT	EN61000-4-4	
	Input Line Surge Immunity	EN61000-4-5	
	Conducted RFI	EN61000-4-6	
	Power Freq Magnetic Field	EN61000-4-8	
	Voltage Dips	EN61000-4-11	
	Electromagnetic Immunity Requirements Applied to Lighting Equipment	EN61547	

Parameter	Standard	Level	Comment
ROHS	European Directive 2002/ 95/ EC	Compliant	




- Power the world with highest efficiency -


200W, EUC-200ST Series

Dimension: (L x W x H)

- 266.4 x 79.5 x 46.0 (mm) / 10.5 x 3.1 x 1.8 (inch)
- tolerance: ± 0.5 mm



L1 AC Input



Input wiring assembly – SJTW 18AWG 3C

- White(N), Black (L), Green(G) – 650±30mm

L2 DC output



Output wiring assembly – SJTW 18AWG 2C

- Brown(+), Blue (-) – 230±30mm

1. Datasheets are updated as needed and as such, specifications are subject to change without notice.
2. Product labels shown, including safety agency certifications on labels, may vary based on the date manufactured.
3. Mechanical drawings (model No. MSL-T0700IC285.0-200B) is for reference only. The cable wire configuration may vary from other custom designed models as picture showing. Please contact your sales representative for detail.
4. Specifications are for reference only. All specifications are measured at an ambient temperature of 25°C, humidity < 75%, nominal input voltage and at rated output load unless otherwise specified.