

EFRP-S3490

3U 950W Server Power Supply

Features:

High Efficiency $\geq 78\%$

N+1 Redundant Design

0~45°C Working Temperature

SSI Standard Compliant

PMBus Support

General Specification

- Input Range: 100 to 240 VAC, +/-10%
- Power Factor: 0.95 minimum
- Hold Up Time: 17ms minimum, at full load
- Short Circuit Protection
- Over Current Protection
- Over Voltage Protection
- MTBF >100,000 Hours@25°C
- Operating Temperature: 0 to 45 °C
- Operating Humidity: 20 to 90 %
- EMI/RFI: CE, FCC class B
- Safety: UL, TUV, CCC, CB, BSMI

Input and Output Characteristics

Input			Output					
Voltage	Frequency	Current	Load	+3.3V	+5V	+12V	-12V	+5VSB
100~240 VAC	47~63Hz	15~7.5A	Max.Load	30A	40A	68A	0.5A	3A
			Min.Load	1A	1A	2A	0A	0.1A

1. The +5 & +3.3 Volt combine total output current shall not exceed 210W

2. The +5, +3.3 & +12Volt total output shall not exceed 930W.

Ripple and Noise

Output	+3.3V	+5V	+12V	-12V	5Vsb
Load Regulation	$\pm 5\%$	$\pm 5\%$	$\pm 5\%$	$\pm 10\%$	$\pm 5\%$
Line Regulation	$\pm 1\%$	$\pm 1\%$	$\pm 1\%$	$\pm 1\%$	$\pm 1\%$
Ripple & Noise	60mV	60mV	120mV	120mV	70mV

Our website >>>
www.etasis.com.tw

Mechanical

Outline Dimension: 86x126.9x290(mm)

Outline Drawing

