

DCMOD® AE-080D

DC INPUT / ITE APPROVED

80 WATT POWER PLATFORM

5.00 x 3.20 x 1.50" | 127.0 x 81.3 x 38.1mm



DESCRIPTION

UNIPOWER's DCMOD® AE-080D SERIES is an 80 Watt DC Input Power Supply platform with both standard and configurable models featuring output voltage(s) that can be quickly configured to order while maintaining all international safety approvals.

These power supplies are available with 12V, 24V or 48V Input Ranges and single or quad output configurations ranging from 1.5 to 48 VDC. The AE-080D feature an industry-standard footprint, international safety approvals, Class B emissions; and -20 ~ +70°C operation (see derating).

DCMOD® UPGRADES include a multitude of output voltage configurations, optional covers (with or without fan), extended temperature operating range, isolated outputs, attached wire harnesses and much, much more. All these modifications are available without any impact on safety approvals to reduce both development cost and time to market.

FEATURES

- ◆ 12V, 24V or 48V DC Input
- ◆ Industry-Standard 3.2" x 5" U-Frame Footprint
- ◆ 1 or 4 Outputs configurable from 1.5~48VDC
- ◆ International Safety Approvals
- ◆ >500k Hours MTBF, Demonstrated
- ◆ Optional -40°C Guaranteed Start-Up
- ◆ Double Sided PC Board



Contact UNIPOWER to discuss
your application and define
the right part number for your
specific application:

Tel: +1-954-905-1070

Email: the.power.solution@unipowerco.com



FIVE YEAR WARRANTY

INTERNATIONAL STANDARDS

UL/cUL 60950-1 2nd Ed.
EN60950-1 2nd Ed.
CB Report, IEC60950-1
CE Mark (LVD)

For the AC input version see [EASYSMOD AE-080U](#) datasheet

For the Medical Approved version see [MEDIMOD AE-080UM](#) datasheet

www.unipowerco.com

North America & CALA: +1 954-346-2442 • EMEA: +1 561-990-3830 • sales@unipowerco.com

“IF WHAT YOU SEE IS WHAT YOU DON’T WANT, IT CAN EASILY BE CHANGED.” The DCMOD® family of switching power supplies has been designed with two precepts; (1) the laws of physics are immutable, and (2) the satisfaction of customer requirements and needs is paramount.

A host of modifications, only some of which are listed below, can and will be performed on products for customer programs requiring as few as 250 units per year. These “mods” are available at nominal premium (if any), normally without non-recurring engineering costs (although a one time documentation fee may be incurred), and usually with all safety agency approvals in place. This minimizes both product development cost and new product time to market. Effectively, DCMODs® allow small program requirements the luxury of costly custom power supply designs.

TYPICAL MODIFICATIONS

- Unique Output Combinations from 1.5 to >48 volts
- Isolated Outputs
- Low Output Ripple and Noise
- Cover & Fan Assembly
- Extended Temperature Operating Range
- -40°C Start-Up
- Zero Load Operation

FLEXIBLE OUTPUT CONFIGURATION GUIDELINES

with 12, 24 or 48 VDC Input and -20-50°C Operation

Single Output Capabilities

OUTPUT CURRENT	1.5~3.3V	5V	12V	15V	24V	48V
MINIMUM	0A	0A	0A	0A	0A	0A
CONVECTION ⁽³⁾	12A	12A	5.0A	4.0A	2.5A	1.25A
15 CFM AIR ⁽⁴⁾	16A	16A	6.6A	5.3A	3.3A	1.67A
PEAK ⁽⁵⁾	19A	19A	7.5A	6.3A	3.75A	1.87A

Multiple Output Capabilities

OUTPUT	DC OUTPUT	MIN	CON ⁽³⁾	AIR ⁽⁴⁾	PEAK ^(4, 5)
V1	1.5 ~ 48V ⁽⁷⁾	1.0A ^(2, 13)	10.0A	14.0A	16.0A
V2	1.5 ~ 48V ⁽⁸⁾	0.4A ^(2, 13)	4.0A	7.0A	9.0A
V3	1.5 ~ 48V ⁽⁸⁾	0.4A ^(2, 13)	4.0A	5.0A	6.5A
V4	1.5 ~ 48V ⁽⁸⁾	0.2A ^(2, 13)	2.0A	3.0A	4.0A

(1) Full power out on V3-V4 with minimal V1 and V2 loading—Option.

(2) 10% minimum load for stated regulation on multiple O/P units.

(3) Convection cooling.

(4) 15 CFM forced air cooling conditions.

(5) 30 seconds maximum duration.

(6) Most output combinations from 1.5 to 48 Volts possible; up to maximum rated Current / Power...Consult UNIPOWER.

(7) Specify 0.1V increments.

(8) Specific output voltage is current dependent.

(9) Regulation may degrade under some output Consult UNIPOWER.

(10) Consult UNIPOWER for Model #.

(11) For outputs >48 Volts, consult UNIPOWER.

(12) Cover and custom sheet metal available.

(13) 10% minimum of marked rating.

Contact UNIPOWER to discuss your application and define the right part number for your specific application:

Call: +1-954-905-1070 • Email: the.power.solution@unipowerco.com

For the Medical Approved version see [MEDIMOD AE-080UM](#) datasheet | For the AC Input version see [EASYSMOD AE-080U](#) datasheet.

SPECIFICATIONS

Typical at Nominal Line, Full Load and 25°C Unless Otherwise Noted.

INPUT

Input Voltage Range Options	9-18, 18-36 or 36-72 VDC Ranges
Input Current @ 12 VDC Input	12A Max
Input Current @ 24 VDC Input	6A Max
Input Current @ 48 VDC Input	4A Max
Fusing @ 24 VDC Input	15A Max
Fusing @ 24 VDC Input	8A Max
Fusing @ 48 VDC Input	5A Max

OUTPUT

Output Power	60W Convection / 80W with 15 CFM Airflow
Efficiency	75% Typical
Adjustment Range (V1 Only)	±5%
Ripple / Noise, max	1% pk-pk max
Line Regulation	Max ±0.2%
Load Regulation @ 60% ±40% Full Load	
V1	±3% max
V2-V4	±5% max
Cross Regulation @ 60% ±40% Full Load	
V1: Change in V2 - V4	±0.5%
V2 - V4: Change in V1 @75 ±25% F/L	±5% max
Overvoltage Protection (V1 Only)	>130% (Latch Off)
Power Limit	>120% (Auto-Recovery)
Overshoot (all outputs)	10% max
Response Time	500 µSec (25-75% step load)
Switching Frequency	60KHz (typical)

ENVIRONMENTAL

Operating Temp. Range	-20°C to +50°C (Full Load)
	Consult factory for -40°C Guaranteed Start-Up and Industrial Temperature Range options
Output Current Derating	2.5%/°C, 50°C to 70°C
Storage Temp. Range	-40°C to +85°C
Humidity	5% to 95%, Non-Condensing
MTBF, Demonstrated	>500,000 Hours
Cooling	15 CFM Airflow for Full Power
Altitude	10,000 feet

PHYSICAL SPECIFICATIONS

Case Dimensions	5.00 x 3.20 x 1.50" / 127 x 81.3 x 38.1mm
Weight	0.9 lbs. (0.41 kg.)
Vibration from 10 - 55Hz	1.0G Peak
	(3 orthogonal axes @ 1 octave/min, 5 minute dwell @ 4 major resonances)

SAFETY STANDARDS

UL60950-1 2nd Ed., EN60950-1 2nd Ed., CB REPORT (IEC 60950-1), CE MARK (LVD)
(not including 12VDC input models)

EMI STANDARDS

FCC Class A & VDE Class A, CISPR 11; EN 55011 Class A
(Class B optional, consult factory)

OUTLINE DRAWING

CONNECTOR 1

(MOLEX#09-65-2058 OR EQUIVALENT;
MATING CONNECTOR= MOLEX#09-50-3051)

PIN1	GROUND
PIN2	-VIN
PIN3	-VIN
PIN4	+VIN
PIN5	+VIN

CONNECTOR 2 (single output)

(MOLEX#09-65-2088 OR EQUIVALENT;
MATING CONNECTOR= MOLEX#09-50-3081)

PIN1	V1
PIN2	V1
PIN3	V1
PIN4	RET
PIN5	RET
PIN6	RET
PIN7	NC
PIN8	NC

CONNECTOR 2 (multi-output)

(MOLEX#09-65-2088 OR EQUIVALENT;
MATING CONNECTOR= MOLEX#09-50-3081)

PIN1	V2
PIN2	V1
PIN3	V1
PIN4	RET
PIN5	RET
PIN6	V3
PIN7	V4
PIN8	V4 RET

