

## DESCRIPTION

UNIPOWER's DCMOD® AF-180D SERIES is a 180 Watt DC Input Power Supply platform with both standard and configurable models featuring output voltage(s) that can be quickly configured to order while maintaining all international safety approvals.

These power supplies are available with 12 / 24 / 48 VDC Input Ranges and single or quad output configurations ranging from 1.5 to 48 VDC. The AF-180D feature an industry-standard footprint, international safety approvals, Class B emissions; and -20 ~ +70°C operation (see derating).

DCMOD® UPGRADES include a multitude of output voltage configurations, optional covers (with or without fan), extended temperature operating range, isolated outputs, attached wire harnesses and much, much more. All these modifications are available without any impact on safety approvals to reduce both development cost and time to market.

## FEATURES

- ◆ 12V, 24V or 48V DC Inputs
- ◆ 1 or 4 Outputs configurable from 1.5~48VDC
- ◆ International Safety Approvals
- ◆ >500k Hours MTBF, Demonstrated
- ◆ Optional -40°C Guaranteed Start-Up
- ◆ Double Sided PC Board



**FIVE YEAR WARRANTY**

## INTERNATIONAL STANDARDS

UL/cUL 60950-1 2nd Ed.  
 EN60950-1 2nd Ed.  
 CB Report, IEC60950-1  
 CE Mark (LVD)

North America & CALA: +1 954-346-2442 • EMEA: +1 561-990-3830 • sales@unipowerco.com

## DCMOD® AF-180D SERIES

DC INPUT / ITE APPROVED

180 WATT POWER PLATFORM

6.80 x 3.80 x 1.50" | 172.7 x 96.5 x 38.1mm



Contact UNIPOWER to discuss  
 your application and define  
 the right part number for your  
 specific application:

Tel: +1-954-905-1070

Email: [the.power.solution@unipowerco.com](mailto:the.power.solution@unipowerco.com)

For the AC input version see [EASMOD AF-180P](#) datasheet

For the Medical Approved version see [MEDIMOD AF-180PM](#) datasheet

[www.unipowerco.com](http://www.unipowerco.com)

“IF WHAT YOU SEE IS WHAT YOU DON’T WANT, IT CAN EASILY BE CHANGED.” The DCMOD® family of switching power supplies has been designed with two precepts; (1) the laws of physics are immutable, and (2) the satisfaction of customer requirements and needs is paramount.

A host of modifications, only some of which are listed below, can and will be performed on products for customer programs requiring as few as 250 units per year. These “mods” are available at nominal premium (if any), normally without non-recurring engineering costs (although a one time documentation fee may be incurred), and usually with all safety agency approvals in place. This minimizes both product development cost and new product time to market. Effectively, DCMODs® allow small program requirements the luxury of costly custom power supply designs.

#### TYPICAL MODIFICATIONS

- Unique Output Combinations from 1.5 to >48 volts
- Power Fail / Power Good Signals
- Enable / Inhibit
- Isolated Outputs
- Low Output Ripple and Noise
- Cover & Fan Assembly
- Extended Temperature Operating Range
- -40°C Start-Up
- Zero Load Operation
- Remote Sense
- Remote On / Off

### FLEXIBLE OUTPUT CONFIGURATION GUIDELINES

with 12, 24 or VDC Input and -20-50°C Operation

#### Single Output Capabilities

OUTPUT CURRENT	1.5~3.3V	5V	12V	15V	24V	48V
MINIMUM	0A	0A	0A	0A	0A	0A
CONVECTION <sup>(3)</sup>	20.0A	20.0A	11.0A	9.5A	5.5A	2.75A
30 CFM AIR <sup>(4)</sup>	36.0A	36.0A	15.0A	12.0A	7.5A	3.75A
PEAK <sup>(5)</sup>	41.0A	41.0A	17.0A	14.0A	8.35A	4.25A

#### Multiple Output Capabilities

OUTPUT	DC OUTPUT	MIN	CON <sup>(3)</sup>	AIR <sup>(4)</sup>	PEAK <sup>(4, 5)</sup>
V1	1.5 ~ 48V <sup>(7)</sup>	2.0A <sup>(2, 13)</sup>	20.0A	30.0A	35.0A
V2	1.5 ~ 48V <sup>(8)</sup>	1.2A <sup>(2, 13)</sup>	12.0A	18.0A	20.0A
V3	1.5 ~ 48V <sup>(8)</sup>	0.4A <sup>(2, 13)</sup>	4.0A	6.0A	8.0A
V4	1.5 ~ 48V <sup>(8)</sup>	0.4A <sup>(2, 13)</sup>	4.0A	6.0A	8.0A

(1) Full power out on V3-V4 with minimal V1 and V2 loading—Option.

(2) 10% minimum load for stated regulation on multiple O/P units.

(3) Convection cooling.

(4) 30 CFM forced air cooling conditions.

(5) 30 seconds maximum duration.

(6) Most output combinations from 1.5 to 48 Volts possible; up to maximum rated Current / Power..Consult UNIPOWER.

(7) Specify 0.1V increments.

(8) Specific output voltage is current dependent.

(9) Regulation may degrade under some output Consult UNIPOWER.

(10) Consult UNIPOWER for Model #.

(11) For outputs >48 Volts, consult UNIPOWER.

(12) Cover and custom sheet metal available.

(13) 10% minimum of marked rating

Contact UNIPOWER to discuss your application and define the right part number for your specific application:

Call: +1-954-905-1070 • Email: [the.power.solution@unipowerco.com](mailto:the.power.solution@unipowerco.com)

For the Medical Approved version see [MEDIMOD AF-180PM](#) datasheet | For the AC Input version see [EASYMOD AF-180P](#) datasheet.

## SPECIFICATIONS

Typical at Nominal Line, Full Load and 25°C Unless Otherwise Noted.

### INPUT

Input Voltage Range Options	10-18 / 18-36 / 36-72 VDC Ranges
Input Current @ 12 VDC Input	20A Max
Input Current @ 24 VDC Input	12A Max
Input Current @ 48 VDC Input	7A Max
Fusing @ 12 VDC Input Range	30A Max
Fusing @ 24 VDC Input Range	20A Max
Fusing @ 48 VDC Input Range	10A Max

### OUTPUT

Output Power	130W Convection / 180W with 30 cfm Airflow
Efficiency	75% Typical
Adjustment Range (V1 Only)	±5%
Ripple / Noise, max	1% pk-pk max
Line Regulation	Max ±0.2%
Load Regulation @ 60% ±40% Full Load	
V1	±3% max
V2-V4	±5% max
Cross Regulation @ 60% ± 40% Full Load	
V1: Change in V2 - V4	±0.5%
V2 - V4: Change in V1 @ 75 ±25% F/L	±5% max
Overvoltage Protection (V1 Only)	>130% (Latch Off)
Power Limit	>120% (Auto-Recovery)
Overshoot (all outputs)	10% max
Response Time	500 µSec (25-75% step load)
Switching Frequency	60KHz (typical)

### ENVIRONMENTAL

Operating Temp. Range	-20°C to +50°C (Full Load)
	Consult factory for -40°C Guaranteed Start-Up and Industrial Temperature Range options
Output Current Derating	2.5%/°C, 50°C to 70°C
Storage Temp. Range	-40°C to + 85°C
Humidity	5% to 95%, Non-Condensing
MTBF, Demonstrated	>500,000 Hours
Cooling	30 cfm Airflow for Full Power
Altitude	10,000 feet

### PHYSICAL SPECIFICATIONS

Case Dimensions	6.80 x 3.80 x 1.50" / 172.7 x 96.5 x 38.1mm
Weight	1.5 lbs. (0.68 kg.)
Vibration from 10 - 55Hz	1.0G Peak
	(3 orthogonal axes @ 1 octave/min, 5 minute dwell @ 4 major resonances)

### SAFETY STANDARDS

UL60950-1 2nd Ed., EN60950-1 2nd Ed., CB REPORT (IEC 60950-1), CE MARK (LVD)
(not including 12VDC input models)

### EMI STANDARDS

FCC Class A & VDE Class A, CISPR 22; EN 55022 Class A
(Class B available. Consult factory)

## OUTLINE DRAWING

### CONNECTOR 1

PIN1	GROUND
PIN2	-VIN
PIN3	+VIN

### CONNECTOR 2 (single output)

PIN1	V1
PIN2	V1
PIN3	V1
PIN4	V1
PIN5	RET
PIN6	RET
PIN7	RET
PIN8	RET

### CONNECTOR 2 (multi-output)

PIN1	V1
PIN2	V1
PIN3	RET
PIN4	RET
PIN5	V2
PIN6	V3
PIN7	V4 RET
PIN8	V4

Consult factory for optional Molex Connectors

