



Helical geared motors and helical gear units
斜齿轮减速马达 / 减速机

H


CH




H - PH



IH







Designation 选型说明

CH - H - IH

CH	Compact geared motor with helical gears (supplied complete with motor) 小型斜齿轮减速马达 (连马达一起供应)		
H - PH	Fitted geared motor with helical gears 斜齿轮减速箱 (输入端可与马达法兰连接)		
IH	Helical gear reduction unit 斜齿轮减速箱 (凸轴输入)		
052	Size 050, 2 reduction stages, cast iron series. 尺寸 050 二级减速- 铸铁外壳		
A52	Size 050, 2 reduction stages, aluminium alloy series. 尺寸 050 二级减速- 铝合金外壳		
FA - FB FC	Output flange 输出法兰		
44.7	Reduction ratio 减速比		
B3	Mounting position 安装方向		
Input Dimensions / 输入尺寸			
PAM	Fitted for motor coupling 连接马达法兰		
160	Motor flange diameter 马达法兰直径	14	Drive-shaft diameter 驱动轴直径
Output Dimensions / 输出尺寸			
250	Output flange diameter. 输出法兰直径	40	Output shaft diameter. 输出轴直径


Features / 选型说明

 Series
系列


HA..

Reducers with casing in aluminium alloy

Industrial applications where high reliability is requested even in the case of heavy but consistent service.

铝合金外壳减速马达

高可靠性, 适合工业用途, 可长时间承受稳定负载.

 Series
系列

H...

Reducers with casing in grey cast iron

Industrial applications where high reliability is requested even in the case of heavy service with high impact loads. Units are particularly suitable to support high radial loads.

铸铁外壳减速马达


高可靠性, 适合工业用途, 可承受瞬间冲击负荷.

CH - H - IH





1	2	3
-	A32	A33
A41	A42	A43
A51	A52	A53
A61	A62	A63

CH - H - PH - IH

1	2	3
-	032	033
041	042	043
051	052	053
061	062	063
081	082	083
101	102	103
121	122	123
-	142	143










Versions 型号

	A41 - A51 - A61
	A41F - A51F - A61F
	A32 - A33 - A42 - A43 - A52 - A53 - A62 - A63
	A32F - A33F - A42F - A43F - A52F - A53F A62F - A63F


CH - H - IH

Aluminium alloy series.
铝合金外壳系列

	041 - 051 - 061 - 081 - 101 - 121
	041F - 051F - 061F - 081F - 101F - 121F
	041M - 051M - 061M - 081M - 101M - 121M
	041U - 051U - 061U - 081U - 101U - 121U
	032 - 033 - 042 - 043 - 052 - 053 - 062 - 063 082 - 083 - 102 - 103 - 122 - 123 - 142 - 143
	032F - 033F - 042F - 043F - 052F - 053F 062F - 063F - 082F - 083F - 102F - 103F 122F - 123F - 142F - 143F
	032U - 033U - 042U - 043U - 052U - 053U 062U - 063U - 082U - 083U - 102U - 103U 122U - 123U - 142U - 143U

CH - H - PH - IH

Grey cast iron series.
铸铁外壳系列



Predisposition 电机-减速机配合
CH...A30 - A40 - A50 - A60

	i	063	071	080	090	100	112
CH A32	5,4 ÷ 30,5	B10	B10	B10			
CH A32	35,4 ÷ 60,7	B10	B10				
CH A33	51,3 ÷ 166,6	B10	B10				
CH A33	193,3 ÷ 347,3	B10	B10				
CH A41	1,45 ÷ 5,45	B10	B10	B10			
CH A41	7,88 ÷ 10,83	B10	B10				
CH A42	5,4 ÷ 30,5	B10	B10	B10	B10		
CH A42	35,4 ÷ 60,7	B10	B10				
CH A43	51,3 ÷ 166,6	B10	B10				
CH A43	193,3 ÷ 347,3	B10	B10				
CH A51	1,45 ÷ 5,45	B10	B10	B10	B10		
CH A51	7,88 ÷ 10,83	B10	B10				
CH A52	5,1 ÷ 25,4			B10	B10	B10	B10
CH A52	29,9 ÷ 61,9			B10	B10		
CH A53	49,8 ÷ 163,1	B10	B10	B10	B10		
CH A53	200,3 ÷ 354	B10	B10				
CH A61	1,33 ÷ 4,38			B10	B10	B10	B10
CH A61	7,75 ÷ 10,67			B10	B10		
CH A62	5,1 ÷ 25,4			B10	B10	B10	B10
CH A62	29,9 ÷ 61,9			B10	B10		
CH A63	49,8 ÷ 163,1	B10	B10	B10	B10		
CH A63	200,3 ÷ 354	B10	B10				

B10 = Motor with special execution / B10 为特殊马达

H...A30 - A40 - A50 - A60

	i	063	071	080	090	100	112
H A32	5,4 ÷ 30,5	B5	B5-B14	B5-B14			
H A32	35,4 ÷ 60,7	B5	B5-B14				
H A33	51,3 ÷ 166,6	B5	B5-B14				
H A33	193,3 ÷ 347,3	B5	B5-B14				
H A41	1,45 ÷ 5,45	B5	B5-B14	B5-B14			
H A41	7,88 ÷ 10,83	B5	B5-B14				
H A42	5,4 ÷ 30,5	B5	B5-B14	B5-B14	B5-B14		
H A42	35,4 ÷ 60,7	B5	B5-B14				
H A43	51,3 ÷ 166,6	B5	B5-B14				
H A43	193,3 ÷ 347,3	B5	B5-B14				
H A51	1,45 ÷ 5,45	B5	B5-B14	B5-B14	B5-B14		
H A51	7,88 ÷ 10,83	B5	B5-B14				
H A52	5,1 ÷ 25,4			B5-B14	B5-B14	B5-B14	B5-B14
H A52	29,9 ÷ 61,9			B5-B14	B5-B14		
H A53	49,8 ÷ 163,1	B5	B5-B14	B5-B14	B5-B14		
H A53	200,3 ÷ 354	B5	B5-B14				
H A61	1,33 ÷ 4,38			B5-B14	B5-B14	B5-B14	B5-B14
H A61	7,75 ÷ 10,67			B5-B14	B5-B14		
H A62	5,1 ÷ 25,4			B5-B14	B5-B14	B5-B14	B5-B14
H A62	29,9 ÷ 61,9			B5-B14	B5-B14		
H A63	49,8 ÷ 163,1	B5	B5-B14	B5-B14	B5-B14		
H A63	200,3 ÷ 354	B5	B5-B14				



Predisposition 电机-减速机配合

CH - H - PH ...032

i	071	080	090	100	112
4.7	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
6.2	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
7.8	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
8.9	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
10.1	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
11.8	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
13.7	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
14.7	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
16.8	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
18.2	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
19.9	B5-B11	B5-B11	B5-B11		
22.7	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
23.8	B5-B11	B5-B11	B5-B11		
26.4	B5-B11	B5-B11	B5-B11		
29.7	B5-B11	B5-B11	B5-B11		
32.9	B5-B11	B5-B11	B5-B11		
37.9	B5-B11	B5-B11	B5-B11		
41.4	B5-B11	B5-B11	B5-B11		
47.3	B5-B11	B5-B11	B5-B11		

CH - H - PH ...033

i	063	071	080	090
53.6	B5-B11	B5-B11	B5-B11	B5-B11
66.8	B5-B11	B5-B11	B5-B11	B5-B11
74.8	B5-B11	B5-B11	B5-B11	B5-B11
99.3	B5-B11	B5-B11	B5-B11	B5-B11
108.0	B5-B11	B5-B11		
123.7	B5-B11	B5-B11	B5-B11	B5-B11
143.3	B5-B11	B5-B11		
178.6	B5-B11	B5-B11		
197.2	B5-B11	B5-B11		
245.7	B5-B11	B5-B11		

CH - H - PH...041

i	071	080	090
1.44	B5-B11	B5-B11	B5-B11
2	B5-B11	B5-B11	B5-B11
2.55	B5-B11	B5-B11	B5-B11
2.71	B5-B11	B5-B11	B5-B11
3.11	B5-B11	B5-B11	B5-B11
3.59	B5-B11	B5-B11	B5-B11
4.2	B5-B11	B5-B11	B5-B11
5	B5-B11	B5-B11	B5-B11
5.5	B5-B11	B5-B11	B5-B11
6.09	B5-B11	B5-B11	B5-B11
7.67	B5-B11	B5-B11	B5-B11
8.75	B5-B11	B5-B11	B5-B11

CH - H - PH ...042


i	071	080	090	100	112
5.5	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
7.2	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
8.9	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
10.3	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
11.8	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
13.6	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
16.0	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
19.0	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
21.0	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
23.1	B5-B11	B5-B11	B5-B11		
26.0	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
27.5	B5-B11	B5-B11	B5-B11		
30.5	B5-B11	B5-B11	B5-B11		
34.1	B5-B11	B5-B11	B5-B11		
37.8	B5-B11	B5-B11	B5-B11		
43.8	B5-B11	B5-B11	B5-B11		
47.5	B5-B11	B5-B11	B5-B11		
54.3	B5-B11	B5-B11	B5-B11		

CH - H - PH ...043

i	063	071	080	090
61.8	B5-B11	B5-B11	B5-B11	B5-B11
76.7	B5-B11	B5-B11	B5-B11	B5-B11
87.1	B5-B11	B5-B11	B5-B11	B5-B11
114.5	B5-B11	B5-B11	B5-B11	B5-B11
125.7	B5-B11	B5-B11		
142.0	B5-B11	B5-B11	B5-B11	B5-B11
165.4	B5-B11	B5-B11		
205.1	B5-B11	B5-B11		
227.5	B5-B11	B5-B11		
282.1	B5-B11	B5-B11		

CH - H - PH...051

i	071	080	090	100	112
1.27		B5-B11	B5-B11	B5-B11	B5-B11
1.42		B5-B11	B5-B11	B5-B11	B5-B11
2.13		B5-B11	B5-B11	B5-B11	B5-B11
2.57	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
3.17	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
3.69	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
4	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
4.77	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
5.25	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
5.82	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
7.33	B5-B11	B5-B11	B5-B11		
8.38	B5-B11	B5-B11	B5-B11		


Predisposition 电机-减速机配合
CH - H - PH ...052

i	071	080	090	100	112
5.7		B5-B11	B5-B11	B5-B11	B5-B11
6.9		B5-B11	B5-B11	B5-B11	B5-B11
8.5		B5-B11	B5-B11	B5-B11	B5-B11
9.6		B5-B11	B5-B11	B5-B11	B5-B11
11.5		B5-B11	B5-B11	B5-B11	B5-B11
14.2		B5-B11	B5-B11	B5-B11	B5-B11
16.6	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
18.0	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
20.0	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
21.7	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
24.7	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
26.2	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
28.4	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
31.5	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
33.0	B5-B11	B5-B11	B5-B11		
39.0	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
45.4	B5-B11	B5-B11	B5-B11		
49.1	B5-B11	B5-B11	B5-B11		
56.1	B5-B11	B5-B11	B5-B11		

CH - H - PH ...053

i	063	071	080	090
58.8	B5-B11	B5-B11	B5-B11	B5-B11
72.7	B5-B11	B5-B11	B5-B11	B5-B11
90.5	B5-B11	B5-B11	B5-B11	B5-B11
108.9	B5-B11	B5-B11	B5-B11	B5-B11
134.8	B5-B11	B5-B11	B5-B11	B5-B11
157.3	B5-B11	B5-B11		
194.6	B5-B11	B5-B11		
216.4	B5-B11	B5-B11		
267.7	B5-B11	B5-B11		

CH - H - PH...061

i	080	090	100	112
1.34	B5-B11	B5-B11	B5-B11	B5-B11
2.13	B5-B11	B5-B11	B5-B11	B5-B11
2.57	B5-B11	B5-B11	B5-B11	B5-B11
3.17	B5-B11	B5-B11	B5-B11	B5-B11
3.69	B5-B11	B5-B11	B5-B11	B5-B11
4	B5-B11	B5-B11	B5-B11	B5-B11
4.77	B5-B11	B5-B11	B5-B11	B5-B11
5.25	B5-B11	B5-B11	B5-B11	B5-B11
5.82	B5-B11	B5-B11	B5-B11	B5-B11
7.33	B5-B11	B5-B11	B5-B11	B5-B11
8.38	B5-B11	B5-B11	B5-B11	B5-B11

CH - H - PH ...062


i	080	090	100	112	132
5.4	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
5.9	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
7.4	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
8.5	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
9.4	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
11.7	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
12.7	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
14.8	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
16.3	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
17.7	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
20.3	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
23.3	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
25.7	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
29.3	B5-B11	B5-B11	B5-B11	B5-B11	
32.0	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
37.0	B5-B11	B5-B11	B5-B11	B5-B11	
40.3	B5-B11	B5-B11	B5-B11	B5-B11	
46.1	B5-B11	B5-B11	B5-B11	B5-B11	

CH - H - PH ...063

i	071	080	090	100	112
49.5		B5-B11	B5-B11	B5-B11	B5-B11
54.6		B5-B11	B5-B11	B5-B11	B5-B11
68.0		B5-B11	B5-B11	B5-B11	B5-B11
85.8	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
94.8	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
118.0	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
135.4	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
149.5	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
170.7	B5-B11	B5-B11	B5-B11		
186.2	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
215.2	B5-B11	B5-B11	B5-B11		
234.7	B5-B11	B5-B11	B5-B11		
268.0	B5-B11	B5-B11	B5-B11		

CH - H - PH...081

i	080	090	100	112	132
1.3					B5-B11
1.43					B5-B11
1.93					B5-B11
2.54			B5-B11	B5-B11	B5-B11
3.25			B5-B11	B5-B11	B5-B11
3.72			B5-B11	B5-B11	B5-B11
4			B5-B11	B5-B11	B5-B11
4.67			B5-B11	B5-B11	B5-B11
5.54	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
6.08	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
7.5	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
8.44	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11



Predisposition 电机-减速机配合

CH - H - PH ...082

i	080	090	100	112	132	160
5.4					B5-B11	B5-B11
5.9					B5-B11	B5-B11
7.4					B5-B11	B5-B11
8.0					B5-B11	B5-B11
8.9					B5-B11	B5-B11
11.0					B5-B11	B5-B11
13.5			B5-B11	B5-B11	B5-B11	B5-B11
14.9			B5-B11	B5-B11	B5-B11	B5-B11
16.6			B5-B11	B5-B11	B5-B11	B5-B11
18.5			B5-B11	B5-B11	B5-B11	B5-B11
19.4			B5-B11	B5-B11	B5-B11	B5-B11
21.4			B5-B11	B5-B11	B5-B11	B5-B11
22.8			B5-B11	B5-B11	B5-B11	B5-B11
26.6			B5-B11	B5-B11	B5-B11	B5-B11
27.9	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11	
31.2	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11	
34.4	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11	
38.7	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11	
42.8	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11	
48.1	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11	

CH - H - PH ...083

i	080	090	100	112	132
56.5	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
71.5	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
78.9	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
85.6	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
98.1	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
112.8	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
124.4	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
142.2	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
154.8	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
162.3	B5-B11	B5-B11			
179.1	B5-B11	B5-B11			
195.1	B5-B11	B5-B11			
222.8	B5-B11	B5-B11			

CH - H - PH...101


i	100	112	132	160	180
1.29			B5-B11	B5-B11	B5-B11
1.41			B5-B11	B5-B11	B5-B11
2.03			B5-B11	B5-B11	B5-B11
2.48			B5-B11	B5-B11	B5-B11
3.27	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
3.7	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
4.22			B5-B11	B5-B11	B5-B11
4.88	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
5.27	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
6.23	B5-B11	B5-B11	B5-B11	B5-B11	
7.55	B5-B11	B5-B11	B5-B11	B5-B11	
8.4	B5-B11	B5-B11	B5-B11	B5-B11	

CH - H - PH ...102

i	100	112	132	160	180
5.3			B5-B11	B5-B11	B5-B11
6.4			B5-B11	B5-B11	B5-B11
7.1			B5-B11	B5-B11	B5-B11
8.3			B5-B11	B5-B11	B5-B11
10.0			B5-B11	B5-B11	B5-B11
11.1			B5-B11	B5-B11	B5-B11
13.3	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
16.1	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
17.9	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
19.8	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
21.4	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
24.0	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
25.9	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
28.7	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11
30.7	B5-B11	B5-B11	B5-B11	B5-B11	
34.2	B5-B11	B5-B11	B5-B11	B5-B11	
38.5	B5-B11	B5-B11	B5-B11		
41.3	B5-B11	B5-B11	B5-B11	B5-B11	
45.8	B5-B11	B5-B11	B5-B11	B5-B11	
51.5	B5-B11	B5-B11	B5-B11		

CH - H - PH ...103

i	090	100	112	132	160
55.5				B5-B11	B5-B11
69.7		B5-B11	B5-B11	B5-B11	B5-B11
79.8		B5-B11	B5-B11	B5-B11	B5-B11
84.2		B5-B11	B5-B11	B5-B11	B5-B11
93.4		B5-B11	B5-B11	B5-B11	B5-B11
100.1		B5-B11	B5-B11	B5-B11	B5-B11
120.8		B5-B11	B5-B11	B5-B11	B5-B11
134.1		B5-B11	B5-B11	B5-B11	B5-B11
143.4	B5-B11	B5-B11	B5-B11	B5-B11	
160.8	B5-B11	B5-B11	B5-B11	B5-B11	
181.1	B5-B11	B5-B11	B5-B11	B5-B11	
194.2	B5-B11	B5-B11	B5-B11	B5-B11	
215.5	B5-B11	B5-B11	B5-B11	B5-B11	
242.6	B5-B11	B5-B11	B5-B11	B5-B11	


Predisposition 电机-减速机配合
CH - H - PH...121

i	132	160	180	200
1.23		B5-B11	B5-B11	B5
1.42		B5-B11	B5-B11	B5
1.81		B5-B11	B5-B11	B5
2	B5-B11	B5-B11	B5-B11	B5
2.48	B5-B11	B5-B11	B5-B11	B5
2.95	B5-B11	B5-B11	B5-B11	B5
3.14	B5-B11	B5-B11	B5-B11	B5
3.58	B5-B11	B5-B11	B5-B11	B5
4.12	B5-B11	B5-B11	B5-B11	B5
4.8	B5-B11	B5-B11	B5-B11	B5
5.21	B5-B11	B5-B11	B5-B11	
6.25	B5-B11	B5-B11	B5-B11	
7.7	B5-B11	B5-B11	B5-B11	

CH - H - PH ...122

i	132	160	180	200
5.3		B5-B11	B5-B11	B5
5.8		B5-B11	B5-B11	B5
7.0		B5-B11	B5-B11	B5
7.7		B5-B11	B5-B11	B5
8.5		B5-B11	B5-B11	B5
10.3		B5-B11	B5-B11	B5
12.7	B5-B11	B5-B11	B5-B11	B5
13.9	B5-B11	B5-B11	B5-B11	B5
16.9	B5-B11	B5-B11	B5-B11	B5
19.3	B5-B11	B5-B11	B5-B11	B5
20.6	B5-B11	B5-B11	B5-B11	B5
22.5	B5-B11	B5-B11	B5-B11	B5
24.5	B5-B11	B5-B11	B5-B11	
27.5	B5-B11	B5-B11	B5-B11	B5
29.9	B5-B11	B5-B11	B5-B11	
33.0	B5-B11	B5-B11	B5-B11	
36.1	B5-B11	B5-B11	B5-B11	
44.1	B5-B11	B5-B11	B5-B11	

CH - H - PH ...123

i	100	112	132	160	180	200
45.8			B5-B11	B5-B11	B5-B11	B5
55.9			B5-B11	B5-B11	B5-B11	B5
67.3	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11	B5
73.7	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11	B5
83.3	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11	B5
90.0	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11	B5
100.3	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11	B5
108.3	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11	B5
118.6	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11	B5
128.2	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11	
144.8	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11	B5
155.2	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11	
172.8	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11	
189.2	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11	
207.4	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11	
230.9	B5-B11	B5-B11	B5-B11	B5-B11	B5-B11	
259.6	B5-B11	B5-B11	B5-B11			


H - PH ...142

i	160	180	200	225
5.3	B5	B5	B5	B5
6.4	B5	B5	B5	B5
7.0	B5	B5	B5	B5
7.8	B5	B5	B5	B5
9.5	B5	B5	B5	B5
10.5	B5	B5	B5	B5
13.1	B5	B5	B5	B5
15.8	B5	B5	B5	B5
17.5	B5	B5	B5	B5
20.0	B5	B5	B5	B5
24.2	B5	B5	B5	B5
26.8	B5	B5	B5	B5
32.2	B5	B5	B5	B5
38.9	B5	B5	B5	B5
43.1	B5	B5	B5	B5

























H - PH ...143


i	132	160	180	200
48.3		B5	B5	B5
53.5	B5	B5	B5	B5
59.2	B5	B5	B5	B5
63.0	B5	B5	B5	B5
71.4	B5	B5	B5	B5
79.1	B5	B5	B5	B5
86.4	B5	B5	B5	B5
96.2	B5	B5	B5	B5
104.5	B5	B5	B5	
115.9	B5	B5	B5	B5
128.5	B5	B5	B5	B5
139.6	B5	B5	B5	
154.3	B5	B5	B5	
186.0	B5	B5	B5	
206.1	B5	B5	B5	

B11 = Motor with special execution / B11 为特殊马达



Mounting positions 安装方向


	H... - HA.. 1	H... 1 M	H... - HA.. 2/3
B3			
B5			
B6			
B7			
B8			
V5			
V1			
V6			
V3			



Mounting positions 安装方向

Position of terminal box

电缆进线箱




- In the case of specific requirements, when ordering, specify the position of the terminal box as shown in the diagram.
- 如果客户有特殊要求时，请在下单时注明进线箱的位置。

- Unless otherwise specified, the gear reducer is supplied with terminal box in position 1.
- 除非特别声明，所有标准产品的接线箱都是在 1 位置。



- For vertical positions, check with pages 10-11.
- 如要垂直安装，请参考第十到十一页。


- Unless specified otherwise, the standard positions are B3/B5.
- 除非特别声明，标准的位置是 B3/B5



- For positions not envisaged, it is necessary to call our Technical Service.
- 如有特殊要求不在上述的图中，请与技术人员联系。




H Performance 性能参数



P1 (kW)	n2 (1/min)	M2 (Nm)	f.s.	i	型号		Fr2 (N)	
0.12	260.3	4	18.9	5.4	HA32	63A4	1096	82-83
	214.8	5	15.6	6.5			1169	
	172.6	6	11.8	8.1			1257	
	128.0	9	10.5	10.9			1389	
	105.7	10	7.7	13.3			1481	
	84.9	13	6.2	16.5			1593	
	69.1	16	5.7	20.3			1706	
	57.0	19	4.4	24.5			1818	
	45.8	24	3.3	30.5			1956	
	39.5	28	3.2	35.4			2000	
	31.7	35	2.6	44.1			2000	
	28.7	38	2.1	48.8			2000	
	23.1	48	2.0	60.7			2000	
20.4	54	1.7	44.1		HA32	63B6	2000	82-83
18.5	60	1.3	48.8				2000	
14.8	74	1.3	60.7				2000	
23.5	46	2.2	59.7		HA33	63A4	2000	84-85
19.4	56	1.8	72.3				2000	
15.6	69	1.4	89.9				2000	
12.7	85	1.2	110.5				2000	
10.5	103	1.0	133.9				2000	
8.4	128	0.8	166.6				2000	
177.8	6	4.0	7.9		HA41	63A4	1000	86-87
129.2	9	2.3	10.83				1000	
15.6	69	2.2	89.9		HA43	63A4	4300	90-91
12.7	85	1.8	110.5				4300	
10.5	103	1.5	133.9				4300	
8.4	128	1.2	166.6				4300	
7.2	149	1.0	193.3				4300	
5.8	185	0.8	240.5				4300	
7.0	154	1.9	200.3		HA53	63A4	6000	96-97
5.9	181	1.7	235.4				6000	
4.9	219	1.4	284.8				6000	
4.0	272	1.1	354.0				6000	
4.9	219	2.2	284.8		HA63	63A4	8000	102-103
4.0	272	1.8	354.0				8000	
13.0	83	2.4	108.0		H033	63A4	5500	106-107
11.3	95	2.10	123.7				5500	
9.8	110	1.81	143.3				5500	
7.8	137	1.46	178.6				5500	
7.1	152	1.32	197.2				5500	
5.7	189	1.06	245.7				5500	
8.5	127	2.4	165.4		H043	63A4	6600	110-111
6.8	158	1.90	205.1				6600	
6.2	175	1.71	227.5				6600	
5.0	217	1.38	282.1				6600	
0.18	260.3	6	12.6	5.4	HA32	63B4	1096	82-83
	214.8	8	10.4	6.5			1169	
	172.6	10	7.8	8.1			1257	
	128.0	13	7.0	10.9			1389	
	105.7	16	5.1	13.3			1481	
	84.9	19	4.1	16.5			1593	



Performance 性能参数
H



P1 (kW)	n2 (1/min)	M2 (Nm)	f.s.	i	型号		Fr2 (N)	
0.18	69.1	24	3.8	20.3	HA32	63B4	1706	82-83
	57.0	29	2.9	24.5			1818	
	45.8	36	2.2	30.5			1956	
	39.5	42	2.2	35.4			2000	
	31.7	52	1.7	44.1			2000	
	28.7	57	1.4	48.8			2000	
	23.1	72	1.3	60.7			2000	
	20.4	81	1.1	44.1	HA32	71A6	2000	82-83
	18.5	89	0.9	48.8			2000	
	14.8	111	0.9	60.7			2000	
	27.3	59	1.7	51.3	HA33	63B4	2000	84-85
	23.5	69	1.5	59.7			2000	
	19.4	83	1.2	72.3			2000	
	15.6	104	1.0	89.9			2000	
	12.7	128	0.8	110.5			2000	
	177.8	9	2.7	7.9	HA41	63B4	900	86-87
	129.2	13	1.6	10.83			1001	
	31.7	52	2.7	44.1	HA42	63B4	4300	88-89
	28.7	57	2.3	48.8			4300	
	23.1	72	2.0	60.7			4300	
	20.4	81	1.7	44.1	HA42	71A6	4300	88-89
	18.5	89	1.5	48.8			4300	
	14.8	111	1.3	60.7			4300	
	23.5	69	2.2	59.7	HA43	63B4	4300	90-91
	19.4	83	1.8	72.3			4300	
	15.6	104	1.4	89.9			4300	
	12.7	128	1.2	110.5			4300	
	10.5	155	1.0	133.9			4300	
	8.4	192	0.8	166.6			4300	
	10.1	160	1.9	138.7	HA53	63B4	6000	96-97
	8.6	188	1.6	163.1			6000	
	7.0	231	1.3	200.3			6000	
	5.9	272	1.1	235.4			6000	
	4.9	329	0.9	284.8			6000	
	7.0	231	2.1	200.3	HA63	63B4	8000	102-103
	5.9	272	1.8	235.4			8000	
	4.9	329	1.5	284.8			8000	
	4.0	409	1.2	354.0			8000	
	14.1	115	1.7	99.3	H033	63B4	5500	106-107
	13.0	125	1.60	108.0			5500	
	11.3	143	1.40	123.7			5500	
	9.8	165	1.21	143.3			5500	
	7.8	206	0.97	178.6			5500	
	7.1	228	0.88	197.2			5500	
	12.2	132	2.3	114.5	H043	63B4	6600	110-111
	11.1	145	2.07	125.7			6600	
	9.9	164	1.83	142.0			6600	
	8.5	191	1.57	165.4			6600	
	6.8	237	1.27	205.1			6600	
	6.2	263	1.14	227.5			6600	
	5.0	326	0.92	282.1			6600	




H Performance 性能参数



P1 (kW)	n2 (1/min)	M2 (Nm)	f.s.	i	型号		Fr2 (N)				
0.18	6.5	250	2.0	216.4	H053	63B4	8000	114-115			
	5.2	309	1.62	267.7			8000				
0.25	260.3	9	9.1	5.4	HA32	71A4	1096	82-83			
	214.8	11	7.5	6.5			1169				
	172.6	13	5.6	8.1			1257				
	128.0	18	5.0	10.9			1389				
	105.7	22	3.7	13.3			1481				
	84.9	27	3.0	16.5			1593				
	69.1	33	2.7	20.3			1706				
	57.0	40	2.1	24.5			1818				
	45.8	50	1.6	30.5			1956				
	39.5	58	1.6	35.4			2000				
	31.7	72	1.2	44.1			2000				
	28.7	80	1.0	48.8			2000				
	23.1	99	1.0	60.7			2000				
	29.5	78	1.0	30.5			HA32		71B6	2000	82-83
	25.4	90	1.0	35.4						2000	
20.4	112	0.8	44.1	2000							
27.3	82	1.2	51.3	HA33	71A4	2000	84-85				
23.5	96	1.0	59.7			2000					
19.4	116	0.9	72.3			2000					
966.7	2	12.5	1.45	HA41	71A4	512	86-87				
475.5	5	6.2	2.94			648					
294.7	8	3.8	4.75			760					
256.7	9	3.3	5.45			796					
177.8	13	1.9	7.88			900					
129.2	18	1.1	10.83	1001							
31.7	72	1.9	44.1	HA42	71A4	4300	88-89				
28.7	80	1.6	48.8			4300					
23.1	99	1.4	60.7			4300					
25.4	90	1.7	35.4	HA42	71B6	4300	88-89				
20.4	112	1.2	44.1			4300					
18.5	124	1.0	48.8			4300					
14.8	154	0.9	60.7			4300					
27.3	82	1.8	51.3	HA43	71A4	4300	90-91				
23.5	96	1.6	59.7			4300					
19.4	116	1.3	72.3			4300					
15.6	144	1.0	89.9			4300					
12.7	177	0.8	110.5			4300					
15.9	141	2.1	88.0	HA53	71A4	6000	96-97				
12.5	179	1.7	111.6			6000					
10.1	222	1.3	138.7			6000					
8.6	261	1.1	163.1			6000					
7.0	321	0.9	200.3			6000					
5.9	377	0.8	235.4			6000					
10.1	222	2.2	138.7	HA63	71A4	8000	102-103				
8.6	261	1.8	163.1			8000					
7.0	321	1.5	200.3			8000					
5.9	377	1.3	235.4			8000					
4.9	457	1.1	284.8			8000					
4.0	567	0.8	354.0			8000					



Performance 性能参数
H



P1 (kW)	n2 (1/min)	M2 (Nm)	f.s.	i	型号		Fr2 (N)	
0.25	26.1	86	2.3	53.6	H033	71A4	5500	106-107
	21.0	107	1.87	66.8			5500	
	18.7	120	1.67	74.8			5500	
	14.1	159	1.26	99.3			5500	
	13.0	173	1.15	108.0			5500	
	11.3	198	1.01	123.7			5500	
	18.3	123	2.4	76.7	H043	71A4	6600	110-111
	16.1	140	2.15	87.1			6600	
	12.2	184	1.63	114.5			6600	
	11.1	201	1.49	125.7			6600	
	9.9	228	1.32	142.0			6600	
	8.5	265	1.13	165.4			6600	
	6.8	329	0.91	205.1	6600			
	8.9	252	2.0	157.3	H053	71A4	8000	114-115
	7.2	312	1.60	194.6			8000	
	6.5	347	1.44	216.4			8000	
	5.2	429	1.17	267.7			8000	
	6.5	345	2.5	215.2	H063	71A4	12000	118-119
	6.0	376	2.26	234.7			12000	
	5.2	430	1.98	268.0			12000	
	0.37	260.3	13	6.1	5.4	HA32	71B4	1096
214.8		16	5.1	6.5	1169			
172.6		20	3.8	8.1	1257			
128.0		26	3.4	10.9	1389			
105.7		32	2.5	13.3	1481			
84.9		40	2.0	16.5	1593			
69.1		49	1.8	20.3	1706			
57.0		59	1.4	24.5	1818			
45.8		74	1.1	30.5	1956			
39.5		86	1.0	35.4	2000			
31.7		107	0.8	44.1	2000			
966.7		4	8.5	1.45	HA41			71B4
475.5		7	4.2	2.94		648		
294.7		12	2.6	4.75		760		
256.7		13	2.2	5.45		796		
177.8		19	1.3	7.88		900		
69.1		49	3.1	20.3	HA42	71B4	3591	88-89
57.0		59	2.6	24.5			3828	
45.8		74	1.9	30.5			4118	
39.5		86	1.7	35.4			4300	
31.7		107	1.3	44.1			4300	
28.7		118	1.1	48.8			4300	
23.1		147	1.0	60.7			4300	
27.3		122	1.2	51.3			HA43	
23.5		142	1.1	59.7	4300			
19.4		171	0.9	72.3	4300			
256.7		13	3.7	5.45	HA51	71B4	2194	92-93
177.8		19	2.1	7.88			2479	
129.2		27	0.9	10.83			2757	




H Performance 性能参数



P1 (kW)	n2 (1/min)	M2 (Nm)	f.s.	i	型号		Fr2 (N)	
0.37	30.1	113	2.7	29.9	HA52	80A6	5921	94-95
	24.9	136	2.2	36.2			6000	
	20.0	169	1.7	45.0			6000	
	18.1	188	1.6	49.8			6000	
	14.5	233	1.2	61.9			6000	
	23.2	143	2.1	60.2	HA53	71B4	6000	96-97
	18.7	178	1.7	74.9			6000	
	15.9	209	1.4	88.0			6000	
	12.5	265	1.1	111.6			6000	
	10.1	329	0.9	138.7			6000	
	8.6	387	0.8	163.1			6000	
	15.9	209	2.3	88.0	HA63	71B4	8000	102-103
	12.5	265	1.8	111.6			8000	
	10.1	329	1.5	138.7			8000	
	8.6	387	1.2	163.1			8000	
	7.0	475	1.0	200.3			8000	
	5.9	558	0.9	235.4			8000	
	36.9	92	2.2	37.9	H032	71B4	5500	106-107
	33.8	100	1.99	41.4			5500	
	29.6	114	1.75	47.3			5500	
	26.1	127	1.6	53.6	H033	71B4	5500	106-107
	21.0	158	1.26	66.8			5500	
	18.7	178	1.13	74.8			5500	
	14.1	236	0.85	99.3			5500	
	229.9	15	3.4	6.09	H041	71B4	1000	108-109
	182.6	19	2.66	7.67			1000	
	160.0	21	2.57	8.75			1000	
	29.5	115	2.4	47.5	H042	71B4	6600	110-111
	25.8	131	2.13	54.3			6600	
	22.6	147	2.0	61.8	H043	71B4	6600	110-111
	18.3	182	1.65	76.7			6600	
	16.1	207	1.45	87.1			6600	
	12.2	272	1.10	114.5			6600	
	11.1	298	1.01	125.7			6600	
	12.9	258	1.9	108.9	H053	71B4	8000	114-115
	10.4	320	1.56	134.8			8000	
	8.9	373	1.34	157.3			8000	
	7.2	462	1.08	194.6			8000	
	6.5	513	0.97	216.4			8000	
	8.2	405	2.1	170.7	H063	71B4	12000	118-119
	7.5	442	1.92	186.2			12000	
	6.5	511	1.66	215.2			12000	
	6.0	557	1.53	234.7			12000	
	5.2	636	1.34	268.0			12000	
0.55	260.3	19	4.1	5.4	HA32	80A4	1096	82-83
	214.8	23	3.4	6.5			1169	
	172.6	29	2.6	8.1			1257	
	128.0	39	2.3	10.9			1389	
	105.7	48	1.7	13.3			1481	



Performance 性能参数
H



P1 (kW)	n2 (1/min)	M2 (Nm)	f.s.	i	型号		Fr2 (N)	
0.55	84.9	59	1.3	16.5	HA32	80A4	1593	82-83
	69.1	73	1.2	20.3			1706	
	57.0	88	1.0	24.5			1818	
	167.3	30	2.7	5.4	HA32	80B6	1270	82-83
	138.1	37	2.2	6.5			1354	
	111.0	45	1.7	8.1			1457	
	82.3	61	1.5	10.9			1609	
	67.9	74	1.1	13.3			1716	
	54.6	92	0.9	16.5			1845	
	44.4	114	0.8	20.3			1976	
	966.7	5	4.7	1.45	HA41	80A4	512	86-87
	475.5	11	2.3	2.94			648	
	294.7	17	1.7	4.75			760	
	256.7	20	1.5	5.45			796	
	69.1	73	2.1	20.3	HA42	80A4	3591	88-89
	57.0	88	1.8	24.5			3828	
	45.8	110	1.3	30.5			4118	
	36.7	138	1.1	24.5	HA42	80B6	4300	88-89
	29.5	171	0.8	30.5			4300	
	475.5	11	3.7	2.94	HA51	80A4	1786	92-93
	294.7	17	2.9	4.75			2095	
	256.7	20	2.5	5.45			2194	
	38.7	130	2.3	36.2	HA52	80A4	5445	94-95
	31.1	162	1.7	45.0			5855	
	28.1	179	1.7	49.8			6000	
	22.6	223	1.3	61.9			6000	
	30.1	167	1.8	29.9	HA52	80B6	5921	94-95
	24.9	203	1.5	36.2			6000	
	20.0	252	1.1	45.0			6000	
	18.1	279	1.1	49.8			6000	
	14.5	347	0.8	61.9			6000	
	28.1	176	1.7	49.8	HA53	80A4	6000	96-97
	23.2	212	1.4	60.2			6000	
	18.7	264	1.1	74.9			6000	
	15.9	310	1.0	88.0			6000	
	12.5	394	0.8	111.6			6000	
	180.6	28	3.2	7.75	HA61	80A4	3691	98-99
	131.3	39	1.8	10.67			4106	
	20.0	252	1.7	45.0	HA62	80B6	8000	100-101
	18.1	279	1.3	49.8			8000	
	14.5	347	1.3	61.9			8000	
	18.7	264	1.8	74.9	HA63	80A4	8000	102-103
	15.9	310	1.5	88.0			8000	
	12.5	394	1.2	111.6			8000	
	10.1	489	1.0	138.7			8000	
	8.6	575	0.8	163.1			8000	




H Performance 性能参数



P1 (kW)	n2 (1/min)	M2 (Nm)	f.s.	i	型号		Fr2 (N)	
0.55	53.0	95	2.1	26.4	H032	80A4	5500	106-107
	47.1	107	1.87	29.7			5500	
	42.6	118	1.69	32.9			5500	
	36.9	137	1.46	37.9			5500	
	33.8	149	1.34	41.4			5500	
	29.6	170	1.18	47.3			5500	
	26.1	189	1.1	53.6	H033	80A4	5500	106-107
	21.0	236	0.85	66.8			5500	
	280.0	18	2.5	5.0	H041	80A4	990	108-109
	254.5	20	2.50	5.50			1000	
	229.9	22	2.26	6.09			1000	
	182.6	28	1.79	7.67			1000	
	160.0	32	1.73	8.75			1000	
	41.1	123	2.3	34.1	H042	80A4	6600	110-111
	37.1	136	2.06	37.8			6600	
	32.0	158	1.78	43.8			6600	
	29.5	171	1.64	47.5			6600	
	25.8	195	1.43	54.3			6600	
	22.6	218	1.4	61.8	H043	80A4	6600	110-111
	18.3	270	1.11	76.7			6600	
	16.1	307	0.98	87.1			6600	
	19.2	257	1.9	72.7	H053	80A4	8000	114-115
	15.5	319	1.57	90.5			8000	
	12.9	384	1.30	108.9			8000	
	10.4	475	1.05	134.8			8000	
	10.3	478	1.8	135.4	H063	80A4	12000	118-119
	9.4	527	1.61	149.5			12000	
	8.2	602	1.41	170.7			12000	
	7.5	657	1.29	186.2			12000	
	6.5	759	1.12	215.2			12000	
	6.0	828	1.03	234.7			12000	
	5.2	945	0.90	268.0			12000	
	6.3	786	2.3	222.8			H083	
0.75	260.3	26	3.0	5.4	HA32	80B4	1096	82-83
	214.8	32	2.5	6.5			1169	
	172.6	40	1.9	8.1			1257	
	128.0	54	1.7	10.9			1389	
	105.7	65	1.2	13.3			1481	
	84.9	81	1.0	16.5			1593	
	69.1	100	0.9	20.3			1706	
	966.7	7	3.5	1.45	HA41	80B4	512	86-87
	475.5	15	1.7	2.94			648	
	294.7	24	1.3	4.75			760	
	256.7	27	1.1	5.45			796	
	105.7	65	2.2	13.3	HA42	80B4	3117	88-89
	84.9	81	1.7	16.5			3353	
	69.1	100	1.5	20.3			3591	
	57.0	121	1.3	24.5			3828	
	45.8	150	0.9	30.5			4118	



Performance 性能参数
H



P1 (kW)	n2 (1/min)	M2 (Nm)	f.s.	i	型号		Fr2 (N)	
0.75	44.4	155	1.0	20.3	HA42	90S6	4161	88-89
	36.7	188	0.8	24.5			4300	
	475.5	15	2.7	2.94	HA51	80B4	1786	92-93
	294.7	24	2.1	4.75			2095	
	256.7	27	1.8	5.45			2194	
	46.8	147	2.0	29.9	HA52	80B4	5110	94-95
	38.7	178	1.7	36.2			5445	
	31.1	221	1.3	45.0			5855	
	28.1	244	1.2	49.8			6000	
	22.6	304	1.0	61.9			6000	
	53.2	129	2.3	16.9	HA52	90S6	4897	94-95
	44.0	156	1.9	20.5			5218	
	35.4	194	1.4	25.4			5610	
	30.1	228	1.3	29.9			5921	
	24.9	276	1.1	36.2			6000	
	20.0	343	0.8	45.0			6000	
	28.1	239	1.3	49.8	HA53	80B4	6000	96-97
	23.2	290	1.0	60.2			6000	
	18.7	360	0.8	74.9			6000	
	319.3	22	5.1	4.38	HA61	80B4	3053	98-99
	180.6	38	2.3	7.75			3691	
	131.3	53	1.3	10.67			4106	
	28.1	244	1.5	49.8	HA62	80B4	8000	100-101
	22.6	304	1.4	61.9			8000	
	30.1	228	2.0	29.9	HA62	90S6	8000	100-101
	24.9	276	1.7	36.2			8000	
	20.0	343	1.3	45.0			8000	
	18.1	380	1.0	49.8			8000	
	14.5	473	0.9	61.9			8000	
	28.1	239	2.0	49.8	HA63	80B4	8000	102-103
	23.2	290	1.7	60.2			8000	
	18.7	360	1.3	74.9			8000	
	15.9	423	1.1	88.0			8000	
	12.5	537	0.9	111.6			8000	
	70.4	98	2.0	19.9	H032	80B4	5440	106-107
	58.7	117	1.71	23.8			5500	
	53.0	130	1.54	26.4			5500	
	47.1	146	1.37	29.7			5500	
	42.6	162	1.24	32.9			5500	
	36.9	186	1.07	37.9			5500	
	33.8	203	0.98	41.4			5500	
	29.6	232	0.86	47.3			5500	
	333.3	21	2.2	4.20	H041	80B4	918	108-109
	280.0	25	1.81	5.00			960	
	254.5	27	1.83	5.50			983	
	229.9	30	1.65	6.09			1000	
	182.6	38	1.31	7.67			1000	
	160.0	43	1.27	8.75			1000	




H Performance 性能参数



P1 (kW)	n2 (1/min)	M2 (Nm)	f.s.	i	型号		Fr2 (N)	
0.75	46.0	150	1.9	30.5	H042	80B4	6600	110-111
	41.1	167	1.67	34.1			6600	
	37.1	185	1.51	37.8			6600	
	32.0	215	1.30	43.8			6600	
	29.5	233	1.20	47.5			6600	
	25.8	266	1.05	54.3	6600			
	22.6	297	1.0	61.8	H043	80B4	6600	110-111
	28.5	241	2.0	49.1	H052	80B4	8000	114-115
	24.9	276	1.78	56.1			8000	
	23.8	283	1.8	58.8	H053	80B4	8000	114-115
	19.2	350	1.43	72.7			8000	
	15.5	435	1.15	90.5			8000	
	12.9	524	0.95	108.9			8000	
	14.8	456	1.9	94.8	H063	80B4	12000	118-119
	11.9	567	1.50	118.0			12000	
10.3	651	1.31	135.4	12000				
9.4	719	1.18	149.5	12000				
8.2	821	1.04	170.7	12000				
7.5	895	0.95	186.2	12000				
7.8	861	2.1	179.1	H083	80B4	18000	122-123	
7.2	938	1.92	195.1			18000		
6.3	1071	1.68	222.8			18000		
0.92	260.3	32	2.5	5.4	HA32	80C4	1096	82-83
	214.8	39	2.0	6.5			1169	
	172.6	49	1.5	8.1			1257	
	128.0	66	1.4	10.9			1389	
	105.7	80	1.0	13.3			1481	
	966.7	9	2.8	1.45	HA41	80C4	512	86-87
	475.5	18	1.4	2.94			648	
	294.7	29	1.0	4.75			760	
	105.7	80	1.8	13.3	HA42	80C4	3117	88-89
	84.9	99	1.4	16.5			3353	
	69.1	122	1.2	20.3			3591	
	57.0	148	1.0	24.5			3828	
	475.5	18	2.2	2.94	HA51	80C4	1786	92-93
	294.7	29	1.7	4.75			2095	
	256.7	33	1.5	5.45			2194	
	46.8	180	1.7	29.9	HA52	80C4	5110	94-95
	38.7	218	1.4	36.2			5445	
	31.1	271	1.0	45.0			5855	
	28.1	300	1.0	49.8			6000	
	28.1	294	1.0	49.8	HA53	80C4	6000	96-97
	23.2	355	0.8	60.2			6000	
	319.3	27	4.1	4.38	HA61	80C4	3053	98-99
	180.6	47	1.9	7.75			3691	
	131.3	65	1.1	10.67			4106	



Performance 性能参数
H



P1 (kW)	n2 (1/min)	M2 (Nm)	f.s.	i	型号		Fr2 (N)				
0.92	38.7	218	2.2	36.2	HA62	80C4	8000	100-101			
	31.1	271	1.6	45.0			8000				
	28.1	300	1.2	49.8			8000				
	22.6	373	1.2	61.9			8000				
	28.1	294	1.6	49.8	HA63	80C4	8000	102-103			
	23.2	355	1.4	60.2			8000				
	18.7	442	1.1	74.9			8000				
	15.9	519	0.9	88.0			8000				
	119.0	71	2.0	11.8	H032	80C4	4691	106-107			
	102.0	83	2.06	13.7			4851				
	95.5	88	1.93	14.7			4918				
	76.9	110	1.55	18.2			5129				
	70.4	120	1.67	19.9			5209				
	61.7	137	1.46	22.7			5320				
	58.7	144	1.39	23.8			5359				
	53.0	159	1.26	26.4			5433				
	47.1	179	1.12	29.7			5500				
	42.6	198	1.01	32.9			5500				
	36.9	228	0.88	37.9			5500				
	973.9	9	2.9	1.44			H041		80C4	672	108-109
	700.0	12	2.05	2.00						738	
	550.0	15	1.94	2.55	788						
	515.8	17	1.82	2.71	802						
	450.8	19	2.12	3.11	831						
	390.2	22	2.06	3.59	862						
	333.3	26	1.76	4.20	896						
	280.0	30	1.48	5.00	934						
	254.5	33	1.49	5.50	954						
	229.9	37	1.35	6.09	975						
	182.6	47	1.07	7.67	1000						
	160.0	53	1.03	8.75	1000						
	66.7	127	2.0	21.0	H042	80C4		6600		110-111	
	60.5	139	1.86	23.1			6600				
	53.8	157	1.66	26.0			6600				
	50.9	166	1.69	27.5			6600				
	46.0	183	1.53	30.5			6600				
	41.1	205	1.36	34.1			6600				
	37.1	228	1.23	37.8			6600				
	32.0	264	1.06	43.8			6600				
	29.5	286	0.98	47.5			6600				
	190.9	45	2.2	7.33			H051	80C4	2500		112-113
	167.2	51	1.96	8.38	2500						
	30.9	273	1.8	45.4	H052	80C4	8000	114-115			
	28.5	296	1.66	49.1			8000				
	24.9	338	1.45	56.1			8000				
	23.8	347	1.4	58.8	H053	80C4	8000	114-115			
	19.2	429	1.17	72.7			8000				
	15.5	534	0.94	90.5			8000				
	16.3	506	1.7	85.8	H063	80C4	12000	118-119			
	14.8	559	1.52	94.8			12000				
	11.9	696	1.22	118.0			12000				
	10.3	799	1.06	135.4			12000				
	9.4	882	0.96	149.5			12000				




H Performance 性能参数



P1 (kW)	n2 (1/min)	M2 (Nm)	f.s.	i	型号		Fr2 (N)	
0.92	9.0	913	2.0	154.8	H083	80C4	18000	122-123
	8.6	958	1.88	162.3			18000	
	7.8	1057	1.70	179.1			18000	
	7.2	1151	1.56	195.1			18000	
	6.3	1314	1.37	222.8			18000	
1.1	260.3	39	3.6	5.4	HA42	90S4	2308	88-89
	214.8	47	3.0	6.5			2461	
	172.6	58	2.2	8.1			2647	
	128.0	79	1.9	10.9			2924	
	105.7	95	1.5	13.3			3117	
	84.9	119	1.2	16.5	3353			
	69.1	146	1.0	20.3	3591			
	57.0	177	0.9	24.5	3828			
	475.5	21	1.9	2.94	HA51	90S4	1786	92-93
	294.7	35	1.4	4.75			2095	
	256.7	40	1.3	5.45			2194	
	145.2	69	4.3	9.6	HA52	90S4	3505	94-95
	120.0	84	3.3	11.7			3735	
	96.6	104	2.7	14.5			4015	
	82.8	122	2.5	16.9			4227	
68.4	147	2.0	20.5	4504				
55.1	183	1.5	25.4	4842				
46.8	215	1.4	29.9	5110				
38.7	261	1.2	36.2	5445				
31.1	324	0.9	45.0	5855				
319.3	32	3.4	4.38	HA61	90S4	3053	98-99	
180.6	56	1.6	7.75			3691		
131.3	78	0.9	10.67			4106		
55.1	183	2.3	25.4	HA62	90S4	7147	100-101	
46.8	215	2.1	29.9			7543		
38.7	261	1.8	36.2			8000		
31.1	324	1.4	45.0			8000		
28.1	359	1.0	49.8			8000		
22.6	446	1.0	61.9			8000		
28.1	351	1.4	49.8	HA63	90S4	8000	102-103	
23.2	425	1.1	60.2			8000		
18.7	528	0.9	74.9			8000		
157.9	64	2.0	8.9	H032	90S4	4280	106-107	
138.0	73	1.92	10.1			4409		
119.0	85	1.71	11.8			4547		
102.0	99	1.72	13.7			4683		
95.5	106	1.61	14.7			4739		
83.5	121	1.57	16.8			4845		
76.9	131	1.30	18.2			4905		
70.4	143	1.40	19.9			4965		
61.7	163	1.22	22.7			5042		
58.7	172	1.16	23.8			5067		
53.0	190	1.05	26.4			5110		
47.1	214	0.93	29.7			5144		
42.6	237	0.84	32.9			5157		



Performance 性能参数
H



P1 (kW)	n2 (1/min)	M2 (Nm)	f.s.	i	型号		Fr2 (N)				
1.1	973.9	10	2.4	1.44	H041	90S4	664	108-109			
	700.0	15	1.72	2.00			727				
	550.0	19	1.62	2.55			774				
	515.8	20	1.52	2.71			787				
	450.8	23	1.77	3.11			814				
	390.2	26	1.72	3.59			842				
	333.3	31	1.47	4.20			873				
	280.0	36	1.24	5.00			906				
	254.5	40	1.25	5.50			923				
	229.9	44	1.13	6.09			941				
	182.6	56	0.90	7.67			979				
160.0	64	0.86	8.75	997							
	87.7	115	2.2	16.0	H042	90S4	6509	110-111			
	73.7	137	1.83	19.0			6600				
	66.7	151	1.65	21.0			6600				
	60.5	167	1.56	23.1			6600				
	53.8	188	1.39	26.0			6600				
	50.9	198	1.41	27.5			6600				
	46.0	219	1.28	30.5			6600				
	41.1	246	1.14	34.1			6600				
	37.1	272	1.03	37.8			6600				
	190.9	53	1.9	7.33			H051		90S4	2500	112-113
	167.2	61	1.64	8.38	2500						
	44.4	227	2.2	31.5	H052	90S4	8000	114-115			
	42.4	238	2.06	33.0			8000				
	35.9	281	1.74	39.0			8000				
	30.9	327	1.50	45.4			8000				
	28.5	354	1.38	49.1			8000				
	24.9	404	1.21	56.1			8000				
	23.8	415	1.2	58.8			H053		90S4	8000	114-115
	19.2	513	0.97	72.7	8000						
	20.6	480	1.8	68.0	H063	90S4	12000	118-119			
	16.3	605	1.40	85.8			12000				
	14.8	668	1.27	94.8			12000				
	11.9	832	1.02	118.0			12000				
	14.3	692	2.6	98.1	H083	90S4	18000	122-123			
	12.4	796	2.26	112.8			18000				
	11.3	878	2.05	124.4			18000				
	9.8	1003	1.80	142.2			18000				
	9.0	1092	1.65	154.8			18000				
	8.6	1145	1.57	162.3			18000				
	7.8	1263	1.42	179.1			18000				
	7.2	1376	1.31	195.1			18000				
	6.3	1571	1.15	222.8			18000				
1.5	260.3	53	2.6	5.4			HA42		90L4	2308	88-89
	214.8	64	2.2	6.5						2461	
	172.6	80	1.6	8.1	2647						
	128.0	107	1.4	10.9	2924						
	105.7	130	1.1	13.3	3117						
	84.9	162	0.9	16.5	3353						




H Performance 性能参数



P1 (kW)	n2 (1/min)	M2 (Nm)	f.s.	i	型号		Fr2 (N)	
1.5	966.7	14	2.8	1.45	HA51	90L4	1410	92-93
	475.5	29	1.4	2.94			1786	
	294.7	47	1.1	4.75			2095	
	256.7	54	0.9	5.45			2194	
	145.2	95	3.2	9.6	HA52	90L4	3505	94-95
	120.0	115	2.4	11.7			3735	
	96.6	142	2.0	14.5			4015	
	82.8	166	1.8	16.9			4227	
	68.4	201	1.4	20.5			4504	
	55.1	250	1.1	25.4			4842	
	46.8	294	1.0	29.9			5110	
	560.0	25	3.6	2.50	HA61	90L4	2531	98-99
	319.3	44	2.5	4.38			3053	
	180.6	77	1.2	7.75			3691	
	131.3	106	0.7	10.67			4106	
	55.1	250	1.7	25.4	HA62	90L4	7147	100-101
	46.8	294	1.5	29.9			7543	
	38.7	355	1.3	36.2			8000	
	31.1	442	1.0	45.0			8000	
	28.1	479	1.0	49.8	HA63	90L4	8000	102-103
	23.2	579	0.8	60.2			8000	
	298.1	46	2.1	4.7	H032	90L4	3529	106-107
	224.7	61	1.72	6.2			3764	
	180.4	76	1.64	7.8			3939	
	157.9	87	1.49	8.9			4039	
	138.0	100	1.41	10.1			4133	
	119.0	116	1.26	11.8			4226	
	102.0	135	1.26	13.7			4309	
	95.5	144	1.18	14.7			4339	
	83.5	165	1.15	16.8			4389	
	76.9	179	0.95	18.2			4410	
	70.4	195	1.02	19.9			4423	
	61.7	223	0.90	22.7			4424	
	58.7	234	0.85	23.8			4418	
	973.9	14	1.8	1.44	H041	90L4	646	108-109
	700.0	20	1.26	2.00			702	
	550.0	25	1.19	2.55			743	
	515.8	27	1.11	2.71			754	
	450.8	31	1.30	3.11			775	
	390.2	36	1.26	3.59			798	
	333.3	42	1.08	4.20			821	
	280.0	50	0.91	5.00			844	
	254.5	55	0.92	5.50			856	
	103.2	133	1.9	13.6	H042	90L4	5968	110-111
	87.7	157	1.59	16.0			6163	
	73.7	187	1.34	19.0			6357	
	66.7	206	1.21	21.0			6459	
	60.5	227	1.14	23.1			6551	
	53.8	256	1.02	26.0			6600	
	50.9	270	1.04	27.5			6600	
	46.0	299	0.94	30.5			6600	



Performance 性能参数
H



P1 (kW)	n2 (1/min)	M2 (Nm)	f.s.	i	型号		Fr2 (N)	
1.5	293.5	47	2.0	4.77	H051	90L4	2370	112-113
	266.7	52	1.92	5.25			2432	
	240.6	58	1.73	5.82			2500	
	190.9	73	1.37	7.33			2500	
	167.2	83	1.20	8.38			2500	
	56.7	243	1.9	24.7	H052	90L4	8000	114-115
	53.5	257	1.91	26.2			8000	
	49.2	279	1.75	28.4			8000	
	44.4	310	1.58	31.5			8000	
	42.4	324	1.51	33.0			8000	
	35.9	383	1.28	39.0			8000	
	30.9	446	1.10	45.4			8000	
	28.5	483	1.02	49.1			8000	
	24.9	551	0.9	56.1			8000	
	167.2	83	2.0	8.38			H061	
	37.8	363	2.2	37.0	H062	90L4	12000	118-119
	34.7	396	2.15	40.3			12000	
	30.4	452	1.88	46.1			12000	
	28.3	476	1.8	49.5	H063	90L4	12000	118-119
	25.6	525	1.62	54.6			12000	
	20.6	654	1.30	68.0			12000	
	16.3	825	1.03	85.8			12000	
	17.8	759	2.4	78.9	H083	90L4	18000	122-123
	14.3	943	1.91	98.1			18000	
	12.4	1085	1.66	112.8			18000	
	11.3	1197	1.50	124.4			18000	
	9.8	1367	1.32	142.2			18000	
	9.0	1489	1.21	154.8			18000	
	8.6	1561	1.15	162.3			18000	
	7.8	1723	1.04	179.1			18000	
	7.2	1876	0.96	195.1			18000	
	6.5	2072	1.7	215.5	H103	90L4	22000	126-127
	5.8	2333	1.54	242.6			22000	
1.84	260.3	65	2.2	5.4	HA42	90LL4	2308	88-89
	214.8	79	1.8	6.5			2461	
	172.6	98	1.3	8.1			2647	
	128.0	132	1.1	10.9			2924	
	105.7	160	0.9	13.3			3117	
	966.7	18	2.3	1.45	HA51	90LL4	1410	92-93
	475.5	36	1.1	2.94			1786	
	294.7	58	0.9	4.75			2095	
	181.0	93	2.6	7.7	HA52	90LL4	3256	94-95
	145.2	116	2.6	9.6			3505	
	120.0	141	2.0	11.7			3735	
	96.6	175	1.6	14.5			4015	
	82.8	204	1.5	16.9			4227	
	68.4	247	1.2	20.5			4504	
	55.1	306	0.9	25.4			4842	
	46.8	360	0.8	29.9			5110	




H Performance 性能参数



P1 (kW)	n2 (1/min)	M2 (Nm)	f.s.	i	型号		Fr2 (N)				
1.84	560.0	30	3.0	2.50	HA61	90LL4	2531	98-99			
	319.3	53	2.1	4.38			3053				
	180.6	94	1.0	7.75			3691				
	68.4	247	1.9	20.5	HA62	90LL4	6647	100-101			
	55.1	306	1.4	25.4			7147				
	46.8	360	1.2	29.9			7543				
	38.7	436	1.1	36.2			8000				
	31.1	542	0.8	45.0			8000				
	298.1	57	1.7	4.7	H032	90LL4	3420	106-107			
	224.7	75	1.40	6.2			3620				
	180.4	94	1.34	7.8			3759				
	157.9	107	1.22	8.9			3833				
	138.0	122	1.15	10.1			3898				
	119.0	142	1.02	11.8			3954				
	102.0	165	1.03	13.7			3991				
	95.5	177	0.96	14.7			4000				
	83.5	202	0.94	16.8			4000				
	76.9	219	0.78	18.2			3988				
	70.4	240	0.83	19.9			3963				
	194.8	87	1.8	7.2			H042		90LL4	5017	110-111
	157.1	107	1.96	8.9						5267	
	135.7	124	1.93	10.3	5431						
	118.6	142	1.76	11.8	5576						
	103.2	164	1.53	13.6	5718						
	87.7	192	1.30	16.0	5868						
	73.7	229	1.09	19.0	6006						
	66.7	253	0.99	21.0	6072						
	60.5	279	0.93	23.1	6124						
	53.8	314	0.83	26.0	6169						
	50.9	331	0.85	27.5	6182						
	442.1	39	2.1	3.17	H051	90LL4		2083		112-113	
	379.7	45	2.00	3.69				2171			
	350.0	49	1.85	4.00			2219				
	293.5	58	1.64	4.77			2324				
	266.7	64	1.56	5.25			2381				
	240.6	71	1.41	5.82			2443				
	190.9	89	1.12	7.33			2500				
	167.2	102	0.98	8.38			2500				
	70.1	241	1.9	20.0			H052	90LL4	8000		114-115
	64.6	261	1.80	21.7	8000						
	56.7	298	1.58	24.7	8000						
	53.5	315	1.55	26.2	8000						
	49.2	343	1.43	28.4	8000						
	44.4	380	1.29	31.5	8000						
	42.4	398	1.23	33.0	8000						
	35.9	470	1.04	39.0	8000						
	30.9	547	0.90	45.4	8000						
	190.9	89	1.9	7.33	H061	90LL4			3700	116-117	
	167.2	102	1.67	8.38			3700				
	47.7	353	2.3	29.3	H062	90LL4	12000	118-119			
	43.8	386	2.20	32.0			12000				
	37.8	446	1.79	37.0			12000				
	34.7	486	1.75	40.3			12000				
	30.4	555	1.53	46.1			12000				



Performance 性能参数
H



P1 (kW)	n2 (1/min)	M2 (Nm)	f.s.	i	型号		Fr2 (N)	
1.84	28.3	583	1.5	49.5	H063	90LL4	12000	118-119
	25.6	644	1.32	54.6			12000	
	20.6	802	1.06	68.0			12000	
	19.6	843	2.1	71.5	H083	90LL4	18000	122-123
	17.8	931	1.93	78.9			18000	
	16.4	1009	1.78	85.6			18000	
	14.3	1157	1.56	98.1			18000	
	12.4	1331	1.35	112.8			18000	
	11.3	1468	1.23	124.4			18000	
	9.8	1677	1.07	142.2			18000	
	9.0	1826	0.99	154.8			18000	
	8.6	1915	0.94	162.3	18000			
8.7	1897	1.8	160.8	H103	90LL4	22000	126-127	
7.7	2136	1.64	181.1			22000		
7.2	2291	1.53	194.2			22000		
6.5	2542	1.38	215.5			22000		
5.8	2862	1.26	242.6			22000		
2.2	272.2	74	3.2	5.1	HA52	100LA4	2842	94-95
	225.0	90	2.7	6.2			3029	
	181.0	111	2.2	7.7			3256	
	145.2	139	2.2	9.6			3505	
	120.0	168	1.7	11.7			3735	
	96.6	209	1.3	14.5			4015	
	82.8	244	1.2	16.9			4227	
	68.4	295	1.0	20.5			4504	
	1050.0	19	4.6	1.33	HA61	100LA4	2053	98-99
	560.0	36	2.5	2.50			2531	
	319.3	64	1.7	4.38			3053	
	96.6	209	2.0	14.5	HA62	100LA4	5926	100-101
82.8	244	2.1	16.9	6238				
68.4	295	1.6	20.5	6647				
55.1	366	1.2	25.4	7147				
298.1	68	1.4	4.7	H032	100LA4	3305	106-107	
224.7	90	1.17	6.2			3467		
180.4	112	1.12	7.8			3569		
157.9	128	1.02	8.9			3616		
256.3	79	2.0	5.5	H042	100LA4	4586	110-111	
194.8	104	1.55	7.2			4877		
157.1	128	1.64	8.9			5093		
135.7	149	1.62	10.3			5229		
118.6	170	1.47	11.8			5345		
103.2	196	1.28	13.6			5452		
87.7	230	1.09	16.0			5556		
73.7	274	0.91	19.0			5634		
1100.0	19	2.2	1.27	H051	100LA4	1585	112-113	
986.4	21	2.90	1.42			1637		
658.8	31	1.94	2.13			1838		
544.4	37	1.87	2.57			1938		
442.1	46	1.74	3.17			2050		




H Performance 性能参数



P1 (kW)	n2 (1/min)	M2 (Nm)	f.s.	i	型号		Fr2 (N)	
2.2	379.7	54	1.68	3.69	H051	100LA4	2133	112-113
	350.0	58	1.55	4.00			2178	
	293.5	69	1.37	4.77			2274	
	266.7	76	1.31	5.25			2327	
	240.6	85	1.18	5.82			2383	
98.3	205	2.1	14.2	H052	100LA4	7518	114-115	
84.4	239	1.88	16.6			7752		
77.8	259	1.77	18.0			7871		
70.1	288	1.60	20.0			8000		
64.6	312	1.51	21.7			8000		
56.7	356	1.32	24.7			8000		
53.5	377	1.30	26.2			8000		
49.2	410	1.20	28.4			8000		
44.4	454	1.08	31.5			8000		
293.5	69	2.3	4.77	H061	100LA4	3663	116-117	
266.7	76	2.22	5.25			3700		
240.6	85	2.01	5.82			3700		
190.9	107	1.59	7.33			3700		
167.2	122	1.39	8.38			3700		
47.7	423	1.9	29.3	H062	100LA4	12000	118-119	
43.8	461	1.84	32.0			12000		
37.8	533	1.50	37.0			12000		
34.7	581	1.46	40.3			12000		
30.4	664	1.28	46.1			12000		
						12000		
28.3	698	1.2	49.5	H063	100LA4	12000	118-119	
25.6	770	1.10	54.6			12000		
36.2	558	2.9	38.7	H082	100LA4	18000	122-123	
32.7	616	2.60	42.8			18000		
29.1	693	2.31	48.1			18000		
24.8	797	2.0	56.5	H083	100LA4	18000	122-123	
19.6	1008	1.79	71.5			18000		
17.8	1113	1.62	78.9			18000		
16.4	1207	1.49	85.6			18000		
14.3	1384	1.30	98.1			18000		
12.4	1591	1.13	112.8			18000		
11.3	1756	1.03	124.4			18000		
9.8	2005	0.90	142.2			18000		
						18000		
9.8	2023	1.7	143.4	H103	100LA4	22000	126-127	
8.7	2269	1.54	160.8			22000		
7.7	2554	1.37	181.1			22000		
7.2	2740	1.28	194.2			22000		
6.5	3039	1.15	215.5			22000		
5.8	3422	1.05	242.6			22000		
						22000		
9.0	2190	2.3	155.2	H123	100LA4	30000	130-131	
8.1	2438	2.05	172.8			30000		
7.4	2669	1.87	189.2			30000		
6.7	2926	1.71	207.4			30000		
6.1	3258	1.53	230.9			30000		
5.4	3663	1.37	259.6			30000		



Performance 性能参数
H



P1 (kW)	n2 (1/min)	M2 (Nm)	f.s.	i	型号		Fr2 (N)			
3	272.2	101	2.4	5.1	HA52	100LB4	2842	94-95		
	225.0	122	2.0	6.2			3029			
	181.0	152	1.6	7.7			3256			
	145.2	189	1.6	9.6			3505			
	120.0	229	1.2	11.7			3735			
	96.6	285	1.0	14.5			4015			
	82.8	332	0.9	16.9			4227			
1050.0	26	3.4	1.33	HA61	100LB4	2053	98-99			
560.0	50	1.8	2.50			2531				
319.3	87	1.3	4.38			3053				
120.0	229	1.9	11.7	HA62	100LB4	5512	100-101			
96.6	285	1.5	14.5			5926				
82.8	332	1.5	16.9			6238				
68.4	402	1.1	20.5			6647				
55.1	500	0.9	25.4			7147				
298.1	92	1.0	4.7	H032	100LB4	3050	106-107			
224.7	122	0.86	6.2			3128				
180.4	152	0.82	7.8			3146				
256.3	107	1.5	5.5	H042	100LB4	4349	110-111			
194.8	141	1.13	7.2			4564				
157.1	175	1.20	8.9			4705				
135.7	203	1.18	10.3			4781				
118.6	232	1.08	11.8			4832				
103.2	267	0.94	13.6			4863				
1100.0	25	1.6	1.27			H051		100LB4	1556	112-113
986.4	28	2.13	1.42	1604						
658.8	42	1.42	2.13	1789						
544.4	51	1.37	2.57	1879						
442.1	63	1.27	3.17	1977						
379.7	73	1.23	3.69	2048						
350.0	79	1.13	4.00	2086						
293.5	95	1.00	4.77	2165						
266.7	104	0.96	5.25	2206						
240.6	115	0.87	5.82	2249						
244.4	113	2.3	5.7	H052	100LB4		5829		114-115	
203.1	135	2.14	6.9				6091			
164.2	168	2.03	8.5				6386			
146.4	188	1.97	9.6			6539				
121.6	226	1.72	11.5			6775				
98.3	280	1.54	14.2			7019				
84.4	326	1.38	16.6			7171				
77.8	354	1.30	18.0			7241				
70.1	392	1.17	20.0			7317				
64.6	426	1.10	21.7			7365				
56.7	485	0.97	24.7			7419				
53.5	514	0.95	26.2			7431				
49.2	559	0.88	28.4			7435				
544.4	51	2.4	2.57			H061	100LB4	3019		116-117
442.1	63	2.07	3.17					3187		
379.7	73	2.05	3.69	3311						
350.0	79	1.89	4.00	3377						
293.5	95	1.69	4.77	3519						




H Performance 性能参数



P1 (kW)	n2 (1/min)	M2 (Nm)	f.s.	i	型号		Fr2 (N)				
3	266.7	104	1.63	5.25	H061	100LB4	3596	116-117			
	240.6	115	1.47	5.82			3676				
	190.9	146	1.17	7.33			3700				
	167.2	166	1.02	8.38			3700				
	69.0	398	2.1	20.3	H062	100LB4	12000	118-119			
	60.2	457	1.86	23.3			12000				
	54.5	505	1.68	25.7			12000				
	47.7	576	1.39	29.3			12000				
	43.8	629	1.35	32.0			12000				
	37.8	727	1.10	37.0			12000				
	34.7	792	1.07	40.3			12000				
	30.4	905	0.94	46.1			12000				
	165.8	168	2.1	8.44			H081		100LB4	4000	120-121
		40.7	675	2.4			34.4		H082	100LB4	18000
36.2		760	2.10	38.7	18000						
32.7		840	1.91	42.8	18000						
29.1		946	1.69	48.1	18000						
	24.8	1087	1.5	56.5	H083	100LB4	18000	122-123			
	19.6	1375	1.31	71.5			18000				
	17.8	1517	1.19	78.9			18000				
	11.6	2325	1.5	120.8	H103	100LB4	22000	126-127			
	10.4	2579	1.36	134.1			22000				
	9.8	2759	1.27	143.4			22000				
	8.7	3094	1.13	160.8			22000				
	7.7	3483	1.00	181.1			22000				
	7.2	3736	0.94	194.2			22000				
	11.8	2282	2.2	118.6	H123	100LB4	30000	130-131			
	10.9	2466	2.03	128.2			30000				
	9.7	2785	1.80	144.8			30000				
	9.0	2986	1.67	155.2			30000				
	8.1	3324	1.50	172.8			30000				
	7.4	3639	1.37	189.2			30000				
	6.7	3990	1.25	207.4			30000				
	6.1	4442	1.13	230.9			30000				
	5.4	4994	1.00	259.6			30000				
	4	272.2	135	1.8			5.1		HA52	112M4	2842
225.0		163	1.5	6.2	3029						
181.0		203	1.2	7.7	3256						
145.2		253	1.2	9.6	3505						
120.0		306	0.9	11.7	3735						
	1050.0	35	2.6	1.33	HA61	112M4	2053	98-99			
	560.0	66	1.4	2.50			2531				
	319.3	116	0.9	4.38			3053				
	181.0	203	1.9	7.7	HA62	112M4	4806	100-101			
	145.2	253	1.8	9.6			5173				
	120.0	306	1.4	11.7			5512				
	96.6	380	1.1	14.5			5926				
	82.8	443	1.1	16.9			6238				
	68.4	536	0.9	20.5			6647				



Performance 性能参数
H



P1 (kW)	n2 (1/min)	M2 (Nm)	f.s.	i	型号		Fr2 (N)			
4	256.3	143	1.1	5.5	H042	112M4	4052	110-111		
	194.8	188	0.85	7.2			4174			
	157.1	233	0.90	8.9			4221			
	135.7	270	0.89	10.3			4221			
1100.0	34	1.2	1.27	H051	112M4	1519	112-113			
986.4	38	1.60	1.42			1564				
658.8	56	1.07	2.13			1728				
544.4	68	1.03	2.57			1805				
244.4	150	1.7	5.7	H052	112M4	5579	114-115			
203.1	181	1.61	6.9			5790				
164.2	223	1.52	8.5			6013				
146.4	250	1.48	9.6			6121				
121.6	302	1.29	11.5			6272				
98.3	373	1.15	14.2			6397				
84.4	435	1.04	16.6			6445				
77.8	471	0.98	18.0			6453				
70.1	523	0.88	20.0			6444				
64.6	568	0.83	21.7			6418				
1041.9	36	2.2	1.34			H061		112M4	2469	116-117
658.8	56	2.13	2.13						2788	
544.4	68	1.76	2.57	2922						
442.1	84	1.55	3.17	3068						
379.7	98	1.54	3.69	3173						
350.0	106	1.42	4.00	3227						
293.5	126	1.27	4.77	3340						
266.7	139	1.22	5.25	3399						
240.6	154	1.10	5.82	3458						
190.9	194	0.88	7.33	3574						
110.5	332	2.1	12.7	H062	112M4		12000		118-119	
94.9	386	1.81	14.8				12000			
86.0	427	1.88	16.3			12000				
79.2	463	1.79	17.7			12000				
69.0	531	1.60	20.3			12000				
60.2	610	1.39	23.3			12000				
54.5	673	1.26	25.7			12000				
47.7	768	1.04	29.3			12000				
43.8	838	1.01	32.0			12000				
186.7	199	1.8	7.50			H081	112M4	4000		120-121
165.8	224	1.57	8.44	4000						
40.7	900	1.8	34.4	H082	112M4	18000	122-123			
36.2	1014	1.58	38.7			18000				
32.7	1120	1.43	42.8			18000				
29.1	1261	1.27	48.1			18000				
24.8	1450	1.1	56.5	H083	112M4	18000	122-123			
19.6	1833	0.98	71.5			18000				
40.9	896	3.6	34.2	H102	112M4	22000	126-127			
36.4	1007	2.78	38.5			22000				
33.9	1082	3.05	41.3			22000				
30.6	1200	2.75	45.8			22000				
27.2	1349	2.45	51.5			22000				




H Performance 性能参数



P1 (kW)	n2 (1/min)	M2 (Nm)	f.s.	i	型号		Fr2 (N)	
4	17.5	2047	1.7	79.8	H103	112M4	22000	126-127
	16.6	2159	1.62	84.2			22000	
	15.0	2395	1.46	93.4			22000	
	14.0	2567	1.36	100.1			22000	
	11.6	3099	1.13	120.8			22000	
	10.4	3438	1.02	134.1			22000	
	9.8	3678	0.95	143.4			22000	
	16.8	2137	2.3	83.3			H123	
15.6	2308	2.17	90.0	30000				
14.0	2572	1.94	100.3	30000				
12.9	2779	1.80	108.3	30000				
11.8	3042	1.64	118.6	30000				
10.9	3288	1.52	128.2	30000				
9.7	3714	1.35	144.8	30000				
9.0	3981	1.26	155.2	30000				
8.1	4432	1.13	172.8	30000				
7.4	4853	1.03	189.2	30000				
6.7	5320	0.94	207.4	30000				
4.8	272.2	162	1.5	5.1	HA52	112MS4	2842	94-95
	225.0	196	1.2	6.2			3029	
	181.0	243	1.0	7.7			3256	
	145.2	303	1.0	9.6			3505	
	120.0	367	0.8	11.7			3735	
	1050.0	42	2.1	1.33	HA61	112MS4	2053	98-99
	560.0	79	1.1	2.50			2531	
	319.3	139	0.8	4.38			3053	
	272.2	162	2.4	5.1	HA62	112MS4	4195	100-101
	225.0	196	1.9	6.2			4470	
	181.0	243	1.6	7.7			4806	
	145.2	303	1.5	9.6			5173	
120.0	367	1.2	11.7	5512				
96.6	456	0.9	14.5	5926				
256.3	172	0.9	5.5	H042	112MS4	3815	110-111	
244.4	180	1.4	5.7	H052	112MS4	5378	114-115	
203.1	217	1.34	6.9			5549		
164.2	268	1.27	8.5			5714		
146.4	301	1.23	9.6			5786		
121.6	362	1.08	11.5			5869		
98.3	448	0.96	14.2			5898		
1041.9	43	1.9	1.34			H061		112MS4
658.8	67	1.78	2.13	2724				
544.4	82	1.47	2.57	2845				
442.1	101	1.29	3.17	2973				
379.7	117	1.28	3.69	3062				
350.0	127	1.18	4.00	3107				
293.5	151	1.06	4.77	3197				
266.7	167	1.02	5.25	3241				
240.6	185	0.92	5.82	3283				
260.5	169	3.0	5.4	H062	112MS4	9750	118-119	
235.9	187	2.95	5.9			10005		
189.4	232	2.37	7.4			10571		
164.7	267	2.25	8.5			10931		
149.2	295	2.03	9.4			11184		



Performance 性能参数
H



P1 (kW)	n2 (1/min)	M2 (Nm)	f.s.	i	型号		Fr2 (N)	
4.8	119.8	367	1.77	11.7	H062	112MS4	11731	118-119
	110.5	398	1.76	12.7			11925	
	94.9	464	1.51	14.8			12000	
	86.0	512	1.56	16.3			12000	
	79.2	555	1.49	17.7			12000	
	69.0	638	1.33	20.3			12000	
	60.2	732	1.16	23.3			12000	
	54.5	808	1.05	25.7			12000	
	252.8	176	1.9	5.54	H081	112MS4	4000	120-121
	230.1	193	1.76	6.08			4000	
	186.7	238	1.47	7.50			4000	
	165.8	268	1.30	8.44			4000	
	52.6	836	1.9	26.6	H082	112MS4	18000	122-123
	50.2	876	1.83	27.9			18000	
	44.9	979	1.63	31.2			18000	
	40.7	1081	1.48	34.4			18000	
36.2	1217	1.32	38.7	18000				
32.7	1344	1.19	42.8	18000				
29.1	1513	1.06	48.1	18000				
24.8	1740	0.9	56.5	H083			112MS4	
40.9	1075	3.0	34.2	H102	112MS4	22000	126-127	
36.4	1209	2.32	38.5			22000		
33.9	1298	2.54	41.3			22000		
30.6	1440	2.29	45.8			22000		
27.2	1619	2.04	51.5			22000		
20.1	2145	1.6	69.7			H103		112MS4
17.5	2457	1.42	79.8	22000				
15.0	2874	1.22	93.4	22000				
14.0	3080	1.14	100.1	22000				
11.6	3719	0.94	120.8	22000				
10.4	4126	0.85	134.1	22000				
16.8	2565	1.9	83.3	H123	112MS4		30000	
15.6	2769	1.81	90.0			30000		
14.0	3087	1.62	100.3			30000		
12.9	3335	1.50	108.3			30000		
11.8	3651	1.37	118.6			30000		
10.9	3945	1.27	128.2			30000		
9.7	4456	1.12	144.8			30000		
9.0	4777	1.05	155.2			30000		
8.1	5318	0.94	172.8			30000		
7.4	5823	0.86	189.2			30000		
5.5	260.5	194	2.6			5.4	H062	132S4
	235.9	214	2.57	5.9	9846			
	189.4	266	2.07	7.4	10373			
	164.7	306	1.96	8.5	10704			
	149.2	338	1.77	9.4	10933			
	119.8	421	1.54	11.7	11419			
	110.5	456	1.53	12.7	11586			
	94.9	531	1.32	14.8	11883			
	86.0	587	1.36	16.3	12000			
	79.2	636	1.30	17.7	12000			
	69.0	730	1.16	20.3	12000			
	60.2	838	1.01	23.3	12000			
	54.5	926	0.92	25.7	12000			




H Performance 性能参数



P1 (kW)	n2 (1/min)	M2 (Nm)	f.s.	i	型号		Fr2 (N)	
5.5	1079.2	47	4.2	1.3	H081	132S4	2950	120-121
	980.0	52	4.23	1.43			3032	
	725.0	70	3.27	1.93			3297	
	550.8	92	3.03	2.54			3547	
	430.8	118	2.62	3.25			3774	
	376.1	135	2.29	3.72			3899	
	350.0	146	2.20	4.00			3965	
	300.0	170	1.88	4.67			4000	
	252.8	202	1.64	5.54			4000	
	230.1	221	1.54	6.08			4000	
	186.7	273	1.28	7.50			4000	
165.8	307	1.14	8.44	4000				
75.6	667	2.2	18.5	H082	132S4	16554	122-123	
72.2	698	2.29	19.4			16708		
65.5	770	2.08	21.4			17034		
61.4	821	1.95	22.8			17240		
52.6	958	1.67	26.6			17710		
50.2	1004	1.59	27.9			17844		
44.9	1122	1.43	31.2			18000		
40.7	1238	1.29	34.4			18000		
36.2	1394	1.15	38.7			18000		
32.7	1540	1.04	42.8			18000		
29.1	1734	0.92	48.1			18000		
166.7	306	2.1	8.4	H101	132S4	5000	124-125	
36.4	1385	2.0	38.5	H102	132S4	22000	126-127	
33.9	1488	2.22	41.3			22000		
30.6	1650	2.00	45.8			22000		
27.2	1855	1.78	51.5			22000		
20.1	2458	1.4	69.7	H103	132S4	22000	126-127	
17.5	2815	1.24	79.8			22000		
16.6	2968	1.18	84.2			22000		
15.0	3293	1.06	93.4			22000		
14.0	3529	0.99	100.1			22000		
16.8	2939	1.7	83.3	H123	132S4	30000	130-131	
15.6	3173	1.58	90.0			30000		
14.0	3537	1.41	100.3			30000		
12.9	3821	1.31	108.3			30000		
11.8	4183	1.20	118.6			30000		
10.9	4520	1.11	128.2			30000		
9.7	5106	0.98	144.8	30000				
13.4	3686	2.2	104.5	H143	132S4	55000	132-133	
12.1	4088	1.96	115.9			55000		
10.9	4531	1.77	128.5			55000		
10.0	4922	1.63	139.6			55000		
9.1	5443	1.47	154.3			55000		
7.5	6558	1.22	186.0			55000		
6.8	7268	1.10	206.1			55000		
260.5	264	1.9	5.4			H062		132L4
235.9	291	1.89	5.9	9393				
189.4	363	1.52	7.4	9809				
164.7	417	1.44	8.5	10055				
149.2	461	1.30	9.4	10217				



Performance 性能参数
H

P1 (kW)	n2 (1/min)	M2 (Nm)	f.s.	i	型号		Fr2 (N)			
7.5	119.8	574	1.13	11.7	H062	132L4	10527	118-119		
	110.5	622	1.13	12.7			10620			
	94.9	724	0.97	14.8			10758			
	86.0	800	1.00	16.3			10816			
1079.2	64	3.1	1.3	H081	132L4	2880	120-121			
980.0	71	3.10	1.43			2955				
725.0	96	2.40	1.93			3193				
550.8	126	2.22	2.54			3411				
430.8	161	1.92	3.25			3600				
376.1	185	1.68	3.72			3700				
350.0	199	1.61	4.00			3751				
300.0	232	1.38	4.67			3855				
252.8	275	1.20	5.54			3959				
230.1	302	1.13	6.08			4000				
186.7	372	0.94	7.50			4000				
165.8	419	0.84	8.44			4000				
189.3	363	2.2	7.4			H082		132L4	12819	122-123
174.5	394	2.03	8.0						13072	
158.2	435	2.07	8.9	13376						
127.2	541	2.03	11.0	14038						
103.7	663	2.11	13.5	14629						
94.0	732	2.05	14.9	14898						
84.3	816	1.84	16.6	15182						
75.6	910	1.65	18.5	15444						
72.2	952	1.68	19.4	15547						
65.5	1051	1.52	21.4	15753						
61.4	1120	1.43	22.8	15874						
52.6	1306	1.22	26.6	16116						
50.2	1369	1.17	27.9	16174						
44.9	1530	1.05	31.2	16276						
40.7	1688	0.95	34.4	16321						
224.7	309	2.1	6.23	H101	132L4	5000	124-125			
185.5	374	1.74	7.55			5000				
166.7	417	1.56	8.40			5000				
40.9	1680	1.9	34.2	H102	132L4	22000	126-127			
36.4	1889	1.48	38.5			22000				
33.9	2028	1.63	41.3			22000				
30.6	2250	1.47	45.8			22000				
27.2	2530	1.30	51.5			22000				
25.2	2668	1.3	55.5	H103	132L4	22000	126-127			
20.1	3351	1.04	69.7			22000				
17.5	3838	0.91	79.8			22000				
16.6	4047	0.86	84.2			22000				
20.8	3238	1.5	67.3	H123	132L4	30000	130-131			
19.0	3545	1.41	73.7			30000				
16.8	4008	1.25	83.3			30000				
15.6	4327	1.16	90.0			30000				
14.0	4823	1.04	100.3			30000				
12.9	5210	0.96	108.3			30000				
11.8	5705	0.88	118.6			30000				
16.2	4157	1.9	86.4			H143		132L4	55000	132-133
14.6	4627	1.73	96.2	55000						
13.4	5026	1.59	104.5	55000						
12.1	5575	1.44	115.9	55000						





H Performance 性能参数


P1 (kW)	n2 (1/min)	M2 (Nm)	f.s.	i	型号		Fr2 (N)				
7.5	10.9	6178	1.29	128.5	H143	132L4	55000	132-133			
	10.0	6711	1.19	139.6			55000				
	9.1	7422	1.08	154.3			55000				
	7.5	8943	0.89	186.0			55000				
9.2	260.5	324	1.5	5.4	H062	132M4	8848	118-119			
	235.9	358	1.54	5.9			9008				
	189.4	445	1.24	7.4			9330				
	164.7	512	1.17	8.5			9504				
	149.2	565	1.06	9.4			9608				
	119.8	704	0.92	11.7			9769				
	1079.2	79	2.5	1.30			H081		132M4	2821	120-121
	980.0	87	2.53	1.43						2890	
	725.0	118	1.96	1.93						3106	
	550.8	155	1.81	2.54						3295	
430.8	198	1.57	3.25	3452							
376.1	227	1.37	3.72	3531							
350.0	243	1.31	4.00	3569							
300.0	284	1.13	4.67	3643							
252.8	337	0.98	5.54	3707							
230.1	370	0.92	6.08	3732							
259.8	325	2.2	5.4	H082	132M4	11559	122-123				
235.5	358	1.95	5.9			11836					
189.3	446	1.80	7.4			12442					
174.5	483	1.66	8.0			12663					
158.2	533	1.69	8.9			12926					
127.2	663	1.66	11.0			13478					
103.7	813	1.72	13.5			13942					
94.0	897	1.67	14.9			14140					
84.3	1001	1.50	16.6			14336					
75.6	1116	1.34	18.5			14501					
72.2	1168	1.37	19.4			14560					
65.5	1289	1.24	21.4			14664					
61.4	1374	1.16	22.8			14713					
52.6	1603	1.00	26.6			14762					
50.2	1680	0.95	27.9			14755					
44.9	1877	0.85	31.2			14690					
287.2	297	2.1	4.88	H101	132M4	5000	124-125				
265.8	321	1.93	5.27			5000					
224.7	379	1.69	6.23			5000					
185.5	459	1.42	7.55			5000					
166.7	511	1.27	8.40			5000					
48.7	1731	1.9	28.7	H102	132M4	22000	126-127				
45.6	1851	1.73	30.7			22000					
40.9	2060	1.55	34.2			22000					
36.4	2317	1.21	38.5			22000					
33.9	2488	1.33	41.3			22000					
30.6	2760	1.20	45.8			22000					
27.2	3104	1.06	51.5			22000					
25.2	3272	1.1	55.5	H103	132M4	22000	126-127				
224.0	380	2.4	6.25	H121	132M4	6000	128-129				
181.8	469	2.13	7.70			6000					
31.7	2657	1.9	44.1	H122	132M4	30000	130-131				





Performance 性能参数


H



P1 (kW)	n2 (1/min)	M2 (Nm)	f.s.	i	型号		Fr2 (N)	
9.2	30.6	2700	1.9	45.8	H123	132M4	30000	130-131
	25.1	3296	1.52	55.9			30000	
	20.8	3972	1.26	67.3			30000	
	19.0	4348	1.15	73.7			30000	
	16.8	4916	1.02	83.3			30000	
	15.6	5307	0.94	90.0			30000	
	19.6	4209	1.9	71.4	H143	132M4	55000	132-133
	17.7	4665	1.71	79.1			55000	
	16.2	5099	1.57	86.4			55000	
	14.6	5675	1.41	96.2			55000	
	13.4	6165	1.30	104.5			55000	
	12.1	6838	1.17	115.9			55000	
	10.9	7578	1.06	128.5			55000	
	10.0	8232	0.97	139.6			55000	
9.1	9104	0.88	154.3	55000				
11	259.8	388	1.8	5.4	H082	160M4	11269	122-123
	235.5	428	1.63	5.9			11515	
	189.3	533	1.50	7.4			12043	
	174.5	578	1.38	8.0			12231	
	158.2	638	1.41	8.9			12449	
	127.2	793	1.39	11.0			12884	
	103.7	972	1.44	13.5			13214	
	94.0	1073	1.40	14.9			13337	
	84.3	1197	1.25	16.6			13440	
	75.6	1334	1.12	18.5			13502	
	72.2	1396	1.15	19.4			13515	
	65.5	1541	1.04	21.4			13511	
	378.4	269	2.2	3.70	H101	160M4	4784	124-125
	331.6	307	1.98	4.22			4931	
	287.2	355	1.75	4.88			5000	
	265.8	383	1.62	5.27			5000	
	224.7	454	1.41	6.23			5000	
	185.5	549	1.18	7.55			5000	
	166.7	611	1.06	8.40			5000	
	78.4	1286	2.5	17.9			H102	
	70.5	1430	2.24	19.8	21432			
	65.3	1545	2.07	21.4	21690			
	58.4	1727	1.91	24.0	22000			
	54.1	1865	1.77	25.9	22000			
	48.7	2069	1.59	28.7	22000			
	45.6	2213	1.45	30.7	22000			
	40.9	2464	1.30	34.2	22000			
	33.9	2975	1.11	41.3	22000			
	30.6	3300	1.00	45.8	22000			
	25.2	3913	0.9	55.5	H103	160M4	22000	126-127
	268.5	380	2.3	5.21	H121	160M4	6000	128-129
	224.0	455	1.98	6.25			6000	
	181.8	560	1.78	7.70			6000	
	42.4	2377	2.1	33.0	H122	160M4	30000	130-131
	38.7	2603	1.92	36.1			30000	
	31.7	3177	1.57	44.1			30000	




H Performance 性能参数



P1 (kW)	n2 (1/min)	M2 (Nm)	f.s.	i	型号		Fr2 (N)					
11	30.6	3229	1.5	45.8	H123	160M4	30000	130-131				
	25.1	3941	1.27	55.9			30000					
	20.8	4749	1.05	67.3			30000					
	19.0	5199	0.96	73.7			30000					
15	26.2	3775	2.1	53.5	H143	160M4	55000	132-133				
	23.6	4177	1.92	59.2			55000					
	22.2	4443	1.80	63.0			55000					
	19.6	5033	1.59	71.4			55000					
	17.7	5577	1.43	79.1			55000					
	16.2	6096	1.31	86.4			55000					
	14.6	6786	1.18	96.2			55000					
	13.4	7371	1.09	104.5			55000					
	12.1	8176	0.98	115.9			55000					
	10.9	9061	0.88	128.5			55000					
	15	259.8	529	1.3			5.4		H082	160L4	10623	122-123
		235.5	584	1.20			5.9				10803	
		189.3	726	1.10			7.4				11158	
174.5		788	1.02	8.0	11270							
158.2		869	1.04	8.9	11388							
127.2		1081	1.02	11.0	11566							
103.7		1326	1.06	13.5	11596							
94.0		1463	1.03	14.9	11552							
15		427.8	325	1.8	3.27	H101	160L4	4426			124-125	
		378.4	367	1.63	3.70			4535				
	331.6	419	1.46	4.22	4646							
	287.2	484	1.28	4.88	4759							
	265.8	523	1.19	5.27	4814							
	224.7	618	1.03	6.23	4921							
	185.5	749	0.87	7.55	5000							
15	266.0	517	3.5	5.3	H102	160L4	15368	126-127				
	220.3	624	3.20	6.4			16074					
	198.6	693	3.32	7.1			16458					
	169.2	813	3.08	8.3			17037					
	140.1	981	2.85	10.0			17689					
	126.3	1089	2.76	11.1			18029					
	105.1	1309	2.37	13.3			18582					
	87.0	1581	2.02	16.1			19064					
	78.4	1754	1.82	17.9			19282					
	70.5	1950	1.64	19.8			19461					
	65.3	2106	1.52	21.4			19561					
	58.4	2354	1.40	24.0			19652					
	54.1	2544	1.30	25.9			19673					
	48.7	2822	1.17	28.7			19639					
	45.6	3018	1.06	30.7			19576					
40.9	3359	0.95	34.2	19398								
15	340.0	409	2.1	4.12	H121	160L4	6000	128-129				
	291.7	476	1.83	4.80			6000					
	268.5	518	1.70	5.21			6000					
	224.0	620	1.45	6.25			6000					
	181.8	764	1.31	7.70			6000					
15	62.2	2212	2.3	22.5	H122	160L4	30000	130-131				
	57.2	2403	2.08	24.5			30000					
	50.9	2700	1.85	27.5			30000					
	46.9	2933	1.70	29.9			30000					



Performance 性能参数
H

P1 (kW)	n2 (1/min)	M2 (Nm)	f.s.	i	型号		Fr2 (N)				
15	42.4	3242	1.54	33.0	H122	160L4	30000	130-131			
	38.7	3549	1.41	36.1			30000				
	31.7	4332	1.15	44.1			30000				
	30.6	4403	1.1	45.8	H123	160L4	30000	130-131			
	25.1	5374	0.93	55.9			30000				
	32.5	4229	1.9	43.1	H142	160L4	53576	132-133			
	29.0	4650	1.7	48.3	H143	160L4	54900	132-133			
	26.2	5148	1.55	53.5			55000				
	23.6	5696	1.40	59.2			55000				
	22.2	6059	1.32	63.0			55000				
	19.6	6863	1.17	71.4			55000				
	17.7	7606	1.05	79.1			55000				
16.2	8313	0.96	86.4	55000							
14.6	9253	0.86	96.2	55000							
18.5	1083.0	158	2.5	1.29	H101	180M4	3463	124-125			
	992.7	173	2.61	1.41			3539				
	688.9	249	1.81	2.03			3855				
	564.2	304	1.81	2.48			4021				
	427.8	401	1.50	3.27			4233				
	378.4	453	1.32	3.70			4316				
	331.6	517	1.18	4.22			4397				
	287.2	597	1.04	4.88			4471				
	265.8	645	0.96	5.27			4504				
	266.0	638	2.8	5.3			H102		180M4	14911	126-127
	220.3	770	2.60	6.4						15522	
	198.6	854	2.69	7.1						15845	
	169.2	1002	2.49	8.3	16318						
	140.1	1211	2.31	10.0	16821						
	126.3	1343	2.23	11.1	17065						
	105.1	1614	1.92	13.3	17424						
	87.0	1949	1.64	16.1	17666						
	78.4	2163	1.48	17.9	17730						
	70.5	2405	1.33	19.8	17737						
	65.3	2598	1.23	21.4	17698						
	58.4	2904	1.14	24.0	17569						
	54.1	3137	1.05	25.9	17423						
	48.7	3480	0.95	28.7	17143						
	445.5	385	2.1	3.14	H121	180M4		5756		128-129	
	391.2	438	1.94	3.58				5925			
	340.0	504	1.69	4.12				6000			
	291.7	588	1.48	4.80				6000			
	268.5	638	1.38	5.21			6000				
	224.0	765	1.18	6.25			6000				
	181.8	943	1.06	7.70			6000				
	265.4	639	4.7	5.3			H122	180M4	22825		130-131
	242.4	700	4.57	5.8	23385						
	198.6	854	4.22	7.0	24631						
	180.8	938	3.94	7.7	25221						
	165.2	1027	3.70	8.5	25792						
	135.3	1253	3.19	10.3	27041						
110.6	1534	2.87	12.7	28280							
101.0	1680	2.74	13.9	28820							
82.7	2050	2.34	16.9	29954							
72.5	2341	2.14	19.3	30000							





H Performance 性能参数


P1 (kW)	n2 (1/min)	M2 (Nm)	f.s.	i	型号		Fr2 (N)			
18.5	68.1	2492	2.01	20.6	H122	180M4	30000	130-131		
	62.2	2729	1.83	22.5			30000			
	57.2	2964	1.69	24.5			30000			
	50.9	3330	1.50	27.5			30000			
	46.9	3618	1.38	29.9			30000			
	42.4	3998	1.25	33.0			30000			
	38.7	4377	1.14	36.1			30000			
31.7	5343	0.94	44.1	30000						
30.6	5430	0.9	45.8	H123	180M4	30000	130-131			
43.4	3906	2.0	32.2	H142	180M4	48515	132-133			
36.0	4707	1.70	38.9			49940				
32.5	5216	1.53	43.1			50624				
29.0	5735	1.4	48.3	H143	180M4	51654	132-133			
26.2	6350	1.26	53.5			52166				
23.6	7025	1.14	59.2			52559				
22.2	7472	1.07	63.0			52735				
19.6	8464	0.95	71.4			52921				
17.7	9380	0.85	79.1			52879				
22	1083.0	188	2.1			1.29		H101	180L4	3387
	992.7	205	2.19	1.41	3456					
	688.9	296	1.52	2.03	3735					
	564.2	361	1.52	2.48	3874					
	427.8	476	1.26	3.27	4039					
	266.0	758	2.4	5.3	H102	180L4	14453	126-127		
	220.3	916	2.18	6.4			14970			
	198.6	1016	2.26	7.1			15233			
	169.2	1192	2.10	8.3			15599			
	140.1	1440	1.95	10.0			15953			
126.3	1597	1.88	11.1	16102						
105.1	1920	1.61	13.3	16266						
87.0	2318	1.38	16.1	16267						
78.4	2572	1.24	17.9	16179						
70.5	2860	1.12	19.8	16012						
65.3	3089	1.04	21.4	15835						
58.4	3453	0.96	24.0	15486						
54.1	3731	0.88	25.9	15173						
775.0	263	2.7	1.81	H121	180L4	4926	128-129			
700.0	291	2.58	2.00			5051				
564.5	361	2.22	2.48			5311				
473.8	430	1.86	2.95			5519				
445.5	458	1.79	3.14			5590				
391.2	521	1.63	3.58			5736				
340.0	599	1.42	4.12			5884				
291.7	699	1.25	4.80			6000				
268.5	759	1.16	5.21			6000				
224.0	910	0.99	6.25			6000				
181.8	1121	0.89	7.70			6000				
265.4	760	3.9	5.3			H122		180L4	22436	130-131
242.4	832	3.85	5.8						22959	
198.6	1016	3.54	7.0						24111	
180.8	1115	3.32	7.7	24650						
165.2	1221	3.11	8.5	25166						
135.3	1491	2.68	10.3	26277						
110.6	1824	2.41	12.7	27345						





Performance 性能参数


H

P1 (kW)	n2 (1/min)	M2 (Nm)	f.s.	i	型号		Fr2 (N)					
22	101.0	1997	2.30	13.9	H122	180L4	27796	130-131				
	82.7	2438	1.97	16.9			28704					
	72.5	2784	1.80	19.3			29226					
	68.1	2964	1.69	20.6			29445					
	62.2	3245	1.54	22.5			29723					
	57.2	3525	1.42	24.5			29933					
	50.9	3961	1.26	27.5			30000					
	46.9	4302	1.16	29.9			30000					
	42.4	4754	1.05	33.0			30000					
	38.7	5205	0.96	36.1			30000					
	<hr/>											
	58.0	3479	2.3	24.2			H142		180L4	44316	132-133	
	52.3	3856	2.07	26.8						45077		
	43.4	4645	1.72	32.2						46304		
36.0	5597	1.43	38.9	47276								
32.5	6203	1.29	43.1	47672								
<hr/>												
29.0	6820	1.2	48.3	H143	180L4	48408	132-133					
26.2	7551	1.06	53.5			48572						
23.6	8354	0.96	59.2			48583						
22.2	8886	0.90	63.0			48506						
<hr/>												
30	1137.5	244	2.7	1.23	H121	200L4	4311	128-129				
	988.2	281	2.49	1.42			4458					
	775.0	359	1.95	1.81			4708					
	700.0	397	1.89	2.00			4809					
	564.5	492	1.63	2.48			5012					
	473.8	586	1.36	2.95			5161					
	445.5	624	1.31	3.14			5210					
	391.2	710	1.20	3.58			5303					
	340.0	817	1.04	4.12			5387					
	291.7	953	0.91	4.80			5454					
	268.5	1035	0.85	5.21			5477					
	<hr/>											
	265.4	1036	2.9	5.3			H122		200L4	21545	130-131	
	242.4	1135	2.82	5.8						21984		
198.6	1385	2.60	7.0	22921								
180.8	1521	2.43	7.7	23343								
165.2	1665	2.28	8.5	23736								
135.3	2033	1.97	10.3	24532								
110.6	2488	1.77	12.7	25208								
101.0	2724	1.69	13.9	25457								
82.7	3324	1.44	16.9	25849								
72.5	3796	1.32	19.3	25966								
68.1	4041	1.24	20.6	25973								
62.2	4425	1.13	22.5	25922								
50.9	5401	0.93	27.5	25510								
<hr/>												
80.2	3429	2.3	17.5	H142	200L4	38906	132-133					
69.9	3938	2.03	20.0			39680						
58.0	4744	1.69	24.2			40531						
52.3	5258	1.52	26.8			40882						
43.4	6334	1.26	32.2			41250						
36.0	7632	1.05	38.9			41187						
32.5	8458	0.95	43.1			40924						
<hr/>												
29.0	9300	0.9	48.3			H143		200L4	40988	132-133		




H Performance 性能参数


P1 (kW)	n2 (1/min)	M2 (Nm)	f.s.	i	型号		Fr2 (N)	
37	265.4	1278	3.6	5.3	H142	225S4	29300	132-133
	220.3	1540	3.18	6.4			30618	
	198.8	1707	2.93	7.0			31335	
	178.5	1900	2.79	7.8			32072	
	148.1	2290	2.84	9.5			33302	
	133.7	2538	2.84	10.5			33946	
	107.1	3167	2.30	13.1			35214	
	88.9	3816	2.04	15.8			36108	
	80.2	4229	1.87	17.5			36512	
	69.9	4856	1.65	20.0			36931	
	58.0	5851	1.37	24.2			37219	
	52.3	6485	1.23	26.8			37212	
	43.4	7812	1.02	32.2			36829	
	36.0	9413	0.85	38.9			35859	
45	265.4	1554	3.0	5.3	H142	225M4	28474	132-133
	220.3	1873	2.62	6.4			29622	
	198.8	2075	2.41	7.0			30231	
	178.5	2311	2.29	7.8			30843	
	148.1	2785	2.33	9.5			31821	
	133.7	3086	2.33	10.5			32305	
	107.1	3852	1.90	13.1			33166	
	88.9	4641	1.68	15.8			33640	
	80.2	5144	1.54	17.5			33776	
	69.9	5906	1.35	20.0			33790	
	58.0	7117	1.12	24.2			33434	
	52.3	7887	1.01	26.8			33017	




IH (n1=1400) Performance 性能参数

M2 (Nm)	i	P1 (kW)	n2 (1/min)	型号	Fr1 (N)	Fr2 (N)	
25	1.45	2.6	966.7	IHA41	330	512	104-105
25	2.94	1.3	475.5		330	648	
30	4.75	1.0	294.7		330	760	
30	5.45	0.8	256.7		330	796	
25	7.88	0.5	177.8		330	900	
20	10.83	0.3	129.2		330	1001	
40	1.45	4.2	966.7	IHA51	330	1410	104-105
40	2.94	2.1	475.5		330	1786	
50	4.75	1.6	294.7		330	2095	
50	5.45	1.4	256.7		330	2194	
40	7.88	0.8	177.8		330	2479	
25	10.83	0.3	129.2		330	2757	
90	1.33	10.2	1050.0	IHA61	550	2053	104-105
90	2.50	5.4	560.0		550	2531	
110	4.38	3.8	319.3		550	3053	
90	7.75	1.8	180.6		550	3691	
70	10.67	1.0	131.3		550	4106	
25	1.44	2.6	973.9	IH041	996	596	108-109
25	2.00	1.9	700.0		1101	678	
30	2.55	1.8	550.0		1116	721	
30	2.71	1.7	515.8		1132	739	
40	3.11	1.9	450.8		1093	733	
45	3.59	1.9	390.2		1100	754	
45	4.20	1.6	333.3		1139	806	
45	5.00	1.4	280.0		1176	866	
50	5.50	1.4	254.5		1174	877	
50	6.09	1.2	229.9		1193	915	
50	7.67	1.0	182.6		1230	1000	
55	8.75	0.9	160.0		1235	1000	
40	1.27	4.7	1100.0	IH051	825	1492	112-113
60	1.42	6.4	986.4		630	1466	
60	2.13	4.3	658.8		883	1712	
70	2.57	4.1	544.4		901	1797	
80	3.17	3.8	442.1		937	1903	
90	3.69	3.7	379.7		952	1975	
90	4.00	3.4	350.0		987	2040	
95	4.77	3.0	293.5		1033	2163	
100	5.25	2.9	266.7		1049	2225	
100	5.82	2.6	240.6		1083	2316	
100	7.33	2.1	190.9		1147	2500	
100	8.38	1.8	167.2		1178	2500	
80	1.34	9.0	1041.9	IH061	2094	2217	116-117
120	2.13	8.5	658.8		2140	2426	
120	2.57	7.1	544.4		2285	2628	
130	3.17	6.2	442.1		2368	2806	
150	3.69	6.1	379.7		2374	2875	
150	4.00	5.7	350.0		2421	2977	
160	4.77	5.1	293.5		2479	3149	
170	5.25	4.9	266.7		2496	3223	
170	5.82	4.4	240.6		2543	3367	
170	7.33	3.5	190.9		2632	3700	
170	8.38	3.1	167.2		2675	3700	
200	1.30	23.3	1079.2	IH081	922	2332	120-121
220	1.43	23.3	980.0		925	2352	



Performance 性能参数 (n1=1400)
IH

M2 (Nm)	i	P1 (kW)	n2 (1/min)	型号	Fr1 (N)	Fr2 (N)			
230	1.93	18.0	725.0	IH081	1404	2651	120-121		
280	2.54	16.6	550.8						
310	3.25	14.4	430.8						
310	3.72	12.6	376.1						
320	4.00	12.1	350.0						
320	4.67	10.4	300.0						
330	5.54	9.0	252.8						
340	6.08	8.4	230.1						
350	7.50	7.1	186.7						
350	8.44	6.3	165.8						
400	1.29	46.8	1083.0		IH101	1816		2847	124-125
450	1.41	48.2	992.7						
450	2.03	33.5	688.9						
550	2.48	33.5	564.2						
600	3.27	27.7	427.8						
600	3.70	24.5	378.4						
610	4.22	21.8	331.6						
620	4.88	19.2	287.2						
620	5.27	17.8	265.8						
640	6.23	15.5	224.7						
650	7.55	13.0	185.5						
650	8.40	11.7	166.7						
650	1.23	79.8	1137.5	IH121		869	3385	128-129	
700	1.42	74.7	988.2						
700	1.81	58.6	775.0						
750	2.00	56.7	700.0						
800	2.48	48.8	564.5						
800	2.95	40.9	473.8						
820	3.14	39.4	445.5						
850	3.58	35.9	391.2						
850	4.12	31.2	340.0						
870	4.80	27.4	291.7						
880	5.21	25.5	268.5						
900	6.25	21.8	224.0						
1000	7.70	19.6	181.8						
80	5.4	2.3	260.3	IHA32	330	1096	104-105		
80	6.5	1.9	214.8						
75	8.1	1.4	172.6						
90	10.9	1.3	128.0						
80	13.3	0.9	105.7						
80	16.5	0.7	84.9						
90	20.3	0.7	69.1						
85	24.5	0.5	57.0						
80	30.5	0.4	45.8						
90	35.4	0.4	39.5						
90	44.1	0.3	31.7						
80	48.8	0.3	28.7						
95	60.7	0.2	23.1						
100	51.3	0.3	27.3	IHA33	472	2000	104-105		
100	59.7	0.3	23.5						
100	72.3	0.2	19.4						
100	89.9	0.2	15.6						
100	110.5	0.14	12.7						
100	133.9	0.12	10.5						
100	166.6	0.09	8.4						
100	193.3	0.08	7.2						




IH (n1=1400) Performance 性能参数


M2 (Nm)	i	P1 (kW)	n2 (1/min)	型号	Fr1 (N)	Fr2 (N)	
100	240.5	0.06	5.8	IHA33	472	2000	104-105
100	279.1	0.06	5.0		472	2000	
100	347.3	0.04	4.0		472	2000	
140	5.4	4.0	260.3	IHA42	330	2308	104-105
140	6.5	3.3	214.8		409	2461	
130	8.1	2.4	172.6		369	2647	
150	10.9	2.1	128.0		424	2924	
140	13.3	1.6	105.7		381	3117	
140	16.5	1.3	84.9		398	3353	
150	20.3	1.1	69.1		432	3591	
155	24.5	1.0	57.0		422	3828	
140	30.5	0.7	45.8		359	4118	
150	35.4	0.6	39.5		457	4300	
140	44.1	0.5	31.7		371	4300	
130	48.8	0.41	28.7		416	4300	
140	60.7	0.35	23.1		428	4300	
150	51.3	0.5	27.3	IHA43	427	4300	104-105
150	59.7	0.4	23.5		426	4300	
150	72.3	0.3	19.4		409	4300	
150	89.9	0.3	15.6		398	4300	
150	110.5	0.2	12.7		403	4300	
150	133.9	0.2	10.5		409	4300	
150	166.6	0.14	8.4		398	4300	
150	193.3	0.12	7.2		427	4300	
150	240.5	0.10	5.8		398	4300	
150	279.1	0.08	5.0		427	4300	
150	347.3	0.07	4.0		398	4300	
240	5.1	7.1	272.2	IHA52	550	2842	104-105
240	6.2	5.9	225.0		682	3029	
240	7.7	4.7	181.0		664	3256	
300	9.6	4.8	145.2		827	3505	
280	11.7	3.7	120.0		636	3735	
280	14.5	2.9	96.6		664	4015	
300	16.9	2.7	82.8		758	4227	
290	20.5	2.2	68.4		659	4504	
280	25.4	1.7	55.1		641	4842	
300	29.9	1.5	46.8		752	5110	
300	36.2	1.3	38.7		682	5445	
280	45.0	1.0	31.1		620	5855	
300	49.8	0.9	28.1		798	6000	
290	61.9	0.7	22.6		642	6000	
300	49.8	0.9	28.1	IHA53	330	6000	104-105
300	60.2	0.8	23.2		409	6000	
300	74.9	0.6	18.7		398	6000	
300	88.0	0.5	15.9		421	6000	
300	111.6	0.4	12.5		390	6000	
300	138.7	0.3	10.1		398	6000	
300	163.1	0.3	8.6		421	6000	
300	200.3	0.23	7.0		403	6000	
300	235.4	0.20	5.9		421	6000	
300	284.8	0.16	4.9		409	6000	
300	354.0	0.13	4.0		398	6000	
380	5.1	11.3	272.2	IHA62	550	4195	104-105
380	6.2	9.3	225.0		682	4470	
380	7.7	7.5	181.0		664	4806	



Performance 性能参数 (n1=1400)


IH

M2 (Nm)	i	P1 (kW)	n2 (1/min)	型号	Fr1 (N)	Fr2 (N)			
460	9.6	7.3	145.2	IHA62	801	5173	104-105		
440	11.7	5.8	120.0		652	5512			
420	14.5	4.4	96.6		634	5926			
500	16.9	4.5	82.8		842	6238			
460	20.5	3.4	68.4		627	6647			
430	25.4	2.6	55.1		621	7147			
450	29.9	2.3	46.8		734	7543			
470	36.2	2.0	38.7		712	8000			
440	45.0	1.5	31.1		621	8000			
370	49.8	1.1	28.1		626	8000			
440	61.9	1.1	22.6		789	8000			
480	49.8	1.5	28.1	IHA63	330	8000	104-105		
480	60.2	1.2	23.2		409	8000			
480	74.9	1.0	18.7		398	8000			
480	88.0	0.9	15.9		421	8000			
480	111.6	0.7	12.5		390	8000			
480	138.7	0.5	10.1		398	8000			
480	163.1	0.5	8.6		421	8000			
480	200.3	0.4	7.0		403	8000			
480	235.4	0.3	5.9		421	8000			
480	284.8	0.3	4.9		409	8000			
480	354.0	0.2	4.0		398	8000			
95	4.7	3.1	298.1		IH032	700		3021	106-107
105	6.2	2.6	224.7			817		3309	
125	7.8	2.5	180.4			843		3432	
130	8.9	2.2	157.9	894		3593			
140	10.1	2.1	138.0	924		3713			
145	11.8	1.9	119.0	975		3920			
170	13.7	1.9	102.0	973		3943			
170	14.7	1.8	95.5	1000		4069			
190	16.8	1.7	83.5	1010		4126			
200	18.2	1.7	76.9	1021		4189			
200	19.9	1.5	70.4	1054		4376			
200	22.7	1.3	61.7	1097		4661			
200	23.8	1.3	58.7	1112		4772			
200	26.4	1.2	53.0	1140		5007			
200	29.7	1.0	47.1	1169		5288			
200	32.9	0.9	42.6	1192		5500			
200	37.9	0.81	36.9	1220		5500			
200	41.4	0.74	33.8	1236		5500			
200	47.3	0.65	29.6	1257		5500			
200	53.6	0.6	26.1	IH033	1274	5500	106-107		
200	66.8	0.47	21.0		1300	5500			
200	74.8	0.42	18.7		1311	5500			
200	99.3	0.31	14.1		1334	5500			
200	108.0	0.29	13.0		1339	5500			
200	123.7	0.25	11.3		1348	5500			
200	143.3	0.22	9.8		1355	5500			
200	178.6	0.17	7.8		1365	5500			
200	197.2	0.16	7.1		1369	5500			
200	245.7	0.13	5.7		1375	5500			
160	5.5	4.5	256.3		IH042	434		3912	110-11
160	7.2	3.4	194.8			673		4408	
210	8.9	3.6	157.1			628		4416	
240	10.3	3.6	135.7	638		4471			




IH (n1=1400) Performance 性能参数


M2 (Nm)	i	P1 (kW)	n2 (1/min)	型号	Fr1 (N)	Fr2 (N)	
250	11.8	3.2	118.6	IH042	709	4681	110-111
250	13.6	2.8	103.2		803	5001	
250	16.0	2.4	87.7		897	5389	
250	19.0	2.0	73.7		982	5831	
250	21.0	1.8	66.7		1024	6097	
260	23.1	1.7	60.5		1047	6280	
260	26.0	1.5	53.8		1089	6600	
280	27.5	1.6	50.9		1083	6600	
280	30.5	1.4	46.0		1116	6600	
280	34.1	1.3	41.1		1150	6600	
280	37.8	1.1	37.1		1177	6600	
280	43.8	0.98	32.0		1211	6600	
280	47.5	0.90	29.5		1228	6600	
280	54.3	0.79	25.8		1253	6600	
300	61.8	0.8	22.6	IH043	1264	6600	110-111
300	76.7	0.61	18.3		1296	6600	
300	87.1	0.54	16.1		1311	6600	
300	114.5	0.41	12.2		1340	6600	
300	125.7	0.37	11.1		1347	6600	
300	142.0	0.33	9.9		1357	6600	
300	165.4	0.28	8.5		1367	6600	
300	205.1	0.23	6.8		1379	6600	
300	227.5	0.21	6.2		1384	6600	
300	282.1	0.17	5.0		1392	6600	
260	5.7	6.9	244.4	IH052	259	4844	114-115
290	6.9	6.4	203.1		343	5059	
340	8.5	6.1	164.2		398	5234	
370	9.6	5.9	146.4		428	5322	
390	11.5	5.2	121.6		548	5680	
430	14.2	4.6	98.3		641	6016	
450	16.6	4.1	84.4		718	6343	
460	18.0	3.9	77.8		757	6530	
460	20.0	3.5	70.1		821	6866	
470	21.7	3.3	64.6		854	7069	
470	24.7	2.9	56.7		921	7521	
490	26.2	2.9	53.5		929	7594	
490	28.4	2.6	49.2		966	7894	
490	31.5	2.4	44.4		1008	8000	
490	33.0	2.3	42.4		1026	8000	
490	39.0	1.9	35.9		1083	8000	
490	45.4	1.6	30.9		1127	8000	
490	49.1	1.5	28.5		1148	8000	
490	56.1	1.3	24.9	1179	8000		
500	58.8	1.3	23.8	IH053	1185	8000	114-115
500	72.7	1.1	19.2		1226	8000	
500	90.5	0.86	15.5		1260	8000	
500	108.9	0.72	12.9		1283	8000	
500	134.8	0.58	10.4		1305	8000	
500	157.3	0.50	8.9		1319	8000	
500	194.6	0.40	7.2		1334	8000	
500	216.4	0.36	6.5		1340	8000	
500	267.7	0.29	5.2		1352	8000	
500	5.4	14.2	260.5	IH062	853	7822	118-119
550	5.9	14.2	235.9		860	7887	
550	7.4	11.4	189.4		1250	8720	
600	8.5	10.8	164.7		1332	8992	



Performance 性能参数 (n1=1400)


IH


M2 (Nm)	i	P1 (kW)	n2 (1/min)	型号	Fr1 (N)	Fr2 (N)	
600	9.4	9.8	149.2	IH062	1475	9407	118-119
650	11.7	8.5	119.8		1652	10084	
700	12.7	8.4	110.5		1660	10166	
700	14.8	7.2	94.9		1827	10900	
800	16.3	7.5	86.0		1791	10815	
830	17.7	7.2	79.2		1837	11061	
850	20.3	6.4	69.0		1946	11686	
850	23.3	5.6	60.2		2061	12000	
850	25.7	5.1	54.5		2134	12000	
800	29.3	4.2	47.7		2259	12000	
850	32.0	4.1	43.8		2274	12000	
800	37.0	3.3	37.8		2379	12000	
850	40.3	3.2	34.7		2391	12000	
850	46.1	2.8	30.4		2447	12000	
850	49.5	2.7	28.3	IH063	2474	12000	118-119
850	54.6	2.4	25.6		2509	12000	
850	68.0	1.9	20.6		2574	12000	
850	85.8	1.5	16.3		2630	12000	
850	94.8	1.4	14.8		2650	12000	
850	118.0	1.1	11.9		2688	12000	
850	135.4	1.0	10.3		2707	12000	
850	149.5	0.89	9.4		2720	12000	
850	170.7	0.78	8.2		2735	12000	
850	186.2	0.71	7.5		2744	12000	
850	215.2	0.62	6.5		2757	12000	
850	234.7	0.56	6.0		2764	12000	
850	268.0	0.49	5.2		2774	12000	
700	5.4	19.8	259.8		IH082	816	
700	5.9	18.0	235.5	1021		10273	
800	7.4	16.5	189.3	1182		10821	
800	8.0	15.2	174.5	1325		11215	
900	8.9	15.5	158.2	1292		11248	
1100	11.0	15.3	127.2	1321		11480	
1400	13.5	15.8	103.7	1258		11258	
1500	14.9	15.4	94.0	1308		11384	
1500	16.6	13.8	84.3	1484		12054	
1500	18.5	12.4	75.6	1641		12745	
1600	19.4	12.6	72.2	1615		12583	
1600	21.4	11.4	65.5	1745		13240	
1600	22.8	10.7	61.4	1824		13678	
1600	26.6	9.2	52.6	1993		14774	
1600	27.9	8.8	50.2	2040		15120	
1600	31.2	7.8	44.9	2141		15956	
1600	34.4	7.1	40.7	2222		16725	
1600	38.7	6.3	36.2	2310		17684	
1600	42.8	5.7	32.7	2376		18000	
1600	48.1	5.1	29.1	2447		18000	
1600	56.5	4.4	24.8	IH083	2530	18000	122-123
1800	71.5	3.9	19.6		2583	18000	
1800	78.9	3.6	17.8		2623	18000	
1800	85.6	3.3	16.4		2653	18000	
1800	98.1	2.9	14.3		2698	18000	
1800	112.8	2.5	12.4		2739	18000	
1800	124.4	2.3	11.3		2764	18000	
1800	142.2	2.0	9.8		2794	18000	
1800	154.8	1.8	9.0		2812	18000	
1800	162.3	1.7	8.6		2821	18000	



IH (n1=1400) Performance 性能参数

M2 (Nm)	i	P1 (kW)	n2 (1/min)	型号	Fr1 (N)	Fr2 (N)			
1800	179.1	1.6	7.8	IH083	2838	18000	130-131		
1800	195.1	1.4	7.2		2852	18000			
1800	222.8	1.3	6.3		2872	18000			
1800	5.3	52.2	266.0	IH102	1731	10504	126-127		
2000	6.4	48.1	220.3		1919	10859			
2300	7.1	49.8	198.6		1840	10364			
2500	8.3	46.1	169.2		2006	10640			
2800	10.0	42.8	140.1		2157	10795			
3000	11.1	41.3	126.3		2223	10783			
3100	13.3	35.5	105.1		2486	11791			
3200	16.1	30.4	87.0		2719	12924			
3200	17.9	27.4	78.4		2854	13798			
3200	19.8	24.6	70.5		2979	14721			
3200	21.4	22.8	65.3		3061	15415			
3300	24.0	21.0	58.4		3141	16067			
3300	25.9	19.5	54.1		3212	16805			
3300	28.7	17.5	48.7		3299	17827			
3200	30.7	15.9	45.6		3372	18885			
3200	34.2	14.3	40.9		3446	20003			
2800	38.5	11.1	36.4		3589	22000			
3300	41.3	12.2	33.9		3540	21688			
3300	45.8	11.0	30.6		3594	22000			
3300	51.5	9.8	27.2		3649	22000			
3500	55.5	9.8	25.2	IH103	3656	22000	126-127		
3500	69.7	7.8	20.1		3745	22000			
3500	79.8	6.8	17.5		3789	22000			
3500	84.2	6.5	16.6		3804	22000			
3500	93.4	5.8	15.0		3833	22000			
3500	100.1	5.5	14.0		3850	22000			
3500	120.8	4.5	11.6		3892	22000			
3500	134.1	4.1	10.4		3911	22000			
3500	143.4	3.8	9.8		3923	22000			
3500	160.8	3.4	8.7		3941	22000			
3500	181.1	3.0	7.7		3958	22000			
3500	194.2	2.8	7.2		3967	22000			
3500	215.5	2.5	6.5		3979	22000			
3600	242.6	2.3	5.8		3989	22000			
3000	5.3	86.9	265.4		IH122	778		15220	130-131
3200	5.8	84.6	242.4			862		15332	
3600	7.0	78.0	198.6	1110		15786			
3700	7.7	73.0	180.8	1297		16325			
3800	8.5	68.5	165.2	1467		16860			
4000	10.3	59.0	135.3	1819		18195			
4400	12.7	53.1	110.6	2043		19049			
4600	13.9	50.7	101.0	2132		19413			
4800	16.9	43.3	82.7	2408		21096			
5000	19.3	39.5	72.5	2550		22087			
5000	20.6	37.1	68.1	2640		22886			
5000	22.5	33.9	62.2	2760		24070			
5000	24.5	31.2	57.2	2861		25182			
5000	27.5	27.8	50.9	2989		26801			
5000	29.9	25.6	46.9	3072		27989			
5000	33.0	23.1	42.4	3163		29467			
5000	36.1	21.1	38.7	3238		30000			
5000	44.1	17.3	31.7	3381		30000			


Performance 性能参数 (n1=1400)
IH

M2 (Nm)	i	P1 (kW)	n2 (1/min)	型号	Fr1 (N)	Fr2 (N)	
5000	45.8	17.0	30.6	IH123	3405	30000	130-131
5000	55.9	14.0	25.1				
5000	67.3	11.6	20.8				
5000	73.7	10.6	19.0				
5000	83.3	9.4	16.8				
5000	90.0	8.7	15.6				
5000	100.3	7.8	14.0				
5000	108.3	7.2	12.9				
5000	118.6	6.6	11.8				
5000	128.2	6.1	10.9				
5000	144.8	5.4	9.7				
5000	155.2	5.0	9.0				
5000	172.8	4.5	8.1				
5000	189.2	4.1	7.4				
5000	207.4	3.7	6.7				
5000	230.9	3.4	6.1				
4600	5.3	133.2	265.4	IH142	4000	19362	132-133
4900	6.4	117.7	220.3				
5000	7.0	108.4	198.8				
5300	7.8	103.2	178.5				
6500	9.5	105.0	148.1				
7200	10.5	105.0	133.7				
7300	13.1	85.3	107.1				
7800	15.8	75.6	88.9				
7900	17.5	69.1	80.2				
8000	20.0	61.0	69.9				
8000	24.2	50.6	58.0				
8000	26.8	45.6	52.3				
8000	32.2	37.9	43.4				
8000	38.9	31.4	36.0				
8000	43.1	28.4	32.5				
8000	48.3	25.8	29.0		IH143	8000	
8000	53.5	23.3	26.2				
8000	59.2	21.1	23.6				
8000	63.0	19.8	22.2				
8000	71.4	17.5	19.6				
8000	79.1	15.8	17.7				
8000	86.4	14.4	16.2				
8000	96.2	13.0	14.6				
8000	104.5	11.9	13.4				
8000	115.9	10.8	12.1				
8000	128.5	9.7	10.9				
8000	139.6	8.9	10.0				
8000	154.3	8.1	9.1				
8000	186.0	6.7	7.5				
8000	206.1	6.1	6.8				