

指针式千分表

2 系列 — 长行程型



2050S



2330S-10



2052S

北京时代宏迪科技有限公司
咨询电话：400-055-2886



(参见第 9 页)



2050S-60
2050S
2050S-19



2052S
2052S-19



2330S-10



2320S-10




2952S



防震型




防水型



最低休止点
带有气阀



宝石轴承型



带有同轴
旋转计数器



反向读数型

性能参数

公制型

ISO/JIS 型

| 分度值 | 货号 | | 测量范围 (测量范围/每圈行程) | 精度 | 表盘读 数值 | 测力 | | | | | | |
|--------|----------|-----------|---------------------|-------|-----------|---------|---|---|---|---|---|---|
| | 带耳后盖 | 平型后盖 | | | | | | | | | | |
| 0.01mm | 2050S | 2050SB | 20mm (1mm) | ±20μm | 0-100 | 2.0N 以下 | — | — | ✓ | — | — | — |
| 0.01mm | 2050S-60 | 2050SB-60 | 20mm (1mm) | ±20μm | 0-100 | 2.5N 以下 | — | ✓ | — | — | — | — |
| 0.01mm | 2050S-19 | 2050SB-19 | 20mm (1mm) | ±20μm | 0-100 | 2.0N 以下 | ✓ | — | ✓ | ✓ | — | — |
| 0.01mm | 2320S-10 | 2320SB-10 | 20mm (1mm) | ±20μm | 0-100 | 2.0N 以下 | — | — | ✓ | ✓ | ✓ | — |
| 0.01mm | 2052S | 2052SB | 30mm (1mm) | ±25μm | 0-100 | 2.5N 以下 | — | — | ✓ | — | — | — |
| 0.01mm | 2052S-19 | 2052SB-19 | 30mm (1mm) | ±25μm | 0-100 | 2.5N 以下 | ✓ | — | ✓ | ✓ | — | — |
| 0.01mm | 2330S-10 | 2330SB-10 | 30mm (1mm) | ±25μm | 0-100 | 2.5N 以下 | — | — | ✓ | ✓ | ✓ | — |
| 0.01mm | 2952S | 2952SB | 30mm (1mm) | ±25μm | 100-0 | 2.5N 以下 | — | — | ✓ | — | — | ✓ |

英制型

ANSI/AGD 型

| 分度值 | 货号 | | 测量范围 (测量范围/每圈行程) | 精度 | 表盘读 数值 | 测力 | | | | | | |
|--------|----------|-----------|---------------------|--------|-----------|---------|---|---|---|---|---|---|
| | 带耳后盖 | 平型后盖 | | | | | | | | | | |
| .01" | 2204S | 2204SB | 1" (.1") | ±.005" | 0-1000 | 1.8N 以下 | — | — | — | — | — | — |
| .001" | 2416S | 2416SB | 1" (.1") | ±.001" | 0-100 | 1.8N 以下 | — | — | — | — | — | — |
| .001" | 2416S-06 | 2416SB-06 | 1" (.1") | ±.001" | 0-100 | 1.8N 以下 | — | — | — | — | — | — |
| .001" | 2416S-10 | 2416SB-10 | 1" (.1") | ±.001" | 0-100 | 1.8N 以下 | — | — | — | ✓ | — | — |
| .001" | 2416S-60 | 2416SB-60 | 1" (.1") | ±.001" | 0-100 | 2.5N 以下 | — | ✓ | — | — | — | — |
| .001" | 2417S | 2417SB | 1" (.1") | ±.001" | 0-50-0 | 1.8N 以下 | — | — | — | — | — | — |
| .001" | 2424S-19 | 2424SB-19 | 2" (.1") | ±.003" | 0-100 | 2.5N 以下 | ✓ | — | — | ✓ | — | ✓ |
| .0005" | 2776S | 2776SB | 1" (.05") | ±.002" | 0-50 | 1.8N 以下 | — | — | — | — | — | — |
| .0005" | 2776S-60 | 2776SB-60 | 1" (.05") | ±.002" | 0-50 | 2.5N 以下 | — | ✓ | — | — | — | — |
| .001" | 2904S | 2904SB | 1" (.1") | ±.002" | 100-0 | 2.0N 以下 | — | — | ✓ | — | — | — |

选件

—: 后盖 (参见 266 页)
—: 测针 (参见 264 页)

尺寸

