

HYGROPALM

HYGROCLIP[®]

Humidity goes Digital



HygroPalm 0

Portable Humidity Temperature Instrument

- Precision measurement of humidity and temperature
- Integrated probe with $\pm 1.5\%rh/0.3\text{ }^{\circ}\text{C}$ accuracy
- Dew-point measurement and wet bulb temperature
- 1-point adjustment performed in seconds
- SWISS MADE

rotronic[®]

LEADING IN HUMIDITY MEASUREMENT

上海博鑫科技有限公司 手机:13816625261 电话:021-2907 5544 / 2910 5544 传真:021-27019266
地址:上海市徐汇区肇嘉浜路269号云福大厦2号楼607室 邮编:200032 MSN:kerenkai@yahoo.com.cn
网址:www.dewpoint.com.cn 或 dewpoint.18show.net E-mail:info@dewpoint.com.cn Skype:kerenkai

www.rotronic-humidity.com



HygroPalm 0

- Portable instrument for %rh, °C/°F
- Display of dew-point or wet-bulb
- Single point probe adjustment



HygroPalm 0 is an ergonomic instrument with an integrated probe that provides measurements with high precision.

The accuracy of $\pm 1.5\%$ rh at 23 °C over the whole range of humidity is unrivalled in this price class. The Hygromer® AC-1 humidity sensor has an unparalleled long-term stability of better than 1 %rh /year!

ROTRONIC grants a warranty period of two years for this product.

Calibration


In combination with the SCS*-certified humidity standards, a single point adjustment can be performed directly with the keypad.

* SCS = Swiss Calibration Service



Applications

Monitoring of production sites, warehouses, museums, galleries, shopping centres, laboratories or computer rooms are typical applications for this instrument.



Summary & Technical Data

SPECIFICATIONS	HYGROPALM 0
Measuring range	0...100 %rh, -10...60 °C
Humidity sensor	Hygromer® AC-1
Temperature sensor	Pt100 1/3 DIN
Accuracy at 23 °C	$\pm 1.5\%$ rh, ± 0.3 K
Reproducibility	Better than 0.5 %rh, 0.1 °C
Long term stability	< 0.1 %rh/year
Calculations	Dew point and wet-bulb temperature
Adjustment	1-point (%rh, °C, °F) directly with keypad
Operating range electronics	0...100 %rh (non condensing) / -10...+60 °C
Display type	Liquid crystal 4 line alphanumeric
Display resolution	0.1 %rh, 0.1 °C/°F, 0.01 calculated value
Instrument power supply	30 mA max. power consumption, 9 V alkaline battery, 100 hours life, 9 V rechargeable, 75 hours life, docking station recharging, 9 V mains adapter,
Weight	Ca. 280 g

ORDER INFORMATION	HYGROPALM AND ACCESSORIES
HygroPalm 0	Humidity temperature meter, incl. probe, dew-point/wet-bulb calculation
PalmDock 1	Docking station for power connection with battery charger
PalmDock 2	Same as PalmDock 1, but with lock
AC1207	Mains adapter for PalmDock 1 and PalmDock 2
ER-15	Calibration device
EA35-SCS	Humidity Standards 35 %rh (box of 5 ampoules) with SCS certificate)
EA50-SCS	Humidity Standards 50 %rh (box of 5 ampoules) with SCS certificate)
EA80-SCS	Humidity Standards 80 %rh (box of 5 ampoules) with SCS certificate)
HygroPalm 1	Humidity temperature meter for HygroClip probes with dew-point/wet-bulb calculation
HygroClip S	Interchangeable sensor module for climate measurement, 0...100 %rh, -40...85 °C