


BB型

AH型

型式	Model	BB01	BB03	BB05	BB10	BB20	BB30	BB50		
最大吐出量（吐出侧 开放时）	ML/min	50Hz	14	55	110	200	400	530	1000	
		60Hz	16	65	130	240	480	640	1200	
Max discharge capacity (at 0 kg/cm ²)	L/h	50Hz	0.83	3.3	6.6	12	24	32	60	
		60Hz	0.98	3.9	7.8	14.4	28.8	38	72	
最高压力 Max dis.Press.kg/cm ²		10						6		
流量调整 Capacity adjustment		运转中手动调整								
马达（层内型）Mototr（indoor use JP20）		4P、15W（25W）、50/60Hz			4P、40W、50/60Hz					
		1Ø、100V 电容起动机 Capacitor run motor			(1) 1 Ø、100V、电容起动机 Capacitor run motor (2) 3 Ø、200V、感应马达 Induction Motor					
重量（约）Weight approx kg		3.1			5.3		5.4			
接续软管 Bradi PVC hose		ID: Ø6			OD: Ø11			ID: Ø9 OD: Ø15		

Series AH Capacity-Pressure Selection Table

Model	Diaphragm (mm)	Stroke length (mm)	No. of stroke spm		Dis capacity L/min		Max. dis pressure (kgf/cm ²)	Output motor (kw)	Joint size			
			50Hz	60Hz	50Hz	60Hz			Flange	Union	Hose	
AHA	01	Ø42	2	48	58	0.035	0.042	10	0.2	JIS 10K 15A	VP16	Ø6 Ø11
	11			48	58	0.07	0.084					
	12		4	96	116	0.14	0.17					
	21			48	58	0.23	0.28					
	22	Ø65	4	96	116	0.46	0.56					
	31			8	48	58	0.9					
	32	Ø84	8		96	116	1.8					
	41			10	48	58	2.3					
	42	Ø120	10			96	116					
	51			Ø144	10	48	58					
52	10	96	116			6.6	8					
AHB			41	Ø120	12	48	58	2.8	3.3	7	0.4	JIS 10K 20A
	42	96	116			5.6	6.6					
	51	Ø144	14	48	58	5	6					
52	96			116	10	12						
AHC	51	Ø144	14	48	58	5	6	7		JIS 10K 40A		
	52			96	116	10	12					
	61	Ø170	18	48	58	9	10.8	3	0.75	JIS 10k 50A		
	62			96	116	18	21.6					
	71	Ø210	20	48	58	15.5	18.6					
	72			96	116	31	37.2					