Flow Meters

Dispense and batch precise amounts of fluid. Connects directly to pump.



Part No.	Description	Construction	Applicable Model	
	U.S. Units - GP	М		
	Factory Calibrate	ed		
106608	FM-1000, totalizer only	Polypropylene	PFM, PFP	
106608-1	FM-1000, rate & totalizer	Polypropylene	PFM, PFP	
106608-2	FM-1000, totalizer only	PVDF	PFV	
106608-3	FM-1000, rate & totalizer	PVDF	PFV	
	User Adjustable Calib	ration		
106609	FM-2000, rate & totalizer	Polypropylene	PFM, PFP	
106609-1	FM-2000, rate & totalizer	PVDF	PFV	
With Batch Control, - User adjustable calibration				
106609-2	FMBC-2000, rate, totalizer	Polypropylene	PFM, PFP	
106609-3	FMBC-2000, rate, totalizer	PVDF	PFV	
Metric Units - LPM				
	Factory Calibrated			
106608-4	FM-1000, totalizer only	Polypropylene	PFM, PFP	
106608-5	FM-1000, rate & totalizer	Polypropylene	PFM, PFP	
106608-6	FM-1000, totalizer only	PVDF	PFV	
106608-7	FM-1000, rate & totalizer	PVDF	PFV	
	User Adjustable Calibration			
106609-4	FM-2000, rate & totalizer (no CE)	Polypropylene	PFM, PFP	
106609-5	FM-2000, rate & totalizer (no CE)	PVDF	PFV	
106734	FM-3000, rate & totalizer (CE & plug type F)	Polypropylene	PFM, PFP	
With Batch Control - User adjustable calibration				
106609-6	FMBC-2000, rate & totalizer (no CE)	Polypropylene	PFM, PFP	
106609-7	FMBC-2000, rate & totalizer (no CE)	PVDF	PFV	
106734-1	FMBC-3000, rate & totalizer, (CE & plug type F)	Polypropylene	PFM, PFP	

Discharge Tubing



Part No.	Discharge Hose Description	Construction	Applicable Model
M102131	3/4" ID x 1" OD x 5 ft. ⁺⁺	Clear PVC	EP
J103470	3/4" ID x 1" OD x per ft. ††	Clear PVC	EP
107435	3/4" ID x 1" OD x 5 ft.†	Reinforced PVC	EF
107440	3/4" ID x 1" OD x per ft.†	Reinforced PVC	EF
M100221	1" ID x 1 5/16" x 5 ft.†	Reinforced PVC	PF
J100302	1" ID x 1 5/16" x per ft.†	Reinforced PVC	PF
M102167	1" ID x 1 1/4" OD x 5 ft. ⁺⁺	Clear PVC	TB, TT
J102785	1" ID x 1 1/4" OD x per ft. ⁺⁺	Clear PVC	TB,TT
J100322	1-1/2" ID x 1 3/4" OD x per ft. ⁺⁺	Clear PVC	BT, HVDP

Note: Temperatures are based on pumping water.

 $^{\scriptscriptstyle \dagger}$ Maximum operating temperature: $\,$ -22°F (-30°C) to 175°F (79°C)

⁺⁺Maximum operating temperature: -41°F (-41°C) to 140°F (60°C)

Static Protection Kit



Increases safety when pumping flammable fluids.

*Kit includes synthetic rubber cross-linked polyethylene grounded hose with brass fittings, ground wire, and clamps.

Part No.	Hose Description	Applicable Model
A101521	4 ft. hose with threaded 1" MNPT*	TBS, TTS, PFS
A100835	4 ft. hose with 1" hose barb*	TBS, TTS, PFS
A100836	4 ft. hose with 1 1/2" hose barb*	BT, HVDP
107429	4 ft. with threaded 3/4" MNPT*	EFS
A100961	Wire Assembly	TM

Note: Special lengths are available. Contact factory.

Note: Temperatures are based on pumping water.

*Maximum temperature: -25°F (-32°C) to 150°F (65°C)



Part No.	Description	Construction	Applicable Model
A101497-1	3/4" hose barb with clamp	Polypropylene/316 SS	EP, EF
107231*	3/4" hose barb with clamp	Stainless steel / FKM	EF
A101497	1" hose barb with clamp	Polypropylene/316 SS	TB, PF, TT
A101522	Union valve nozzle 1" hose barb with clamp	Polypropylene/FKM	TB, PF, TT
J101929	1" threaded FNPT	Aluminum	TBS, TTS, PFS
107232*	1" hose barb with clamp	Stainless steel / FKM	TB, PF, TT
107464	1" threaded FNPT	Stainless steel / FKM	TB, PF, TT

^{*}Features auto shut-off.

Inlet Strainers



Prevents intake of objects or particulates.

Part No.	Construction	Applicable Model
A100855	Polypropylene	PFP
A100111	316 SS	PF, BT
A100337	316 SS	TTS,TBS
A100109	PVC/Polyethylene	TTC

Drum Adapters





Keeps pump snug in container bung and limits the escape of fumes.

Fits standard 2" IPS bung opening

Part No.	Construction	Applicable Model	
J100366	Polypropylene	EP	
107426	304 SS	EFS	
107425	Polypropylene	EFP, EFV	
M100095	Polypropylene	BT, PF, TM, HVDP	
M100088	Galvanized Steel	BT, PF, TM	
M100094	304 SS	BT, PF, TM, HVDP	
M100090	Polypropylene	TBS, TTS	
M100091	Polypropylene	TBP, TTC	
M100089	Galvanized Steel	TBS, TTS	
M100092	304 SS	TBS, TTS	

SS Hose Clamp



Secures discharge tubing around pump and fittings.

Part No.	Diameter	Applicable Model
J101756	1/2" - 1-1/4"	EP, EF
J101832	3/4" - 1-3/4"	TB, PF, TT
J100832	1-1/2" - 2-1/4"	BT, HVDP

Wall Mount Bracket



Stores pump upright on the wall.

Part No.	Applicable Model
M100015	TB, PF, TT, TM
M100740	BT-1, 2, 3 HP

Filter / Lubricator Assembly and Air Hose



Maintains a clean and oiled air motor for longer life and good operation. Air hose sold separately.

Part No.	Item	Applicable Model
A100003	Filter / Lubricator	M6, M6X, M18, M57, M54
A100221	Filter / Lubricator	M19, M20
A100009	Air Hose	M6, M6X, M18, m57, M54, S4



FINISH THOMPSON INC.

921 Greengarden Road • Erie, PA 16501-1591 U.S.A. Ph 814-455-4478 • Fax 814-455-8518 Email fti@finishthompson.com • www.finishthompson.com 1-800-934-9384