

BAND-IT 成卷、带涂层扎带

全功能型扎带

型号	材料*	宽度		厚度		孔径		数量	重量		紧带机
		In	mm	In	mm	In	mm		Lbs	Kg	
AE4759	316 SS (coated)	1/2	13	0.050**	1.10**	3/16	5	82.5'/roll	3.1	1.4	n/a
AE4769	316 SS (coated)	3/4	19	0.050**	1.10**	9/32	7	82.5'/roll	5.3	2.4	
AE4779	316 SS (coated)	1	25	0.050**	1.10**	5/16	8	82.5'/roll	7.3	3.3	
AE4259	316 SS (uncoated)	1/2	13	0.030**	0.76**	3/16	5	82.5'/roll	3.1	1.4	
AE4269	316 SS (uncoated)	3/4	19	0.030**	0.76**	9/32	7	82.5'/roll	4.6	2.1	
AE4279	316 SS (uncoated)	1	25	0.030**	0.76**	5/16	8	82.5'/roll	5.5	2.5	

**材料厚度包括PPA551涂层 - 金属材料厚度0.030"

Q-Band™

型号	材料*	宽度		厚度		数量	重量		紧带机
		In	mm	In	mm		Lbs	Kg	
Q70499	White Plastic	1/2	13	0.030	0.76	100'/roll	0.8	0.3	Q72099

Q-Clip™

型号	材料*	宽度		数量	重量	
		In	mm		Lbs	Kg
Q71499	White Plastic	1/2	13	25/box	0.2	0.1

*BAND-IT保留用抗腐蚀和（或）机械性能相当或更好材料替换的权利。



Q71499 Q-Clip™

316 型不锈钢扎带 无涂层和涂层

型号	材料*	宽度		厚度		平均断裂强度 (磅)	数量	重量		紧带机
		In	mm	In	mm			Lbs	Kg	
C40299	316 SS	1/4	6	0.020	0.51	400	100'/roll	1.7	0.9	
C40399	316 SS	3/8	10	0.025	0.63	750	100'/roll	3.2	1.6	C00169
C40499	316 SS	1/2	13	0.030	0.76	1200	100'/roll	5.1	2.4	C00369
C44499	316 SS	1/2	13	0.015	0.38	600	200'/roll	5.3	2.6	C07569
C40599	316 SS	5/8	16	0.030	0.76	1500	100'/roll	6.4	3.0	C08569
C44599	316 SS	5/8	16	0.015	0.38	750	200'/roll	6.6	3.2	C40099
C40699	316 SS	3/4	19	0.030	0.76	1800	100'/roll	7.7	3.6	J02069+
C44699	316 SS	3/4	19	0.015	0.38	900	200'/roll	7.8	3.7	

这些产品长度有大盘卷钢可选。

+ J02069 紧带机能用于 1/4" 和 3/8" 宽度的产品。

316 型不锈钢涂层扎带

AE4329	316 SS	1/4	6	0.048**	1.00**	335	82.5'/roll	2.0	0.9	C07569
AE4339	316 SS	3/8	10	0.048**	1.00**	505	82.5'/roll	2.6	1.2	C08569
AE4349	316 SS	1/2	13	0.048**	1.00**	670	82.5'/roll	3.5	1.6	C40099
AE4359	316 SS	5/8	16	0.048**	1.00**	840	82.5'/roll	4.4	2.0	
AE4369	316 SS	3/4	19	0.048**	1.00**	1000	82.5'/roll	5.3	2.4	

**材料厚度包括 PPA 571 涂层 - 金属材料厚度 0.015"

316 型不锈钢扎扣


型号	材料*	宽度		数量	重量	
		In	mm		Lbs	Kg
AE4529	316 SS	1/4	6	100/box	0.3	0.1
AE4539	316 SS	3/8	10	100/box	0.6	0.3
AE4549	316 SS	1/2	13	100/box	1.0	0.4
AE4559	316 SS	5/8	16	100/box	1.1	0.5
AE4569	316 SS	3/4	19	100/box	1.3	0.6



316 型不锈钢扎扣



全功能型扎带



Q70499 Q-Band™



Q72099 Q-紧带机

C00169 BAND-IT 紧带机
产品信息参看第11页。



316 型不锈钢扎带



316 型涂层不锈钢扎带

Band-Lok 扣带

型号	材料*	宽度		长度		厚度		内径 单层缠绕		最小环绕 张力强度 (磅)	数量	重量		紧带机
		In	mm	In	mm	In	mm	In	mm			Lbs	Kg	
BL2119	201 SS	5/16	8	10.0	254	0.015	0.38	2.0	51	250	100/bag	1.4	0.7	A95079
BL2129	201 SS	5/16	8	16.0	406	0.015	0.38	3.5	89	250	100/bag	2.3	1.1	
BL2139	201 SS	5/16	8	19.0	482	0.015	0.38	5.0	127	250	100/bag	3.1	1.5	
BL2149	201 SS	5/16	8	27.0	686	0.015	0.38	7.0	178	250	100/bag	3.9	1.8	
BL2159	201 SS	5/16	8	34.0	864	0.015	0.38	9.0	229	250	100/bag	4.7	2.2	



A95079 Band-Lok 紧带机



Band-Lok 扣带

CE, DNV 和海岸警卫认证

Ball-Lok 扣带

型号	材料*	宽度		长度		内层金属 厚度		内径 单层缠绕		最小环绕 张力强度 (磅)	数量	重量		紧带机	
		In	mm	In	mm	In	mm	In	mm			Lbs	Kg		
KE1128	-	304 SS	0.180	5	7.9	201	0.010	0.25	2.0	50	200	100/bag	0.6	0.3	K50289 or by hand
KE1138	-	304 SS	0.180	5	10.2	259	0.010	0.25	2.7	69	200	100/bag	0.7	0.4	
KE1148	-	304 SS	0.180	5	14.2	360	0.010	0.25	4.0	102	200	100/bag	0.9	0.5	
KE1158	-	304 SS	0.180	5	20.4	520	0.010	0.25	6.0	152	200	100/bag	1.3	0.6	
KE1168	-	304 SS	0.180	5	26.8	679	0.010	0.25	8.0	203	200	100/bag	1.8	0.8	
KE1178	-	304 SS	0.180	5	33.0	838	0.010	0.25	10.0	254	200	100/bag	2.1	1.0	
KE1188	-	304 SS	0.180	5	42.0	1067	0.010	0.25	12.0	305	200	100/bag	2.4	1.1	
KE0128	-	316 SS	0.180	5	7.9	201	0.010	0.25	2.0	50	200	100/bag	0.6	0.3	
KE0138	-	316 SS	0.180	5	10.2	259	0.010	0.25	2.7	69	200	100/bag	0.7	0.4	
KE0148	-	316 SS	0.180	5	14.2	360	0.010	0.25	4.0	102	200	100/bag	0.9	0.5	
KE0158	-	316 SS	0.180	5	20.4	520	0.010	0.25	6.0	152	200	100/bag	1.3	0.6	
KE0168	-	316 SS	0.180	5	26.8	679	0.010	0.25	8.0	203	200	100/bag	1.8	0.8	
KE0178	-	316 SS	0.180	5	33.0	838	0.010	0.25	10.0	254	200	100/bag	2.1	1.0	
KE0188	-	316 SS	0.180	5	42.0	1067	0.010	0.25	12.0	305	200	100/bag	2.4	1.1	
KE1328	-	304 SS	0.310	8	7.9	201	0.010	0.25	2.0	50	300	100/bag	1.0	0.5	
KE1338	-	304 SS	0.310	8	10.2	259	0.010	0.25	2.7	69	300	100/bag	1.3	0.6	
KE1348	-	304 SS	0.310	8	14.2	360	0.010	0.25	4.0	102	300	100/bag	1.7	0.8	
KE1358	-	304 SS	0.310	8	20.4	520	0.010	0.25	6.0	152	300	100/bag	2.2	1.1	
KE1368	-	304 SS	0.310	8	26.8	679	0.010	0.25	8.0	203	300	100/bag	2.9	1.3	
KE1378	-	304 SS	0.310	8	33.0	838	0.010	0.25	10.0	254	300	100/bag	3.5	1.6	
KE1388	-	304 SS	0.310	8	42.0	1067	0.010	0.25	12.0	305	300	100/bag	4.6	2.1	
KE0328	-	316 SS	0.310	8	7.9	201	0.010	0.25	2.0	50	300	100/bag	1.0	0.5	
KE0338	-	316 SS	0.310	8	10.2	259	0.010	0.25	2.7	69	300	100/bag	1.3	0.6	
KE0348	-	316 SS	0.310	8	14.2	360	0.010	0.25	4.0	102	300	100/bag	1.7	0.8	
KE0358	-	316 SS	0.310	8	20.4	520	0.010	0.25	6.0	152	300	100/bag	2.2	1.1	
KE0368	-	316 SS	0.310	8	26.8	679	0.010	0.25	8.0	203	300	100/bag	2.9	1.3	
KE0378	-	316 SS	0.310	8	33.0	838	0.010	0.25	10.0	254	300	100/bag	3.5	1.6	
KE0388	-	316 SS	0.310	8	42.0	1067	0.010	0.25	12.0	305	300	100/bag	4.6	2.1	
-	KE0828	316 SS	0.310	8	7.9	201	0.010	0.25	2.0	50	300	100/bag	1.2	0.6	
-	KE0848	316 SS	0.310	8	14.2	360	0.010	0.25	4.0	102	300	100/bag	1.8	0.9	
-	KE0858	316 SS	0.310	8	20.4	520	0.010	0.25	6.0	152	300	100/bag	2.5	1.2	




K50289 Ball-Lok 紧带机



Ball-Lok 扣带

*BAND-IT 保留用抗腐蚀和（或）机械性能相当或更好材料替换的权利。



参看第3页。

UL, CE 和 DNV 认证



AE2009 缆线扣带拉紧



M50389 Multi-Lok 手动紧带机

Multi-Lok 扣带

型号	材料*	宽度		长度		厚度				内径 单层缠绕		最小环绕 张力强度 (磅)	数量	重量		紧带机	
		In	mm	In	mm	无涂层 In	无涂层 mm	涂层 In	涂层 mm	In	mm			Lbs	Kg		
AE6019	AE6119	316 SS	0.270	7	6.0	150	0.011	0.28	0.018	0.46	1.9	48	250	100/bag	0.7	0.3	AE2009
AE6029	AE6129	316 SS	0.270	7	9.0	225	0.011	0.28	0.018	0.46	2.8	71	250	100/bag	0.9	0.5	AE2018
AE6039	AE6139	316 SS	0.270	7	12.0	300	0.011	0.28	0.018	0.46	3.8	96	250	100/bag	1.3	0.6	M50389
AE6049	AE6149	316 SS	0.270	7	18.0	450	0.011	0.28	0.018	0.46	5.7	144	250	100/bag	1.8	0.8	or by hand
AE6059	AE6159	316 SS	0.270	7	24.0	610	0.011	0.28	0.018	0.46	7.6	193	250	100/bag	2.6	1.2	
AE7019	AE7119	316 SS	0.470	12	6.0	150	0.011	0.28	0.018	0.46	1.9	48	250	100/bag	1.1	0.5	
AE7029	AE7129	316 SS	0.470	12	9.0	225	0.011	0.28	0.018	0.46	2.8	71	250	100/bag	1.7	0.8	
AE7039	AE7139	316 SS	0.470	12	12.0	300	0.011	0.28	0.018	0.46	3.8	96	250	100/bag	2.2	1.0	
AE7049	AE7149	316 SS	0.470	12	18.0	450	0.011	0.28	0.018	0.46	5.7	144	250	100/bag	3.0	1.4	
AE7059	AE7159	316 SS	0.470	12	24.0	610	0.011	0.28	0.018	0.46	7.6	193	250	100/bag	4.3	2.0	

UL, DNV, CE 和海岸警卫认证 (5/8" 宽度)

BAND-IT 扣带

型号	材料*	宽度		长度		厚度 涂层		内径 单层缠绕		最小环绕 张力强度 (磅)	数量	重量		紧带机
		In	mm	In	mm	In	mm	In	mm			Lbs	Kg	
AE1118	SS	1/4	6	6.0	152	0.026	0.66	1.5	38	75/300**	100/bag	1.4	0.6	AE2018
AE1128	SS	1/4	6	9.0	229	0.026	0.66	2.5	63	75/300**	100/bag	1.8	0.8	AE2009
AE1138	SS	1/4	6	12.0	305	0.026	0.66	3.4	86	75/300**	100/bag	2.1	1.0	C07569
AE1148	SS	1/4	6	18.0	457	0.026	0.66	5.4	137	75/300**	100/bag	3.0	1.4	or by hand
AE1158	SS	1/4	6	24.0	610	0.026	0.66	7.3	185	75/300**	100/bag	3.7	1.7	
AE3118	SS	3/8	10	6.0	152	0.026	0.66	1.5	38	100/500**	100/bag	1.8	0.8	
AE3128	SS	3/8	10	9.0	229	0.026	0.66	2.5	63	100/500**	100/bag	2.5	1.1	
AE3138	SS	3/8	10	12.0	305	0.026	0.66	3.4	86	100/500**	100/bag	3.1	1.4	
AE3148	SS	3/8	10	18.0	457	0.026	0.66	5.4	137	100/500**	100/bag	4.4	2.2	
AE3158	SS	3/8	10	24.0	610	0.026	0.66	7.3	185	100/500**	100/bag	6.6	3.0	
AE3168	SS	3/8	10	30.0	762	0.026	0.66	9.1	231	100/500**	100/bag	7.0	3.2	
AE3178	SS	3/8	10	36.0	914	0.026	0.66	11.0	280	100/500**	100/bag	8.3	3.8	
AE8638	SS	5/8	16	12.0	305	0.044	1.1	3.4	86	200/800**	100/bag	5.6	2.5	
AE8648	SS	5/8	16	18.0	457	0.044	1.1	5.4	137	200/800**	100/bag	7.6	3.5	
AE8658	SS	5/8	16	24.0	610	0.044	1.1	7.3	185	200/800**	100/bag	9.7	4.4	
AE8668	SS	5/8	16	30.0	762	0.044	1.1	9.1	231	200/800**	100/bag	11.9	5.4	
AE8678	SS	5/8	16	36.0	914	0.044	1.1	11.0	280	200/800**	100/bag	13.9	6.4	

**单层/双层缠绕
材料厚度包括尼龙 11 涂层 - 内层金属无涂层时的厚度为: 1/4" 和 3/8" 带宽, 0.015"; 5/8" 带宽, 0.020"。



Multi-Lok 扣带



AE2018 钩式拉紧器



BAND-IT 扣带

UL 认证

Self-Lok 扣带

型号	材料*	宽度		长度		厚度		内径 单层缠绕		最小环绕 张力强度 (磅)	数量	重量		紧带机
		In	mm	In	mm	In	mm	In	mm			Lbs	Kg	
K01199	304 SS	3/16	5	5.4	137	0.010	0.25	1.0	25	150	100/bag	0.4	0.2	K50289
K01299	304 SS	3/16	5	8.4	213	0.010	0.25	2.0	51	150	100/bag	0.5	0.2	or by hand
K01399	304 SS	3/16	5	10.9	276	0.010	0.25	2.7	69	150	100/bag	0.7	0.3	
K01499	304 SS	3/16	5	14.9	378	0.010	0.25	4.0	102	150	100/bag	0.9	0.5	
K01599	304 SS	3/16	5	20.9	530	0.010	0.25	6.0	152	150	100/bag	1.2	0.6	
K01699	304 SS	3/16	5	27.4	695	0.010	0.25	8.0	203	150	50/bag	0.8	0.4	
K01799	304 SS	3/16	5	33.4	848	0.010	0.25	10.0	254	150	50/bag	1.0	0.5	
K01899	304 SS	3/16	5	42.4	1076	0.010	0.25	12.0	305	150	50/bag	1.2	0.6	
K01999	304 SS	3/16	5	47.4	1203	0.010	0.25	14.0	356	150	50/bag	1.3	0.6	
K04199	316 SS	3/16	5	5.4	137	0.010	0.25	1.0	25	150	100/bag	0.4	0.2	
K04299	316 SS	3/16	5	8.4	213	0.010	0.25	2.0	51	150	100/bag	0.5	0.3	
K04399	316 SS	3/16	5	10.9	276	0.010	0.25	2.7	69	150	100/bag	0.7	0.4	
K04499	316 SS	3/16	5	14.9	378	0.010	0.25	4.0	102	150	100/bag	0.9	0.5	
K04599	316 SS	3/16	5	20.9	530	0.010	0.25	6.0	152	150	100/bag	1.2	0.6	
K04699	316 SS	3/16	5	27.4	695	0.010	0.25	8.0	203	150	50/bag	0.8	0.4	
K04799	316 SS	3/16	5	33.4	848	0.010	0.25	10.0	254	150	50/bag	1.0	0.5	
K04899	316 SS	3/16	5	42.4	1076	0.010	0.25	12.0	305	150	50/bag	1.2	0.6	
K04999	316 SS	3/16	5	47.4	1203	0.010	0.25	14.0	356	150	50/bag	1.3	0.6	



K50289 Ball-Lok™ 或 Self-Lok 手动紧带机



Self-Lok 扣带

*BAND-IT 保留用抗腐蚀和（或）机械性能相当或更好材料替换的权利。

UL 和 DNV 认证

Tie-Lok 扣带

型号	材料*	宽度		长度		厚度		内径 单层缠绕		最小环绕 张力强度 (磅)	数量	重量		紧带机
		In	mm	In	mm	In	mm	In	mm			Lbs	Kg	
AS2119	304 SS	1/4	6	10.0	254	0.015	0.38	2	51	250	100/bag	1.2	0.6	A92079
AS2129	304 SS	1/4	6	16.5	419	0.015	0.38	4	102	250	100/bag	1.8	0.9	IT1000
AS2139	304 SS	1/4	6	22.5	572	0.015	0.38	6	152	250	100/bag	2.6	1.2	
AS2149	304 SS	1/4	6	29.0	737	0.015	0.38	8	203	250	100/bag	3.3	1.5	
AS2159	304 SS	1/4	6	35.0	889	0.015	0.38	10	254	250	100/bag	3.9	1.8	
AS4119	316 SS	1/4	6	10.0	254	0.015	0.38	2	51	250	100/bag	1.2	0.6	A92079
AS4129	316 SS	1/4	6	16.5	419	0.015	0.38	4	101	250	100/bag	1.8	0.9	IT1000
AS4139	316 SS	1/4	6	22.5	572	0.015	0.38	6	152	250	100/bag	2.6	1.2	
AS4149	316 SS	1/4	6	29.0	737	0.015	0.38	8	203	250	100/bag	3.3	1.5	
AS4159	316 SS	1/4	6	35.0	889	0.015	0.38	10	254	250	100/bag	3.9	1.8	
AS6219	304 SS	3/8	10	7.2	184	0.020	0.51	1.5	40	350	100/bag	1.9	0.9	IT6000
AS6229	304 SS	3/8	10	10.0	254	0.020	0.51	2	51	350	100/bag	2.6	1.2	
AS6239	304 SS	3/8	10	16.0	406	0.020	0.51	4	101	350	100/bag	3.9	1.8	
AS6249	304 SS	3/8	10	22.5	572	0.020	0.51	6	152	350	100/bag	5.3	2.4	
AS6259	304 SS	3/8	10	29.0	737	0.020	0.51	8	203	350	100/bag	6.7	3.1	



A92079 Tie-Lok II 紧带机



Tie-Lok 扣带

UL, CE 和 DNV 认证

小型 Tie-Lok 扣带

型号	材料*	宽度		长度		厚度		内径 单层缠绕		最小环绕 张力强度 (磅)	数量	重量		紧带机
		In	mm	In	mm	In	mm	In	mm			Lbs	Kg	
AS2219	304 SS	0.177	5	7.0	165	0.015	0.38	1	25	100	100/bag	0.7	0.3	A91079
AS2229	304 SS	0.177	5	10.0	254	0.015	0.38	2	51	100	100/bag	0.9	0.4	IT0750
AS2239	304 SS	0.177	5	16.0	406	0.015	0.38	4	102	100	100/bag	1.4	0.7	
AS2249	304 SS	0.177	5	22.5	572	0.015	0.38	6	152	100	100/bag	1.9	0.9	
AS2259	304 SS	0.177	5	29.0	737	0.015	0.38	8	203	100	100/bag	2.4	1.1	
AS4219	316 SS	0.177	5	7.0	165	0.015	0.38	1	25	100	100/bag	0.7	0.3	
AS4229	316 SS	0.177	5	10.0	254	0.015	0.38	2	51	100	100/bag	0.9	0.4	
AS4239	316 SS	0.177	5	16.0	406	0.015	0.38	4	102	100	100/bag	1.4	0.7	
AS4249	316 SS	0.177	5	22.5	572	0.015	0.38	6	152	100	100/bag	1.9	0.9	
AS4259	316 SS	0.177	5	29.0	737	0.015	0.38	8	203	100	100/bag	2.4	1.1	



A91079 小型 Tie-Lok II 紧带机

CE 认证

Ultra-Lok 扣带

型号	材料*	宽度		长度		厚度		内径 单层缠绕		最小环绕 张力强度 (磅)	数量	重量		紧带机
		In	mm	In	mm	In	mm	In	mm			Lbs	Kg	
AU2029	201 SS	1/4	6	8	203	0.015	0.38	1.5	38	400	100/bag	1.0	0.5	A94079
AU2039	201 SS	1/4	6	10	254	0.015	0.38	2.5	63	400	100/bag	1.2	0.6	IT3000
AU2049	201 SS	1/4	6	12	305	0.015	0.38	3.0	76	400	100/bag	1.4	0.7	
AU2059	201 SS	1/4	6	14	356	0.015	0.38	3.8	96	400	100/bag	1.6	0.8	
AU2069	201 SS	1/4	6	16	406	0.015	0.38	4.5	114	400	100/bag	1.9	0.9	
AU2079	201 SS	1/4	6	19	483	0.015	0.38	5.4	137	400	100/bag	2.2	1.0	
AU2089	201 SS	1/4	6	24	610	0.015	0.38	7.0	177	400	100/bag	2.7	1.3	
AU2099	201 SS	1/4	6	29	737	0.015	0.38	8.0	215	400	100/bag	3.3	1.5	
AU2159	201 SS	1/4	6	35	889	0.015	0.38	10.5	266	400	100/bag	3.9	1.8	



A94079 Ultra-Lok 紧带机



Ultra-Lok 扣带