



型号规格 MODEL AND SPEC

| | | | |
|---|--------------------|--|---------------------------|
| A | 平面法兰 plane flange | | 法兰密封面 flange sealing face |
| B | 凸面法兰 convex flange | | |
| T | 透光式 transparent | | 基本形式 basic type |
| R | 反射式 reflective | | |
| | □□ | 公称压力数字 nominal pressure class | 工作压力 operating pressure |
| | - | I 碳钢 carbon steel | 材质 material |
| | | II 不锈钢 stainless steel | |
| | | III 碳钢 + 不锈钢 (仅用于R6和R型) C.S+S.S. (just for R6and R type) | |
| | | Z 附加蒸汽夹套 annexed with heating jacket | 附加装置 annex |
| | | ∅L=□□□□ 测量范围 measuring range, 单位: mm | |

液面计规定标记 LEVEL GAUGE SPECIFICATION AND MARK

| 名称 name | 型号 model | 规格 specification | 标准号 mark number | 备注 remark |
|------------------------------|--------------------------------------|----------------------------------|--|---|
| 液面计 level gauge | A(B) T25-I, II A(B) T25-I Z, II Z | L= 500, 800, 1100, 1400, 1700 | HG5 -1364 -80 | 平面法兰 A 按HGJ46-91 DN20 PN2.5MPa 制造 凸面法兰 B 按HGJ46-91 DN20 PN2.5MPa 制造 工作压力 operating pressure: 2.5MPa |
| | BT64-I, II BT64-I Z, II Z | L= 500, 800, 1100, 1400, 1700 | HG5 -1365 -80 | 凸面法兰 B 按HGJ47-91 DN20 PN6.3MPa 制造 工作压力 operating pressure: 6.3MPa |
| | BR40-I, II BR40-I Z, II Z | L= 500, 800, 1100, 1400, 1700 | HG5 -1366 -80 | 凸面法兰 B 按HGJ47-91 DN20 PN4.0MPa 制造 工作压力 operating pressure: 4.0MPa |
| | R6 -III | 304 | HG5 -1367 -80 | 工作压力 operating pressure: 0.6MPa |
| | R6 - I, II | 304 | HG5 -1368 -80 | |
| | R -III | 304 | HG5 -1369-80 | |
| | R -I, II | 304 | HG5 -1370-80 | |
| | BT40-I, II BT40-I Z, II Z | L= 500, 800, 1100, 1400, 1700 | HG5 -1366-80 (派生系列) | 凸面法兰 B 按HGJ47-91 DN20 PN4.0MPa 制造 工作压力 operating pressure: 4.0MPa |
| | A(B) R25-I, II A(B) R25-I Z, II Z | L= 500, 800, 1100, 1400, 1700 | HG5 -1364-80 (派生系列) | 凸面法兰 B 按HGJ47-91 DN20 PN2.5MPa 制造 工作压力 operating pressure: 2.5MPa |
| BR64-I, II BR64-I Z, II Z | L= 500, 800, 1100, 1400, 1700 | HG5 -1365-80 (派生系列) | 凸面法兰 B 按HGJ47-91 DN20 PN6.3MPa 制造 工作压力 operating pressure: 6.3MPa | |

标记示例: mark example

- 透光式玻璃板液面计, 平面法兰, 工作压力2.5MPa, 材质不锈钢, 带伴热夹套, 测量范围800mm.
标记Marking: AT25- II Z/L=800mm HG5-1364-80.
Transparent glass plate liquid level gauge, plane flange, operating pressure 2.5MPa, material stainless steel, with heating jacket, and measuring range 800mm.
- 反射式玻璃板液面计, 凸面法兰, 工作压力6.4 MPa, 材质碳钢, 测量范围1700mm
标记Marking: BR64-I/L=1700mm HG5-1365-80
(派生系列 derived series)
Reflex glass plate liquid level gauge, raised face flange, operating pressure 6.4MPa, material carbon steel, with heating jacket, and measuring range 1700mm.

订货须知 ORDER INFORMATION

型号规格 model and spec
工作压力、温度 operating pressure and temperature
测量范围 measuring range
材质 material
特殊要求协商 special requests need consulted
是否配套供应容器上法兰、螺栓、螺母、阀门及密封垫圈等配件。
Accessories such as vessel flange, bolts, nuts, valves and sealing gasket.