



型号规格 MODELS AND SPEC

YSZK-110	标准型, 干式陶瓷压力变送器 standard		结构形式 structure	316L, 氧化铝陶瓷 alumina ceramic		接液材质 contacting material		
YSZK-120	钛/蓝宝石-硅压力变送器 Ti/sapphire-silicon			钛 Ti, 316L				
YSZK-130	扩散硅压力变送器 diffused silicon			316L				
	G	表压 gauge pressure				测量方式 measurement form		
	A	绝对压力 absolute pressure						
	C	差压 differential pressure						
		D1	0~4kPa	D2	0~6kPa	D3	0~10kPa	测量范围 measuring range
		D4	0~16kPa	D5	0~20kPa	D6	0~25kPa	
		D7	0~40kPa	D8	0~60kPa	E1	0~100kPa	
		E2	0~160kPa	E3	0~200kPa	E4	0~250kPa	
		E5	0~400kPa	F1	0~0.6MPa	F2	0~1.0MPa	
		F3	0~1.6MPa	F4	0~2.0MPa	F5	0~2.5MPa	
		F6	0~4.0MPa	F7	0~6.0MPa	H1	0~10MPa	
		H2	0~30MPa	H3	0~60MPa	H4	0~100MPa	
		H5	0~160MPa	C1	-2~2kPa	C2	-5~5kPa	
		C3	-10~10kPa	C4	-20~20kPa	C5	-50~50kPa	
		不注	标准型螺纹连接 M20×1.5 阳螺纹 standard type M20×1.5 male thread				过程连接 process connection	
		1	G1/2" 阳螺纹 male thread	2	G1/2" 阴螺纹 female thread			
		3	1/2"-14NPT 阳螺纹 male thread	4	1/2"-14NPT 阴螺纹 female thread			
		5	单平法兰 single flat flange			DN50 PN1.0/40		
		6	单插法兰 single inserting flange	-□	插入长度 inserting length, mm			
		7	卫生型, 符合GMP标准和3-A标准 DN32 Tri-clamp					
		8	卫生型, 符合GMP标准和3-A标准 DN50 Tri-clamp					
		9	特殊连接 用户指定 special connection specified by user					
		D	隔爆型 explosion-proof type					选项 options
		E	本安型 intrinsically safe type					
		B	配截止泄放阀 with cut-off release valve					
		L	LED数字显示 digit indication					
		H	智能型, 采用HART通讯协议 intelligent type with HART protocol					
		T	高温型 high temperature type					
		F	防腐型, 内衬聚四氟乙烯 corrosion proof type with PTFE lining					
		S	小巧型 cabinet type					
		J	支架安装 bracket mounting					
		/	出厂时标定量程 calibrated range					

标记示例 e.g.: YSZK-110GF4EB/0~1.8MPa 表示标准型, 压力变送器, 测量方式为表压力, 测量范围0~2.0MPa, 过程连接M20×1.5, 本安型, 配专用压力变送器截止泄放阀, 产品出厂时根据用户指定, 标定量程0~1.8MPa。
standard pressure transmitter for gauge pressure, measuring range is 0~2.0MPa, process connection is M20×1.5, intrinsically safe type, with special cut-off release valve, and calibrated range is 0~1.8MPa according to user.