



沪制02240183



## 型号规格 MODEL SPECIFICATION

电极编号 electrode No.	电极形式和典型应用 electrode mode and typical application	最大测量 范围 max measuring range	工作温度和工作压力 operating temperature and pressure	电极直径和材质 electrode diameter and material	安装连接形式 installation and connection mode
2	耐腐蚀型, 用于腐蚀性液体、有机酸。 不能用于氢氟酸、研磨性浆体、氯化铁 corrosion resistant type for corrosive liquids and organic acids, not for hydrofluoric acid, rubbing slurries and chloridized iron	5.8m	38°C/6.9MPa 149°C/3.45MPa	13.7mm/FEP	3/4" NPT
6	高强度型, 用于浆体, 盐溶液。 不能用于酮类、强腐蚀性液体 high rugged type for slurries and salt solutions, not for ketones and strong corrosive liquids	6.1m	38°C/6.9MPa 121°C/3.45MPa	21.3mm/X	1" NPT
7	高温型, 用于搅拌液体、高温液体 不能用于氢氟酸、苯乙烯单体、丁二烯单体 high temperature type for churned liquids and high temperature liquids, not for hydrofluoric acid, cinnamene monomer and butadiene monomer	4.3m	38°C/6.9MPa 232°C/3.45MPa	19mm/TFE	3/4" NPT
9	标准型: 用于污水、有机酸。 不能用于氢氟酸、氯化铁 standard type for sewage and organic acid, not for hydrofluoric acid and chloridized iron	6.1m	38°C/6.9MPa 149°C/3.45MPa	9.5mm/TFE	3/4" NPT
13	柔性带锤型: 用于长量程液体、浆体或颗粒, 重锤或底锚固定。 不能用于酮类、强腐蚀性液体 flexible type with weight for long range liquids, slurries or granulars, weight or bottom anchor fixed, and not for ketones and strong corrosive liquids	30m	38°C/6.9MPa 121°C/3.45MPa	7.9mm/X柔性	3/4" NPT
16	带笼式参考极: 用于绝缘液体如植物油、燃油、MEK和其它溶剂。 不能用于氢氟酸、苯乙烯单体、丁二烯单体 caged reference electrode type for insulated liquids such as vegetable oils, fuels, MEK and other solutions, not for hydrofluoric acid, cinnamene monomer and butadiene monomer	6.1m	38°C/6.9MPa 149°C/3.45MPa	42mm/ 316SS和TFE	1 1/2" NPT
17	带PFA贴面全密封法兰: 用于危险性液体或昂贵液、渗透性液体、强腐蚀性液体。 不能用于氢氟酸、发烟硫酸 PFA affixed fully sealing flange type for hazardous liquids or costly liquids, infiltrative liquids and strong corrosive liquids, not for hydrofluorid acid and oleum	6.1m	38°C/6.9MPa 177°C/3.45MPa	9.5mm/PFA	法兰 flange
20	316SS和TFE组合电极: 用于长量程绝缘液体或颗粒、沥青、液态硫、油墨 16SS and TFE combined electrode type for long range insulated liquids or granulars, bitumen, liquid sulfur and printing ink	61m	232°C/常压	4.8mm/316SS	1" NPT
25	标准长量程: 用于水、酸、碱、酒精 standard range for waters, acids, alkalis and alcohols	30m	38°C/6.9MPa 149°C/3.45MPa	2.7mm/ PFA柔性	3/4" NPT
31	带杆式参考极: 用于非金属容器内的水、酸、浓度小于10%的碱液。 不能用于氢氟酸、浓度大于30%的盐酸 pole reference electrode type for waters, acids, concentration less than 10% alkalis in nonmetal containers, not for hydrofluoric acid and concentration more than 30% hydrochloric acid	6.1m	38°C/6.9MPa 149°C/3.45MPa	9.5mm/ 哈氏C和TFE	TFE 镀面 法兰 mosaic flange